

COMSOL Multiphysics

Application Programming Guide



Application Programming Guide

© 1998-2019 COMSOL

Protected by patents listed on www.comsol.com/patents, and U.S. Patents 7,519,518; 7,596,474; 7,623,991; 8,457,932; 8,954,302; 9,098,106; 9,146,652; 9,323,503; 9,372,673; 9,454,625; and 10,019,544. Patents pending.

This Documentation and the Programs described herein are furnished under the COMSOL Software License Agreement (www.comsol.com/comsol-license-agreement) and may be used or copied only under the terms of the license agreement.

COMSOL, the COMSOL logo, COMSOL Multiphysics, COMSOL Desktop, COMSOL Compiler, COMSOL Server, and LiveLink are either registered trademarks or trademarks of COMSOL AB. All other trademarks are the property of their respective owners, and COMSOL AB and its subsidiaries and products are not affiliated with, endorsed by, sponsored by, or supported by those trademark owners. For a list of such trademark owners, see www.comsol.com/trademarks.

Version: COMSOL 5.5

Contact Information

Visit the Contact COMSOL page at www.comsol.com/contact to submit general inquiries, contact Technical Support, or search for an address and phone number. You can also visit the Worldwide Sales Offices page at www.comsol.com/contact/offices for address and contact information.

If you need to contact Support, an online request form is located at the COMSOL Access page at www.comsol.com/support/case. Other useful links include:

- Support Center: www.comsol.com/support
- Product Download: www.comsol.com/product-download
- Product Updates: www.comsol.com/support/updates
- COMSOL Blog: www.comsol.com/blogs
- Discussion Forum: www.comsol.com/community
- Events: www.comsol.com/events
- COMSOL Video Gallery: www.comsol.com/video
- Support Knowledge Base: www.comsol.com/support/knowledgebase

Part number: CM020012

Contents

ln ⁻	troduction	7
Sy	yntax Primer	8
	Data Types	8
	Declarations	
	Built-in Elementary Math Functions	. 15
	Control Flow Statements	. 15
lπ	nportant Programming Tools	. 18
	Ctrl+Space for Code Completion	.18
	Recording Code	. 20
	Methods Called from the Model Builder	. 23
	Global Methods, Form Methods, and Local Methods	.23
	Method Names	. 24
ln ⁻	troduction to the Model Object	. 25
	Model Object Tags	. 25
	Creating a Model Object	. 28
	Creating Model Components and Model Object Nodes .	. 28
	Get and Set Methods for Accessing Properties	. 29
	Parameters and Variables.	. 34
	Unary and Binary Operators in the Model Object	. 36
	Geometry	. 37
	Mesh	. 39
	Physics	.40
	Material	
	Study	. 44
	Results	48

Multiphysics
Working with Model Objects
The Model Object Class Structure53
The Application Object55
Shortcuts
Accessing the Application Object57
The Name of User Interface Components57
Important Classes
Get and Set Methods for the Color of a Form Object 58
General Properties59
The Main Application Methods60
Main Window61
Form62
Form Object
ltem83
Data Source84
Method Class89
Form, Form Object, and Item List Methods
The Built-in Method Library for the Application Builder. \dots 9 I
Model Utility Methods
License Methods93
File Methods
Operating System Methods
Email Methods107
Email Class Methods
GUI-Related Methods
GUI Command Methods
Debug Methods

	Methods for External C Libraries	
	Progress Methods	
	Date and Time Methods	
	Conversion Methods	
	Array Methods	
	String Methods	
	Collection Methods	
	Model Builder Methods for Use in Add-ins	
ı	Programming Examples	
	Running the Examples150	
	Visualization Without Solution Data: Grid Data Sets150	
	Visualization of Points, Curves, and Surfaces152	
	Reading and Writing Data to File	
	Converting Interpolation Curve Data	
	Plotting Points on a Parametric Surface	
	Using Selections for Editing Geometry Objects 189	
	Recursion and Recursively Defined Geometry Objects194	
	Mesh Information and Statistics	
	Accessing Higher-Order Finite Element Nodes 199	
	Accessing System Matrices and Vectors201	
	Using Built-In Methods from an External Java Library 205	
	Measuring the Java Heap Space Memory206	
	Time-Limited and Hardware-Locked Applications206	

Introduction

This book is a guide to writing code for COMSOL[®] models and applications using the Method editor. The Method editor is an important part of the Application Builder and is available in the COMSOL Desktop[®] environment in the Windows[®] version of COMSOL Multiphysics. For an introduction to using the Application Builder and its Form editor and Method editor, see the book *Introduction to Application Builder*.

Writing a method is needed when an action is not already available in the standard run commands associated with functionality in the model tree nodes of the Model Builder. A method may, for example, contain loops, process inputs and outputs, and send messages and alerts to the user of the application.

In the Model Builder, the model tree is a graphical representation of the data structure that represents a model. This data structure is called the model object and stores the state of the underlying COMSOL Multiphysics model that is embedded in an application.

The contents of the application tree in the Application Builder is accessed through the application object, which is an important part of the model object. You can write code using the Method editor to directly access and change the user interface of a running application, for example, to update button text, icons, colors, and fonts.

In the COMSOL Multiphysics environment, you use the Java® programming language to write methods, which means that you can utilize the extensive collection of Java® libraries. In addition to the Java® libraries, the Application Builder includes a built-in library for building applications and modifying the model object. A number of tools and resources are available to help you automatically create code for methods. For more information on autogeneration of code, see the book *Introduction to Application Builder*.

This book assumes no prior knowledge of the Java[®] programming language. However, some familiarity with a programming language is helpful.

Syntax Primer

If you are not familiar with the Java[®] programming language, read this section to quickly get up to speed with its syntax. When creating applications, it is useful to know the basics of Java such as how to use the if, for, and while control statements. The more advanced aspects of Java will not be covered in this book. For more detail, see any dedicated book on Java programming or one of the many online resources. You can also learn a lot by reviewing the methods in the example applications available in the Application Libraries.

Data Types

PRIMITIVE DATA TYPES

Java contains eight primitive data types, listed in the table below.

DATA TYPE	DESCRIPTION	NUMBER OF BYTES	EXAMPLE
byte	Integer between -127 and 128	1	byte b=33;
char	Unicode character; integer between 0 and 65535 (0 and 2 ¹⁶ -I)	2	char c='a'; char c=97;
short	Integer between -32768 and 32767 (-2 ¹⁵ -1 and 2 ¹⁵ -1)	2	short s=-1025;
int	Integer between -2 ³¹ and 2 ³¹ -1	4	int i=15;
long	Integer between -2 ⁶³ and 2 ⁶³ -1	8	long I=15;
float	32-bit floating point number	4	float f =4.67f;
double	64-bit floating point number	8	double d=4.67;
boolean	Boolean with values false or true	N/A	boolean b=true;

Other data types such as strings are classes, which are also referred to as composite data types.

In methods, you can use any⁵ of the primitive or composite data types available in Java and the Java libraries. Many of the Application Builder built-in methods make use of primitive or composite data types. For example, the timeStamp() method provides a long integer as its output.

ASSIGNMENTS AND LITERALS

A few examples of using literals in assignments are:

```
int i=5; // initialize i and assign the value 5 double d=5.0; // initialize d and assign the value 5.0 boolean b=true; // initialize b and assign the value true
```

The constants 5, 5.0, and true are literals. Java distinguishes between the literals 5 and 5.0, where 5 is an integer and 5.0 is a double (or float).

Unary and Binary Operators in Methods (Java Syntax)

You can perform calculations and operations using primitive data types just like with many other programming languages. The table below describes some of the most common unary and binary operators used in Java code.

PRECEDENCE LEVEL	SYMBOL	DESCRIPTION
1	++	unary: postfix addition and subtraction
2	++ + - !	unary: addition, subtraction, positive sign, negative sign, logical not
3	* / %	binary: multiplication, division, modulus
4	+ -	binary: addition, subtraction
5	!	Logical NOT
6	< <= > >=	comparisons: less than, less than or equal, greater than, greater than or equal
7	== !=	comparisons: equal, not equal
8	&&	binary: logical AND
9	П	binary: logical OR
10	?:	conditional ternary
П	= += -= *= /= %= >>= <<= &= ^= =	assignments
12	,	element separator in lists

TYPE CONVERSIONS AND TYPE CASTING

When programming in Java, conversion between data types is automatic in many cases. For example, the following lines convert from an integer to a double:

```
int i; // initialize i
double d; //initialize d
i=41;
d=i; // the integer i is assigned to the double d and d is 41.0
```

However, the opposite will not work automatically (you will get a compilation error). Instead you can use explicit type casting as follows:

```
int i; // initialize i
double d; //initialize d
d=41.0;
i=(int) d; // the double d is assigned to the integer i and i is 41
```

You can convert between integers and doubles within arithmetic statements in various ways, however you will need to keep track of when the automatic type conversions are made. For example:

```
int i; // initialize i
double d; //initialize d
i=41;
d=14/i; // d is 0
```

In the last line, 14 is seen as an integer literal and the automatic conversion to a double is happening after the integer division 14/41, which results in 0.

Compare with:

```
int i; // initialize i
double d; //initialize d
i=41;
d=14.0/i; // d is 0.3414...
```

In the last line, 14.0 is seen as a double literal and the automatic conversion to a double is happening before the division and is equivalent to 14.0/41.0.

You can take charge over the type conversions with explicit casting by using the syntax (int) or (double):

```
int i; // initialize i
double d,e; //initialize d and e
i=41;
d=((int) 14.0)/i; // d is 0
e=14/((double) i); // e is 0.3414...
```

Strings and Java Objects

The String data type is a Java object. This is an example of how to declare a string variable:

```
String a="string A";
```

When declaring a string variable, the first letter of the data type is capitalized. This is a convention for composite data types (or object-oriented classes).

After you have declared a string variable, a number of methods are automatically made available that can operate on the string in various ways. Two such methods are concat and equals as described below, but there are many more methods available in the String class. See the online Java documentation for more information.

Concatenating Strings

To concatenate strings, you can use the method concat as follows:

```
String a="string A";
String b=" and string B";
a.concat(b);
```

The resulting string a is "string A and string B". From an object-oriented perspective, the variable a is an instance of an object of the class String. The method concat is defined in the String class and available using the a.concat() syntax.

Alternatively, you can use the + operator as follows:

```
a=a+b;
which is equivalent to:
    a="string A" + " and string B";
and equivalent to:
    a="string A" + " " + "and string B";
```

where the middle string is a string with a single whitespace character.

Comparing Strings

Comparing string values in Java is done with the equals method and not with the == operator. This is due to the fact that the == operator compares whether the strings are the same when viewed as class objects and does not consider their values. The code below demonstrates string comparisons:

```
boolean streq=false;
String a="string A";
String b="string B";
streq=a.equals(b);
// In this case streq==false
streq=(a==b);
// In this case streq==false
b="string A";
streq=a.equals(b);
// In this case streq==true
```

Special Characters

If you would like to store, for example, a double quotation mark or a new line character in a string you need to use special character syntax preceded by a backslash (\). The table below summarizes some of the most important special characters.

SPECIAL CHARACTER	DESCRIPTION
\ '	Single quotation mark
/ "	Double quotation mark

SPECIAL CHARACTER	DESCRIPTION
11	Backslash
\t	Tab
\b	Backspace
\r	Carriage return
\f	Formfeed
\n	Newline

Note that in Windows the new line character is the composite \r\n whereas in Linux and macOS \n is used.

The example below shows how to create a string in Windows that you later on intend to write to file and that consists of several lines.

```
String contents = "# Created by me\r\n"
+"# Version 1.0 of this file format \r\n"
+"# Body follows\r\n"
+"0 1 \r\n"
+"2 3\r\n"
+"4 5\r\n";
```

The string is here broken up into several lines in the code for readability. However, the above is equivalent to the following:

```
String contents = "# Created by me\r\n# Version 1.0 of this file format \r\n# Body follows\r\n0 1 \r\n2 3\r\n4 5\r\n";
```

which is clearly less readable.

ARRAYS

In the application tree, the **Declarations** node directly supports 1D and 2D arrays of type string (String), integer (int), Boolean (boolean), or double (double). A 1D array may be referred to as a vector and a 2D array referred to as a matrix, provided that the array is rectangular. A non-rectangular array is called jagged or ragged. In methods, you can define higher-dimensional arrays as well as arrays of data types other than string, integer, Boolean, or double.

ID Arrays

If you choose not to use the **Declarations** node to declare an array, then you can use the following syntax in a method:

```
double dv[] = new double[12];
```

This declares a double array of length 12.

The previous line is equivalent to the following two lines:

```
double dv[];
dv = new double[12];
```

When a double vector has been declared in this way, the value of each element in the array will be zero.

To access elements in an array you use the following syntax:

```
double e;
e=dv[3]; // e is 0.0
```

Arrays are indexed starting from 0. This means that dv[0] is the first element of the array in the examples above, and dv[11] is the last element.

You can simultaneously declare and initialize the values of an array by using curly braces:

```
double dv[] = \{4.1, 3.2, 2.93, 1.3, 1.52\};
```

In a similar way you can create an array of strings as follows:

```
String sv[] = {"Alice", "Bob", "Charles", "David", "Emma"};
```

2D Arrays

2D rectangular arrays can be declared as follows:

```
double dm[][] = new double[2][3];
```

This corresponds to a matrix of doubles with 2 rows and 3 columns. The row index comes first.

You can simultaneously declare and initialize a 2D array as follows:

```
double dm[][] = \{\{1.32, 2.11, 3.43\}, \{4.14, 5.16, 6.12\}\};
```

where the value of, for example, dm[1][0] is 4.14. This array is a matrix since it is rectangular (it has same number of columns for each row). You can declare a ragged array as follows:

```
double dm[][] = \{\{1.32, 2.11\}, \{4.14, 5.16, 6.12, 3.43\}\};
```

where the value of, for example, dm[1][3] is 3.43.

Copying Arrays

For copying arrays, the following code:

```
for(int i1=0;i1<=11;i1++) {
  for(int i2=0;i2<=2;i2++) {
    input_array[i1][i2]=init_input_array[i1][i2];
  }
}</pre>
```

is not equivalent to the line:

```
input_array=init_input_array;
```

since the last line will only copy by reference.


Instead, you can use the copy method as follows:

```
input_table = copy(init_input_table);
```

which allocates a new array and then copies the values.

Declarations

Variables defined in the **Declarations** node in the application tree are directly available as global variables in a method and need no further declarations.



Variables declared in methods will have local scope unless you specify otherwise. The **Declarations** node directly supports integers (int), doubles (double), and Booleans (boolean). In addition, strings are supported (see "Strings and Java Objects" on page 10). In the **Declarations** node, variables can be scalars, 1D arrays, and 2D arrays.

To simplify referencing form objects as well as menu, ribbon, and toolbar items by name, you can create shortcuts with a custom name. These names are available in the **Declarations** node under **Shortcuts**. They are directly available in methods along with the other global variables defined under **Declarations**. For more information on shortcuts, see "Shortcuts" on page 55.

FORM DECLARATIONS

Variables can also be defined as **Form Declarations** under each respective form node in the application tree.



Form declarations can be of the types **Scalar**, **Array 1D**, **Array 2D** and **Choice List**. Global declarations are exposed to all components of the application whereas form declarations are only exposed to the form that they are defined in and the form objects within that form. Form declarations are used to limit the scope of variables and thereby logically separate the different parts of an application.

Built-in Elementary Math Functions

Elementary math function for use in methods are available in the Java math library. Some examples:

```
double a = Math.PI; // the mathematical constant pi double b = Math.sin(3*a); // trigonometric sine function double c = Math.cos(4*a); // trigonometric cosine function double d = Math.random(); // random number uniformly distributed in [0,1) double e = Math.exp(2*a); // exponential function double f = Math.log(1+e); // natural base e logarithm double g = Math.pow(10,3) // power function double h = Math.log10(2.5); // base 10 logarithm double k = Math.sqrt(81.0); // square root
```

There are several more math functions available in the Java math library. For additional information, see any Java book or online resource.

Control Flow Statements

Java supports the usual control flow statements if-else, for, and while. The following examples illustrate some of the most common uses of control flow statements.

THE IF-ELSE STATEMENT

This is an example of a general if-else statement:

```
if(a<b) {
   alert("Value too small.");
} else {
   alert("Value is just right.");
}</pre>
```

Between curly braces {} you can include multiple lines of code, each terminated with a semicolon. If you only need one line of code, such as in the example above, this shortened syntax is available:

```
if(a<b)
  alert("Value too small.");</pre>
```

```
else
  alert("Value is just right.");
```

THE FOR STATEMENT

Java supports several different types of for statements. This example uses the perhaps most conventional syntax:

```
// Iterate i from 1 to N:
int N=10;
for (int i = 1; i <= N; i++) {
    // Do something
}</pre>
```

An alternative syntax is shown in the example on page 64 where the loop is over all form objects in a list of form objects:

```
for (FormObject formObject : app.form("form1").formObject()) {
   if ("Button".equals(formObject.getType())) {
      formObject.set("enabled", false);
   }
}
```

where the local iteration variable looped over is formObject of the type, or class, FormObject. The collection of objects, in this case app.form("form1").formObject(), can be an array or other types of lists of objects. Using this syntax, the iteration variable loops over all entries in the collection, from start to finish. Another example can be found on page 90.

THE WHILE STATEMENT

This example shows a while statement.

```
double t=0,h=0.1,tend=10;
while(t<tend) {
   //do something with t
   t=t+h;
}</pre>
```

For a more advanced example of a while statement, see "Creating and Removing Model Tree Nodes" on page 41.

Note that Java also supports do-while statements.

THE WITH STATEMENT

When writing methods in the Method editor, in addition to the standard Java control flow statement, there is also a with statement that is used to make Application Builder code more compact and easier to read. A simple example is shown below:

```
// Set the global parameter L to a fixed value
with(model.param());
```

```
set("L", "10[cm]");
endwith();
```

The code above is equivalent to:

```
model.param().set("L", "10[cm]");
```

In this case using the with statement has limited value since just one parameter is assigned but for multiple assignments readability increases. See "Parameters and Variables" on page 34 for an example with multiple assignments.

Note that the with statement is only available when writing code in the Method editor. It is not available when using the COMSOL API for use with Java[®]. You can turn off the use of with statements in the section for **Methods** in **Preferences**.

The method descr returns the variable description for the last parameter or variable in a with statement:

```
with(model.param());
  set("L", "10[cm]");
  String ds = descr("L");
endwith();
```

Assuming that the parameter description of the parameter L is Length. The string ds will have the value Length.

EXCEPTION HANDLING

An exception is an error that occurs at run time. The Java[®] programming language has a sophisticated machinery for handling exceptions and each exception generates an object of an exception class. The most common way to handle exceptions is by using try and catch, as in the example below.

```
double d[][] = new double[2][15];
try {
   d = readMatrixFromFile("common:///my_file.txt");
} catch (Exception e) {
   error("Cannot find the file my_file.txt.");
}
```

where an error dialog box is shown in case the file my_file.txt is not found in the application file folder common. See the Java[®] documentation for more information about using try and catch.


Important Programming Tools

The Application Builder includes several tools for automatically generating code. These tools include code completion, **Record Method**, **Record Code**, **Convert to New Method**, **Editor Tools**, **Language Elements**, and **Copy as Code to Clipboard**, and are described in the book *Introduction to Application Builder*. These utilities allow you to quickly get up and running with programming tasks even if you are not familiar with the syntax.

The following sections describes two of the most important tools: code completion using Ctrl+Space and **Record Code**. Using these tools will make you more productive, for example, by allowing you to copy-paste or auto-generate blocks of code.

Ctrl+Space for Code Completion


While typing code in the Method editor, the Application Builder can provide suggestions for code completions. The list of possible completions are shown in a separate completion list that opens while typing. In some situations, detailed information appears in a separate window when an entry is selected in the list. Code completion can always be requested with the keyboard shortcut Ctrl+Space. Alternatively Ctrl+/ can be used to request code completion, which is useful if Ctrl+Space is in use by the Windows operating system such as for certain languages. When accessing parts of the model object, you will get a list of possible completions, as shown in the figure below:



Select a completion by using the arrow keys to choose an entry in the list and double-click, or press the Tab or Enter key, to confirm the selection.

If the list is long, you can filter by typing the first few characters of the completion you are looking for.

For example, if you enter the first few characters of a variable or method name, and press Ctrl+Space, the possible completions are shown:



In the example above, only variables that match the string iv are shown. This example shows that variables local to the method also appear in the completion suggestions.

You can also use Ctrl+Space to learn about the syntax for the built-in methods that are not directly related to the model object. Type the name of the command and use Ctrl+Space to open a window with information on the various calling signatures available.




Additional information is also available in the form of tool tips that are displayed when hovering over the different parts of the code.

The Method editor also supports code completion for properties, including listing the properties that are available for a given model object feature node, and providing a list of allowed values that are available for a given property.

The figure below shows an example of code completion for the mesh element size property, where a list of the allowed values for the predefined element sizes is presented.



COMSOL Multiphysics and its add-on modules contain thousands of physics features that you can learn about by using, for example, **Record Code**, **Save as>Model File for Java**, and code completion. The figure below shows code completion for a particular feature in the Ray Optics Module.



Recording Code

Click the **Record Code** button in the **Code** section of the Method editor ribbon to record a sequence of operations that you perform using the model tree, as shown in the figure below.





Certain operations in the application tree can also be recorded, for example, code that changes the color of a text label in a running application may be generated.

To record a new method, click the **Record Method** button in the **Main** section of the Method editor ribbon.



While recording code, the COMSOL Desktop windows are surrounded by a red frame:






To stop recording code, click one of the **Stop Recording** buttons in the ribbon of either the Model Builder or the Application Builder.



By using **Data Access**, you can set the values of the **Heat transfer coefficient** and the **External temperature** properties of the busbar tutorial model used in the books *Introduction to COMSOL Multiphysics* and *Introduction to Application Builder*.



To generate similar code using **Record Code** (**Data Access** is not used when recording code), follow these steps:

- Create a simple application based on the busbar model (MPH file).
- In the Model Builder window, in the **Developer** tab, click **Record Method**, or with the Method editor open, click **Record Code**.
- Change the value of the **Heat transfer coefficient** to 5.
- Change the value of the **External temperature** to 300[K].
- Click Stop Recording.
- If it is not already open, open the method with the recorded code.

The resulting code is listed below:

```
with(model.physics("ht").feature("hf1"));
  set("h", "5");
  set("Text", "300[K]");
endwith();
```

In this case, the autogenerated code contains a with() statement in order to make the code more compact. For more information on the use of with(), see "The With Statement" on page 16.

To generate code corresponding to changes to the application object, use **Record Code** or **Record Method**, then go to the Form editor and, for example, change the appearance of a form object. The following code corresponds to changing the color of a text label from the default **Inherit** to **Blue**:

```
with(app.form("form1").formObject("textlabel1"));
  set("foreground", "blue");
endwith();
```

Built-in methods that changes the application object are only available when running applications and not when running methods from the Model Builder.

Use the tools for recording code to quickly learn how to interact with the model object or the application object. The autogenerated code shows you the names of properties, parameters, and variables. Use strings and string-number conversions to assign new parameter values in model properties. By using **Data Access** while recording, you can, for example, extract a parameter value using get, process its value in a method, and save it back into the model object using set. For more information on **Data Access**, see the *Introduction to Application Builder*.

Methods Called from the Model Builder

Methods called from the Model Builder directly modify the model object represented by the Model Builder in the current session. Using methods in this way can be used to automate modeling tasks that consist of several manual steps. For example, in a model with multiple studies, you can record code for the process of first computing Study 1; then computing Study 2, which may be based on the solution from Study 1; and so on.

To customize the workflow in the Model Builder you can create an add-in based on methods by using a **Method Call** or a **Settings Form**. For an introductory example of using methods from the Model Builder and for information on how to create add-ins, see the *Introduction to Application Builder*.

Global Methods, Form Methods, and Local Methods

There are global methods, form methods, and local methods. Global methods are displayed in the application tree and are accessible from all methods and form objects. Form methods are displayed in the application tree as child nodes to the

form it belongs to. A local method is associated with a form object or event and can be opened from the corresponding **Settings** window.

Global methods are exposed to all components of the application whereas form methods are only exposed to the form that they are defined in and the form objects within that form. You can use form methods to provide a logical separation of the different parts of an application.

Method Names

A method name has to be a text string without spaces. The string can contain letters, numbers, and underscores. Java® programming language keywords cannot be used. The name must not begin by a number (this is also true for the name of a form object, variable, and method.)

A global method cannot have the same name as a form method and vice versa. In addition, the following names are reserved:

- onDataChange
- · onPickingChanged
- focusGained
- focusLost
- onLoad
- onClose
- onStartup
- onShutdown
- onClick
- onEvent

Introduction to the Model Object

The model object is the data structure that stores the state of the COMSOL Multiphysics model. The model object contents are reflected in the COMSOL Desktop user interface by the structure of the Model Builder and its model tree. The model object is associated with a large number of methods for setting up and running sequences of operations such as geometry sequences, mesh sequences, and study steps. As an alternative to using the Model Builder, you can write programs in the Method editor that directly access and change the contents of the model object.

The model object methods are structured in a tree-like way, similar to the nodes in the model tree. The top-level methods just return references that support further methods. At a certain level the methods perform actions, such as adding data to the model object, performing computations, or returning data.

For a complete list of methods used to edit the model object, see the *Programming Reference Manual*. For an introduction to using the Model Builder, see the book *Introduction to COMSOL Multiphysics*.


The contents of the application tree in the Application Builder are accessed through the application object, which is an important part of the model object. You can write code using the Method editor to alter, for example, button text, icons, colors, and fonts in the user interface of a running application.

This section gives an overview of the model object. The section "The Application Object" on page 55 gives an overview of the application object.


Model Object Tags

In the model tree and when working with the model object from methods, tags are used as handles to different parts of the model object. These tags can also be

made visible in the Model Builder by first clicking the Model Builder toolbar menu **Model Tree Node Text** and then choosing **Tag**, as shown in the figure below.



The figures below show an example of a model tree without tags shown in the left figure and with tags shown in the right figure.






In code, the tags are referenced using double quotes. For example, in the following line

```
model.geom("geom1").create("r1", "Rectangle");
```

geom1 is a tag for a geometry object and r1 is a tag for a rectangle object. The following sections contain multiple examples of using tags to create and edit parts of a model object.

The option Name, available in the Model Tree Node Text menu in the Model Builder toolbar, represents the name used for scoping. The scope names are used to access the different parts of the model object. This is important, for example, when working with global variables for defining the constraints and objective functions for an optimization study. In the figure below, the variables mass, freq, and maxStress are referenced by scope names: comp1.mass, comp1.solid.freq, and comp1.maxStress.



Using scope names avoids name collisions in cases where there are multiple model components or multiple physics interfaces with identical variable names.

Creating a Model Object

If you create an application using the Model Builder and the Application Builder, then a model object model is automatically created the first time you enter the Model Builder. You may also create an embedded model with a call to the createModel method:

```
Model model = createModel("Model1");
```

The model tag Model1 is automatically created and may instead be Model2, Model3, and so on, to ensure a unique model tag (this depends on which model tags were used previously). Alternatively by not specifying the model tag a unique model tag is created automatically:

```
Model model = createModel();
```

When using the Model Wizard, the creation of the model tag is automatically handled.

When writing methods in the Method editor you can directly access the model object model without first calling createModel.

If you want to create additional model objects in the same application, then you need to call createModel or load a model object from file. For more information on working with several model objects, see the section "Working with Model Objects" on page 51.

Creating Model Components and Model Object Nodes

A model contains one or more model components. You create a model component as follows:

```
model.modelNode().create("comp1");
```

The component is given a definite spatial dimension when you create a geometry node:

```
model.geom().create("geom1", 2);
```

where the second argument can be 0, 1, 2, or 3, depending on the spatial dimension. In the example above, the spatial dimension is 2.

In addition to creating model components and geometry nodes, there are create methods for many of the nodes in the model tree.

Whether the geometry should be interpreted as being axisymmetric or not is determined by a Boolean property that you can assign as follows:

```
boolean makeaxi=true;
model.geom("geom1").axisymmetric(makeaxi);
```

The axisymmetric property is only applicable to models of spatial dimension 1 or 2.




Using the Model Wizard, if you first create a **Blank Model** and then add a component using the Model Builder, you will be prompted to choose the space dimension of the component. This operation will, in addition to creating a component, also create a geometry and mesh node. For example, selecting a 2D component corresponds to the following lines of code:

```
model.modelNode().create("comp1");
model.geom().create("geom1", 2);
model.mesh().create("mesh1", "geom1");
```

Get and Set Methods for Accessing Properties

The get and set methods are used to access and assign, respectively, property values in the different parts of the model object. To assign individual elements of a vector or matrix, the setIndex method is used. The property values can be of the basic data types: String, int, double, and boolean, as well as vectors or matrices of these types (1D or 2D arrays).

The get, set, and create methods (described in the previous section) are also accessible from the model tree by right-clicking and selecting **Copy as Code to Clipboard**.



THE GET METHODS

The family of get methods is used to retrieve the values of properties. For example, the getDouble method can be used to retrieve the value of the predefined element size property hauto for a mesh and store it in a variable hv:

```
double hv = model.mesh("mesh1").feature("size").getDouble("hauto")
```

See the section "Example Code" on page 32 below for more information on the property hauto.

The syntax for the family of get methods for the basic data types is summarized in the following table:

TYPE	SYNTAX	
String	getString(String name)	
String array	<pre>getStringArray(String name)</pre>	
String matrix	<pre>getStringMatrix(String name)</pre>	
Integer	<pre>getInt(String name)</pre>	
Integer array	getIntArray(String name)	
Integer matrix	<pre>getIntMatrix(String name)</pre>	
Double	<pre>getDouble(String name)</pre>	
Double array	getDoubleArray(String name)	
Double matrix	getDoubleMatrix(String name)	
Boolean	getBoolean(String name)	
Boolean array	getBooleanArray(String name)	
Boolean matrix	getBooleanMatrix(String name)	

All arrays are returned as copies of the data; writing to a retrieved array does not change the data in the model object. To change the contents of an array in the model object, use one of the methods set or setIndex.

Automatic type conversion is attempted from the property type to the requested return type.

THE SET METHOD

The syntax for assignment using the set method is exemplified by this line of code, which sets the title of a plot group pg1:

```
model.result("pg1").set("title", "Temperature T in Kelvin");
```

The first argument is a string with the name of the property, in the above example "title". The second argument is the value and can be a basic type as indicated by the table below.

TYPE	SYNTAX
String	set(String name,String val1)
String array	<pre>set(String name,new String[]{"val1","val2"})</pre>
String matrix	set(String name, new String[][]{{"1","2"},{"3","4"}})

TYPE	SYNTAX
Integer	set(String name,17)
Integer array	<pre>set(String name,new int[]{1,2})</pre>
Integer matrix	set(String name,new int[][]{{1,2},{3,4}})
Double	set(String name,1.3)
Double array	<pre>set(String name,new double[]{1.3,2.3})</pre>
Double matrix	set(String name, new double[][]{{1.3,2.3},{3.3,4.3}})
Boolean	set(String name,true)
Boolean array	<pre>set(String name,new boolean[]{true,false})</pre>
Boolean matrix	<pre>set(String name,new boolean[][]{{true, false},{false, false}})</pre>

Using the set method for an object returns the object itself. This allows you to append multiple calls to set as follows:

```
model.result("pg1").set("edgecolor", "black").set("edges", "on");
```

The previous line of code assigns values to both the edgecolor and edges properties of the plot group pg1 and is equivalent to the two lines:

```
model.result("pg1").set("edgecolor", "black");
model.result("pg1").set("edges", "on");
```

In this case, the set method returns a plot group object.

Automatic type conversion is attempted from the input value type to the property type. For example, consider a model parameter a that is just a decimal number with no unit. Its value can be set with the statement:

```
model.param().set("a", "7.54");
```

where the value "7" is a string. In this case, the following syntax is also valid: model.param().set("a",7.54);

THE SETINDEX METHOD

The setIndex method is used to assign a value to a 1D or 2D array element at a position given by one or two indices (starting from index 0).

The following line illustrates using setIndex with one index:

```
model.physics("c").feature("cfeq1").setIndex("f", "2.5", 0);
```

The following line illustrates using setIndex with two indices:

```
model.physics("c").feature("cfeq1").setIndex("c", "-0.1", 0, 1);
```

For the setIndex method in general, use one of these alternatives to set the value of a single element:

```
setIndex(String name,String value,int index);
setIndex(String name,String value,int index1,int index2);
```

The name argument is a string with the name of the property. The value argument is a string representation of the value. The indices start at 0, for example:

```
setIndex(name, value, 2)
```

sets the third element of the property name to value.

The setIndex method returns an object of the same type, which means that setIndex methods can be appended just like the set method.

If the index points beyond the current size of the array, then the array is extended as needed before the element at index is set. The values of any newly created intermediate elements are undefined.

The method setIndex and set can both be used to assign values in ragged arrays. For example, consider a ragged array with 2 rows. The code statements:

```
setIndex(name,{"1","2","3"},0);
setIndex(name,{"4","5"},1);
```

sets the first and second row of the array and are equivalent to the single statement:

```
set("name",new String[][]{{"1","2","3"},{"4","5"}});
```

METHODS ASSOCIATED WITH SET AND GET METHODS

For object types for which the set, setIndex, and get methods can be used, the following additional methods are available:

```
String[] properties();
returns the names of all available properties,
  boolean hasProperty(String name);
returns true if the feature has the named property,
  String[] getAllowedPropertyValues(String name);
returns the allowed values for named properties, if it is a finite set.
```

EXAMPLE CODE

The following code block can be used to warn an application's user of excessive simulation times based on the element size:


```
if (model.mesh("mesh1").feature("size").getDouble("hauto")<=3) {
  exp_time = "Solution times may be more than 10 minutes for finer element
  sizes.";
}</pre>
```

In the above example, getDouble is used to retrieve the value of the property hauto, which corresponds to the Element Size parameter Predefined in the Settings window of the Size node under the Mesh node. This setting is available when the Sequence type is set to User-controlled mesh, in the Settings window of the Mesh node.

The following line of code retrieves an array of strings corresponding to the legends of a 1D point graph.

```
String[] legends =
model.results("pg3").feature("ptgr1").getStringArray("legends");
```

The figure below shows an example of a vector of legends in the **Settings** window of the corresponding **Point Graph**.



The following line of code sets the Data Set dset1 for the Plot Group pg1:

```
model.result("pg1").set("data", "dset1");
```

The following lines of code set the anisotropic diffusion coefficient for a Poisson's equation problem on a block geometry.

```
model.geom("geom1").create("blk1", "Block");
with(model.geom("geom1").feature("blk1"));
  set("size", new String[]{"10", "1", "1"});
endwith();
model.geom("geom1").run();
with(model.physics("c").feature("cfeq1"));
  setIndex("c", "-0.1", 0, 1);
  setIndex("c", "-0.2", 0, 6);
  setIndex("f", "2.5", 0);
endwith();
```

The code below sets the global parameter L to a fixed value.

```
with(model.param());
  set("L", "10[cm]");
endwith();
```

The code below sets the material link index to the string variable alloy, defined under the **Declarations** node.

```
with(model.material("matlnk1"));
  set("link", alloy);
endwith();
```

The code below sets the coordinates of a cut point data set cpt1 to the values of the 1D array samplecoords[].

```
with(model.result().dataset("cpt1"));
  set("pointx", samplecoords[0]);
```

```
set("pointy", samplecoords[1]);
set("pointz", samplecoords[2]);
endwith();
```

The code below sets the components of a deformation plot.

```
with(model.result("pg7").feature("surf1").feature("def"));
  setIndex("expr", withstru, 0);
  setIndex("expr", withstrv, 1);
  setIndex("expr", withstrw, 2);
endwith();
```

The code below sets the title and color legend of a plot group pg2 and then regenerates the plot.

```
with(model.result("pg2"));
  set("titletype", "auto");
endwith();
with(model.result("pg2").feature("surf1"));
  set("colorlegend", "on");
endwith();
model.result("pg2").run();
```

Parameters and Variables

This code defines a global parameter L with **Expression** 0.5[m] and **Description** Length:

```
model.param().set("L", "0.5[m]");
model.param().descr("L", "Length");
```

There is an alternative syntax using three input arguments:

```
model.param().set("L", "0.5[m]", "Length");
```

You can also use the with syntax to set the **Expression** and **Description** for several parameters, for example:

```
with(model.param());
  set("L", "0.5[m]");
  descr("L", "Length");
  set("wd", "10[cm]");
  descr("wd", "Width");
  set("TO", "500[K]");
  descr("TO", "Temperature");
endwith();
```

which corresponds to the following **Settings** window for **Global Definitions>Parameters**:

ression	Value	Description
m]	0.5 m	Length
:m]	0.1 m	Width
[K]	500 K	Temperature
	[m] cm] [K]	[m] 0.5 m cm] 0.1 m

ACCESSING A GLOBAL PARAMETER

You would typically use the **Editor Tools** window for generating code for setting the value of a global parameter. While in the Method editor, right-click the parameter and select **Set**.

To set the value of the global parameter L to 10 cm:

```
model.param().set("L", "10[cm]");
```

To get the global parameter L and store it in a double variable Length:

```
double Length=model.param().evaluate("L");
```

The evaluation is in this case with respect to the base **Unit System** defined in the model tree root node.

To return the unit of the parameter L, if any, use:

```
String Lunit=model.param().evaluateUnit("L");
```

To write the value of a model expression to a global parameter, you typically need to convert it to a string. The reason is that model expressions may contain units.

Multiply the value of the variable Length with 2 and write the result to the parameter L including the unit of cm.

```
Length=2*Length;
model.param().set("L", toString(Length)+"[cm]");
```

To return the value of a parameter in a different unit than the base **Unit System**, use:

```
double Length real = model.param().evaluate("L","cm");
```

For the case where the parameter is complex valued, the real and imaginary parts can be returned as a double vector of length 2:

```
double[] realImag = model.param().evaluateComplex("Ex","V/m");
```

For parameters that are numbers without units, you can use a version of the set method that accepts a double instead of a string. For example, the lines

```
double a_double=7.65;
model.param().set("a_param",a_double);
```

assigns the value 7.65 to the parameter a_param.

VARIABLES

The syntax for accessing and assigning variables is similar to that of parameters. For example, the code:

```
with(model.variable("var1"));
  set("F", "150[N]");
  descr("F", "Force");
endwith();
```

assigns the Expression 150[N] to the variable with Name F.

The following code assigns a model expression to the variable f:

```
with(model.variable("var1"));
  set("f", "(1-alpha)^2/(alpha^3+epsilon)+1");
endwith();
```

and the following code stores the model expression for the same variable in a string fs.

```
String fs = model.variable("var1").get("f");
```

Unary and Binary Operators in the Model Object

The table below describes the unary and binary operators that can be used when accessing a model object, such as the model expressions used when defining parameters, variables, material properties, and boundary conditions, as well as in expressions used in results for postprocessing and visualization.

PRECEDENCE LEVEL	SYMBOL	DESCRIPTION
1	() {}.	grouping, lists, scope
2	^	power
3	! - +	unary: logical not, minus, plus
4	[]	unit
5	* /	binary: multiplication, division
6	+ -	binary: addition, subtraction
7	< <= > >=	comparisons: less-than, less-than or equal, greater-than, greater-than or equal
8	== !=	comparisons: equal, not equal
9	&&	logical and

PRECEDENCE LEVEL	SYMBOL	DESCRIPTION
10	11	logical or
11	,	element separator in lists

The following example code creates a variable to indicate whether the effective von Mises stress exceeds 200 MPa by using the inequality solid.mises>200[MPa]:

```
model.variable().create("var1");
model.variable("var1").model("comp1");
model.variable("var1").set("hi_stress", "solid.mises>200[MPa]");
```

The following code demonstrates using this variable in a surface plot:

```
model.result().create("pg3", "PlotGroup3D");
model.result("pg3").create("surf1", "Surface");
with(model.result("pg3").feature("surf1"));
  set("expr", "hi_stress");
endwith();
model.result("pg3").run();
```

The same plot can be created by directly using the inequality expression in the surface plot expression as follows:

```
with(model.result("pg3").feature("surf1"));
  set("expr", "solid.mises>200[MPa]");
endwith();
model.result("pg3").run();
```

Geometry

Once the **Geometry** node is created (see "Creating Model Components and Model Object Nodes" on page 28) you can add geometric features to the node. For example, add a square using default position (0,0) and default size 1:

```
model.geom("geom1").create("sq1", "Square");
```

The first input argument "sq1" to the create method is a tag, a handle, to the square. The second argument "Square" is the type of geometry object.

Add another square with a different position and size:

```
model.geom("geom1").create("sq2", "Square");
with(model.geom("geom1").feature("sq2"));
  set("pos", new String[]{"0.5", "0.5"});
  set("size", "0.9");
endwith();
```

The with statement in the above example is used to make the code more compact and, without using with, the code statements above are equivalent to:

```
\label{loss} $$ \bmod 1.geom("geom1").feature("sq2").set("pos", new String[]{"0.5", "0.5"}); $$ \bmod 1.geom("geom1").feature("sq2").set("size", "0.9"); $$ $$
```


Take the set difference between the first and second square:

```
model.geom("geom1").create("dif1", "Difference");
with(model.geom("geom1").feature("dif1").selection("input"));
  set(new String[]{"sq1"});
endwith();
with(model.geom("geom1").feature("dif1").selection("input2"));
  set(new String[]{"sq2"});
endwith();
```

To build the entire geometry, you call the method run for the **Geometry** node:

```
model.geom("geom1").run();
```

The above example corresponds to the following **Geometry** node settings:



In this way, you have access to the functionality that is available in the geometry node of the model tree. Use **Record Code** or any of the other tools for automatic generation of code to learn more about the syntax and methods for other geometry operations.

REMOVING MODEL TREE NODES

You can remove geometry objects using the remove method:

```
model.geom("geom1").feature().remove("sq2");
```

Remove a series of geometry objects (circles) with tags c1, c2, ..., c10:

```
for(int n=1;n<=10;n=n+1) {
  model.geom("geom1").feature().remove("c"+n);
}</pre>
```

The syntax "c"+n automatically converts the integer n to a string before concatenating it to the string "c".

To remove all geometry objects:

```
for(String tag : model.geom("geom1").feature().tags()) {
    model.geom("geom1").feature().remove(tag);
}
```

However, the same can be achieved with the shorter:

```
model.geom("geom1").feature().clear();
```

In a similar way, you can remove other model tree nodes.

Mesh

The following line adds a **Mesh** node, with tag mesh1, linked to the geometry with tag geom1:

```
model.mesh().create("mesh1", "geom1");
```

You can control the mesh element size either by a preconfigured set of sizes or by giving low-level input arguments to the meshing algorithm.

The following line:

```
model.mesh("mesh1").autoMeshSize(6);
```

corresponds to a mesh with **Element size** set to **Coarse**. The argument to the method autoMeshSize ranges from 1-9, where 1 is **Extremely fine** and 9 is **Extremely coarse**.


To generate the mesh, you call the run method for the mesh node:


```
model.mesh("mesh1").run();
```

Use **Record Code** to generate code for other mesh operations.

The code below shows an example where the global mesh parameters have been changed.

```
model.mesh("mesh1").automatic(false); // Turn off Physics-controlled mesh
with(model.mesh("mesh1").feature("size"));
  set("custom", "on"); // Use custom element size
  set("hmax", "0.09"); // Maximum element size
  set("hmin", "3.0E-3"); // Minimum element size
  set("hgrad", "1.2"); // Maximum element growth rate
  set("hcurve", "0.35"); // Curvature factor
  set("hnarrow", "1.5"); // Resolution of narrow regions
endwith();
model.mesh("mesh1").run();
```





Note that you can also set local element size properties for individual points, edges, faces, and domains. Use **Record Code** or any of the other tools for automatic generation of code to learn more about the syntax and methods for other mesh operations.

Physics

Consider analyzing stationary heat transfer in the solid rectangular geometry shown earlier. To create a physics interface, for **Heat Transfer in Solids**, use:

```
model.physics().create("ht", "HeatTransfer", "geom1");
```

The first input argument to the create method is a physics interface tag that is used as a handle to this physics interface. The second input argument is the type of physics interface. The third input argument is the tag of the geometry to which the physics interface is assigned.

To set a fixed temperature boundary condition on a boundary, you first create a TemperatureBoundary feature using the following syntax:

```
model.physics("ht").create("temp1", "TemperatureBoundary", 1);
```

The first input argument to create is a feature tag that is used as a handle to this boundary condition. The second input argument is the type of boundary condition. The third input argument is the spatial dimension for the geometric entity that this boundary condition should be assigned to. Building on the previous example of creating a 2D rectangle, the input argument being 1 means that the dimension of this boundary is 1 (that is, an edge boundary in 2D).

The next step is to define which selection of boundaries this boundary condition should be assigned to. To assign it to boundary 1 use:

```
model.physics("ht").feature("temp1").selection().set(new int[]{1});
To assign it to multiple boundaries, for example 1 and 3, use:
    model.physics("ht").feature("temp1").selection().set(new int[]{1,3});
```

To set the temperature on the boundary to a fixed value of 400 K, use:

```
model.physics("ht").feature("temp1").set("T0", "400[K]");
```

The following lines of code show how to define a second boundary condition for a spatially varying temperature, varying linearly with the coordinate y:

```
\label{local-physics("ht").create("temp2", "TemperatureBoundary", 1);} \\ model.physics("ht").feature("temp2").selection().set(new int[]{4}); \\ model.physics("ht").feature("temp2").set("TO", "(300+10[1/m]*y)[K]"); \\ \end{cases}
```

The resulting model tree structure is shown in the figure below.

```
    ▶ ∰ Materials
    ▲ (☐ Heat Transfer in Solids (ht) (ht)
    ➡ Solid 1 (solid1)
    ➡ Initial Values 1 (init1)
    ➡ Thermal Insulation 1 (ins1)
    ➡ Temperature 1 (temp1)
    ➡ Temperature 2 (temp2)
    ➡ Mesh 1 (mesh1)
```

Use **Record Code** or any of the other tools for automatic generation of code to learn more about the syntax and methods for other physics interface features and other physics interfaces.

CREATING AND REMOVING MODEL TREE NODES

Below is a larger block of code that removes, creates, and accesses physics interface feature nodes. It uses the Iterator class and methods available in the java.util package. For more information, see the Java® documentation.

```
String[] flowrate = column1;
String[] Mw = column2;
java.util.Iterator<PhysicsFeature> iterator =
model.physics("pfl").feature().iterator();
while (iterator.hasNext()) {
   if (iterator.next().getType().equals("Inlet"))
```

```
iterator.remove();
}
if (flowrate != null) {
  for (int i = 0; i < flowrate.length; i++) {
    if (flowrate[i].length() > 0) {
        if (Mw[i].length() > 0) {
            int d = 1+i;
            model.physics("pfl").create("inl"+d, "Inlet");
            model.physics("pfl").feature("inl"+d).setIndex("spec", "3", 0);
            model.physics("pfl").feature("inl"+d).set("qsccm0", flowrate[i]);
            model.physics("pfl").feature("inl"+d).set("Mn", Mw[i]);
            model.physics("pfl").feature("inl"+d).selection().set(new int[]{d});
        }
    }
}
```

The need to remove and create model tree nodes is fundamental when writing methods because the state of the model object is changing each time a model tree node is run. In the method above, the number of physics feature nodes are dynamically changing depending on user inputs. Each time the simulation is run, old nodes are removed first and then new nodes are added.

Material

A material, represented in the Model Builder by a **Materials** node, is a collection of property groups, where each property group defines a set of material properties, material functions, and model inputs that can be used to define, for example, a temperature-dependent material property. A property group usually defines properties used by a particular material model to compute a fundamental quantity.

To create a **Materials** node:

```
model.material().create("mat1", "Common", "comp1");
```


You can give the material a name, for example, Aluminum, as follows:

```
model.material("mat1").label("Aluminum");
```


The following lines of code shows how to create a basic material property group for heat transfer:

```
with(model.material("mat1").propertyGroup("def"));
  set("thermalconductivity", new String[]{"238[W/(m*K)]"});
  set("density", new String[]{"2700[kg/m^3]"});
  set("heatcapacity", new String[]{"900[J/(kg*K)]"});
endwith();
```

The built-in property groups have a read-only tag. In the above example, the tag def represents the property group **Basic** in the model tree.




The resulting model tree and Material node settings are shown in the figure below.



Note that some physics interfaces do not require a material to be defined. Instead, the corresponding properties can be accessed directly in the physics interface. This is also the case if the physics model settings are changed from **From material** to **User defined**. For example, for the **Heat Transfer in Solids** interface, this setting can be

found in the **Settings** window of the subnode **Solid**, in the sections **Heat Conduction**, **Solid** and **Thermodynamics**, **Solid**, as shown in the figure below.



Use **Record Code** or any of the other tools for automatic generation of code to learn more about the syntax and methods for materials.

Study

The **Study** node in the model tree contains one or more study steps, instructions that are used to set up solvers and solve for the dependent variables. The settings for the **Study** and the **Solver Configurations** nodes can be quite complicated. Consider the simplest case for which you just need to create a study, add a study step, and run it.

Building on the example from the previous sections regarding stationary heat transfer, let's add a **Stationary** study step.

```
model.study().create("std1"); // Study with tag std1
model.study("std1").create("stat", "Stationary");
model.study("std1").run();
```

The call to the method run automatically generates a solver sequence in a data structure model.sol and then runs the corresponding solver. The settings for the solver are automatically configured by the combination of physics interfaces you have chosen. You can manually change these settings, as shown later in this section. The data structure model.sol roughly corresponds to the contents of the Solver Configurations node under the Study node in the model tree.

All low-level solver settings are available in model.sol. The structure model.study is used as a high-level instruction indicating which settings should be created in model.sol when a new solver sequence is created.

For backward compatibility, some of the low-level settings in model.sol are automatically generated when using **Record Code**.

The example below shows a somewhat more elaborate case of programing the study that would be applicable for the stationary heat transfer example shown earlier. The instructions below more closely resemble the output autogenerated by using the **Record Code** option.

First create instances of the **Study** node (with tag std1) and a **Stationary** study step subnode:

```
model.study().create("std1");
model.study("std1").create("stat", "Stationary");
```

The actual settings that determine how the study is run are contained in a sequence of operations in the **Solution** data structure, with tag sol1, which is linked to the study:

```
model.sol().create("sol1");
model.sol("sol1").study("std1");
```

The following code defines the sequence of operations contained in sol1.

First, create a **Compile Equations** node under the **Solution** node to determine which study and study step will be used:

```
model.sol("sol1").create("st1", "StudyStep");
model.sol("sol1").feature("st1").set("study", "std1");
model.sol("sol1").feature("st1").set("studystep", "stat");
```

Next, create a **Dependent Variables** node, which controls the scaling and initial values of the dependent variables and determines how to handle variables that are not solved for:

```
model.sol("sol1").create("v1", "Variables");
```

Now create a **Stationary Solver** node. The **Stationary Solver** contains the instructions that are used to solve the system of equations and compute the values of the dependent variables.

```
model.sol("sol1").create("s1", "Stationary");
```

Add subnodes to the **Stationary Solver** node to choose specific solver types. In this example, use an **Iterative** solver:

```
model.sol("sol1").feature("s1").create("i1", "Iterative");
```

Add a Multigrid preconditioner subnode:

```
model.sol("sol1").feature("s1").feature("i1").create("mg1", "Multigrid");
```

You can have multiple **Solution** data structures in a study node (such as sol1, sol2, and so on) defining different sequences of operations. The process of notifying the study of which one to use is done by "attaching" the **Solution** data structure sol1 with study std1:


```
model.sol("sol1").attach("std1");
```

The attachment step determines which **Solution** data structure sequence of operations should be run when selecting **Compute** in the COMSOL Desktop user interface.

Finally, run the study, which is equivalent to running the **Solution** data structure sol1:

```
model.sol("sol1").runAll();
```

The resulting **Study** node structure is shown in the figure below. Note that there are several additional nodes added automatically. These are default nodes and you can edit each of these nodes by explicit method calls. You can edit any of the nodes while using **Record Code** to see the corresponding methods and syntax used.



MODIFYING LOW-LEVEL SOLVER SETTINGS

To illustrate how some of the low-level solver settings can be modified, consider a case where the settings for the **Fully Coupled** node are modified. This subnode controls the type of nonlinear solver used.

The first line below may not be needed depending on whether the **Fully Coupled** subnode has already been generated or not (it could have been automatically generated by code similar to what was shown above).

```
model.sol("sol1").feature("s1").create("fc1", "FullyCoupled");
with(model.sol("sol1").feature("s1").feature("fc1"));
  set("dtech", "auto"); // The Nonlinear method (Newton solver)
  set("initstep", "0.01"); // Initial damping factor
  set("minstep", "1.0E-6"); // Minimum damping factor
  set("rstep", "10"); // Restriction for step-sized update
  set("useminsteprecovery", "auto"); // Use recovery damping factor
  set("minsteprecovery", "0.75"); // Recovery damping factor
  set("ntermauto", "tol"); // Termination technique
  set("maxiter", "50"); // Maximum number of iterations
  set("ntolfact", "1"); // Tolerance factor
  set("termonres", "auto"); // Termination criterion
  set("reserrfact", "1000"); // Residual factor
endwith();
```

For more information on the meaning of these and other low-level solver settings, see the *Solver* section of the *Programming Reference Manual*.

Changing the low-level solver settings requires that model.sol has first been created. It is always created the first time you compute a study, however, you can trigger the automatic generation of model.sol as follows:

```
model.study().create("std1");
model.study("std1").create("stat", "Stationary");
model.study("std1").showAutoSequences("sol");
```

where the call to showAutoSequences corresponds to the option **Show Default Solver**, which is available when right-clicking the **Study** node in the model tree.

This can be used if you do not want to take manual control over the settings in model.sol (the solver sequence) and are prepared to rely on the physics interfaces to generate the solver settings. If your application makes use of the automatically generated solver settings, then updates and improvements to the solvers in future versions are automatically included. Alternatively, the automatically generated model.sol can be useful as a starting point for your own edits to the low-level solver settings.

CHECKING IF A SOLUTION EXISTS

When creating an application it is often useful to keep track of whether a solution exists or not. The method model.sol("sol1").isEmpty() returns a boolean and is true if the solution structure sol1 is empty. Consider an application where the solution state is stored in a string solution_state. The following code sets the state depending on the output from the isEmpty method:

```
if (model.sol("sol1").isEmpty()) {
   solution_state = "nosolution";
}
```

```
else {
   solution_state = "solutionexists";
}
```

Almost all of the example applications in the Application Libraries use this technique.

Results

The Results node contains nodes for Data Sets, Derived Values, Tables, Plot Groups, Export, and Reports. As soon as a solution is obtained, a set of Plot Group nodes are automatically created. In the example of Heat Transfer in Solids, when setting up such an analysis in the Model Builder, two Plot Group nodes are added automatically. The first one is a Surface plot of the Temperature and the second one is a Contour plot showing the isothermal contours. Below you will see how to set up the corresponding plots manually.

```
First create a 2D plot group with tag pg1:

model.result().create("pg1", "PlotGroup2D");

Change the Label of the Plot Group:

model.result("pg1").label("Temperature (ht)");

Use the data set dset1 for the Plot Group:

model.result("pg1").set("data", "dset1");
```

Create a **Surface** plot for pg1 with settings for the color table used, the intra-element interpolation scheme, and the data set referring to the parent of the **Surface** plot node, which is the pg1 node:

```
model.result("pg1").feature().create("surf1", "Surface");
  model.result("pq1").feature("surf1").label("Surface");
  with(model.result("pg1").feature("surf1"));
    set("colortable", "ThermalLight");
    set("smooth", "internal");
    set("data", "parent");
  endwith();
Now create a second 2D plot group with contours for the isotherms:
  model.result().create("pg2", "PlotGroup2D");
  model.result("pg2").label("Isothermal Contours (ht)");
  with(model.result("pg2"));
    set("data", "dset1");
  endwith();
  model.result("pg2").feature().create("con1", "Contour");
  model.result("pg2").feature("con1").label("Contour");
  with(model.result("pg2").feature("con1"));
    set("colortable", "ThermalLight");
    set("smooth", "internal");
```

```
set("data", "parent");
endwith();
Finally, generate the plot for the Plot Group pg1:
```

model.result("pg1").run();

To find the maximum temperature, add a **Surface Maximum** subnode to the **Derived Values** node as follows:

First create the **Surface Maximum** node with tag max1:

```
model.result().numerical().create("max1", "MaxSurface");
```

Note that in this context the method corresponding to the **Derived Values** node is called numerical.

Next, specify the selection. In this case there is only one domain 1:

```
model.result().numerical("max1").selection().set(new int[]{1});
```

Create a **Table** node to hold the numerical result and write the output from max1 to the **Table**:

```
model.result().table().create("tbl1", "Table");
model.result().table("tbl1").comments("Surface Maximum 1 {max1} (T)");
model.result().numerical("max1").set("table", "tbl1");
model.result().numerical("max1").setResult();
```

Use **Record Code** or any of the other tools for automatic generation of code to learn more about the syntax and methods for **Results**.

Using Parameterized Solutions in Results

The code below changes the visualization of a plot group pg1 by setting the property looplevel, which controls the solution parameter, to the string variable svar.

```
with(model.result("pg1"));
  set("looplevel", new String[]{svar});
endwith();
model.result("pg1").run();
```

The property looplevel has a central role in accessing parameterized solutions. Its argument is a 1D string array with one index per "loop level" in a study. The different loop levels correspond to the different nested parameters in a parametric sweep with multiple parameters.

Loading Data to Tables

By using the loadFile method you can import data into a table and then display it using a results table form object or a table surface plot. The following example demonstrates loading data from an Excel file into a table and visualizing the contents using a table surface plot. The file in this example is assumed to be imported, in an application, using a file import form object with a file declaration file1 as the **File Destination**.

```
model.result().table("tbl1").loadFile("upload://file1", "", cells);
  The string variable cells contains the spreadsheet selection to be
  imported, for example A1:J7.
  The following code creates a plot group pq1 with a table surface plot.
  This code is not needed if the embedded model already contains a table
  and a table surface plot.
* /
model.result().create("pg1", 2);
model.result("pg1").create("tbls1", "TableSurface");
with(model.result("pg1").feature("tbls1"));
  set("table", "tbl1");
endwith();
with(model.result("pg1").feature("tbls1"));
  set("dataformat", "cells");
endwith();
model.result("pq1").feature("tbls1").create("hqht1". "TableHeight");
with(model.result("pg1").feature("tbls1").feature("hght1"));
  set("view", "view3");
endwith();
with(model.view("view3").camera());
  set("viewscaletype", "manual");
  set("xscale", "1");
  set("yscale", "1");
  set("zscale", "1");
endwith();
// The following line is needed to update the plot
model.result("pq1").run();
```

Multiphysics

Some of the physics interfaces define a multiphysics analysis by themselves without being coupled to any other interface. This is the case when the physics interface is used for a coupling that is so strong that it doesn't easily lend itself to be separated into several physics interfaces. In other cases, a set of single physics interfaces, typically two, can be combined by the use of the **Multiphysics** node. For example, a **Joule Heating** analysis is defined as the combination of an **Electric Currents** interface and a **Heat Transfer in Solids** interface with an additional **Electromagnetic Heat Source** node under the **Multiphysics** node. The following lines of code illustrate the corresponding method calls.

```
model.physics().create("ec", "ConductiveMedia", "geom1");
model.physics().create("ht", "HeatTransfer", "geom1");
model.multiphysics().create("emh1", "ElectromagneticHeatSource", "geom1",
2);
model.multiphysics("emh1").selection().all();
with(model.multiphysics("emh1"));
```

```
set("EMHeat_physics", "ec");
set("Heat_physics", "ht");
endwith();
```

When using the Model Builder to set up a **Joule Heating** analysis, nodes in addition to those shown above will be created corresponding to Joule heating in thin shells, should they exist in the model, and temperature couplings if there are multiple field variables for electric potential and temperature.

Working with Model Objects

When using the Model Builder in the COMSOL Desktop, an embedded model with variable name model is automatically created. The embedded model has a special status. For example, the automatic code generation tools only consider the embedded model. In addition, when you save to or load from an MPH file, only the embedded model is saved or loaded. General tools include the **Save Application As** command in the Application Builder and **File > Save As**, from the **File** menu of the COMSOL Desktop environment.

However, in an application you are allowed to create and edit multiple models. Saving and loading such models is done by using the built-in methods saveModel and loadModel. An MPH file can only contain a single model object.

If you need to create model objects, in addition to the embedded model, use the built-in method createModel.

To create a new model you use:

```
Model extmodel = createModel();
```

A unique model tag is created automatically and assigned to the model. If you want to explicitly control the model tag, use:

```
Model extmodel = createModel("My model 1");
```

where My_model_1 is a unique tag. It is recommended that you do not use the names Model1, Model2, Model3, and so on, since these names are used by the mechanism that automatically generates model tags for the embedded model when loading and saving MPH files.

The following example retrieves the model tag of the embedded model:

```
String my modeltag = model.tag();
```

however, you rarely need to use the model tag of the embedded model object.

Instead of creating and building up the contents of a model from scratch, you can load an existing model and edit it.

For example in the Windows operating system, load a model my_model.mph from the folder C:\COMSOL_Work, by using the built-in method loadModel:

```
Model extmodel = loadModel("C:\\COMSOL Work\\my model.mph");
```

A unique model tag is created automatically and is assigned to the model upon load. Note the double-backslash syntax in the file name. Backslash (\) is a special character in Java and the double backslash is needed in this case.

To make your application portable, you can use the file scheme syntax available in the Application Builder. Assuming you stored the MPH file in the common folder, the call to loadModel should be:

```
Model extmodel = loadModel("My Model 1", "common://my model.mph");
```

In this example, the tag My_Model_1 is important since it is used to retrieve the model from other methods. Once loaded, the model extmodel exists in the work space of the current COMSOL Multiphysics or COMSOL Server session. Note that an MPH file can only contain one model object, so there is no ambiguity on which model you refer to when loading an MPH file.

Assume that you, in one method, have loaded the model extmodel with the tag My_Model_1, such as in the example above. The model variable extmodel is not available in other methods. In order to retrieve the model from another method use:

```
Model mymodel = getModel("MyModel 1");
```

The contents of mymodel and extmodel are the same, but these variables exist in the variable space of two different methods.

The tag My_Model_1 uniquely identified and retrieved the model object from the current COMSOL Multiphysics or COMSOL Server session.

To clear the contents of a model object, use the built-in method clearModel. For a list of model utility methods, see "Model Utility Methods" on page 91.

TURNING OFF AND RESET THE MODEL HISTORY

When running method code in applications or otherwise in order to automate modeling tasks, the stored model history may become excessively large. The model history is used, for example, when saving to Model M-file or Model Java-file. Because of this, depending on the repetitive nature of your code, you may need to temporarily turn off model history recording, as illustrated by the following example:

```
model.hist().disable();
// some code
model.hist().enable();
```

If you wish to reset the model history to an almost minimal sequence of commands that creates the current state of the model object you can use:


```
model.resetHist();
```

In the **File** menu, this functionality is referred to as **Compact History**.

The Model Object Class Structure

For a full description of the class structure and method signatures, see the HTML document *Java Documentation* available in the *COMSOL Documentation*. You find the Java documentation under **COMSOL API for use with Java**[®] at the bottom of the Documentation window.

The figure below shows the document as displayed in a browser.



If you encounter a class that you are unfamiliar with you will get help by a tooltip as in the figure below for the output of the getView method.

```
Preview X form1 X method1 X

1
2
3
4
5
6
my_view = getView("/form1/graphics1");
my_view cannot be resolved to a variable. Use Ctrl+1 to correct this error.
```

By using the keyboard shortcut Ctrl+1 the correct type declaration is assigned to the variable as shown in the figure below.



This way you can avoid having to consult the Java Documentation.

The Application Object

The application object is a part of the model object and is the data structure that allows access to the user interface features of an application from within a method. The state of the application object is reflected in the COMSOL Desktop user interface by the contents of the Application Builder and its application tree.

You can write code using the Method editor to directly access and change the features presented in a running application, including button text, icons, colors, and fonts.


The application object gives you access to a subset of the features and settings available in the Application Builder. You can use the application object methods for run time modifications to the user interface, but not for building a complete user interface. For building the user interface of an application, you need to use the Form editor as described in the book *Introduction to Application Builder*.

This section gives an overview of the application object.

Shortcuts

Form objects and other user interface components are referenced in methods by using a certain syntax. For example, using the default naming scheme form3/button5 refers to a button with name button5 in form3 and form2/graphics3 refers to a graphics object with name graphics3 in form2. You can also change the default names of forms and form objects. For example, if form1 is your main form then you can change its name to main.


To simplify referencing form objects as well as menu, ribbon, and toolbar items by name, you can create shortcuts with a custom name. In the **Settings** window of an object or item, click the button to the right of the **Name** field and type the name of your choice.



To create or edit a shortcut, you can also use the keyboard shortcut Ctrl+K. All shortcuts that you create are made available in a **Shortcuts** node under **Declarations** in the application tree.



In the **Settings** window for **Shortcuts** shown below, two shortcuts plot_temp and temp_vis were created for a button and a graphics object, respectively.



The shortcuts can be referenced in other form objects or in code in the Method editor. The example below shows a shortcut temp_vis used as an input argument to a temperature plot.



Shortcuts are automatically updated when objects are renamed, moved, copied, and duplicated. They are available in application methods as read-only Java[®] variables, similar to string, integer, double, and Boolean declarations.

Using shortcuts is recommended because it avoids the need to update methods when the structure of the application user interface changes.

Shortcuts can also be created for most objects in the model builder tree.

EXAMPLE CODE

If the application contains a button named button1 in a form named form1, and the button has a shortcut named b1, the following two ways to change the button text to red are equivalent:

```
b1.set("foreground", "red");
app.form("form1").formObject("button1").set("foreground", "red");
```

Accessing the Application Object

In the Method editor you can directly access the application object part of the model object by using the app variable. This variable is a shorthand for model.app().

The Name of User Interface Components

Access the various parts of the application object by using the *name* of a form object, form, item, etc. A *name* in the application object has the same function as the *tag* in the model object omitting the model.app part.

For example, in the line of code

```
app.form("form1").formObject("button1").set("enabled", false);
```

the string form1 is the *name* of a form and button1 is the *name* of a button.

Important Classes

THE MAIN APPLICATION CLASS

When working with an application object, the main application class is AppModel, which is the type of model.app().

DECLARATION CLASSES

In addition to the basic data types and shortcut declarations, the **Declaration** node may include Choice List and Unit List declarations. The corresponding classes are ChoiceList and UnitSet. The parent class to ChoiceList and UnitSet is called DataSource. In addition, Scalar, Array 1D, and Array 2D data types are handled by the DataSource class. For more information, see "Data Source" on page 84.

METHOD CLASS

The Method class is used to represent methods. For more information, see "Method Class" on page 89.

MAIN USER INTERFACE COMPONENT CLASSES

In an application object, the main user interface components correspond to the following classes:

- MainWindow
 - The class representing the Main Window node in the application tree.
- Form
 - The class representing a form.
- FormObject
 - The class representing a form object.
- Item
 - The class representing, for example, a menu, toolbar, or ribbon item.

Each class has a set of associated methods that are used to edit the corresponding user interface component at run time. These are described in the following sections.

In addition to the main user interface component classes, there are also list versions of the Form, FormObject, and Item classes. These are: FormList, FormObjectList, and ItemList.

Get and Set Methods for the Color of a Form Object

The get and set methods described in the section "Get and Set Methods for Accessing Properties" on page 29 are applicable to the model object as well as the model app part of the model object. In addition, the following methods are available for changing the color of a form object:

NAME	SYNTAX	DESCRIPTION
setColor	<pre>setColor(String prop, int r, int g, int b)</pre>	Set a color property using red, green, and blue values.
getColor	<pre>int[] getColor(String prop)</pre>	Get the value of a color property as an array of red, green, and blue values.

Not all methods are applicable to all properties. Use Ctrl+Space to use code completion to find out what methods are applicable for a certain object, and what property names and property values are applicable for a certain method.

General Properties

The following table lists properties that are available for several different user interface components, including form objects. In the table below, a user interface component is referred to as an object.

PROPERTY	VALUE	DEFAULT	DESCRIPTION
visible	true false	true	If the value is true, the corresponding object is visible in the user interface.
enabled	true false	true	If the value is true, the corresponding object is enabled in the user interface, which means that the user can interact with the object.
background	String	default	The background color for the corresponding user interface element.
foreground	String	default	The foreground color for the corresponding user interface element.
font	String	default	The font family name. The special value default means that the font to use is determined by the parent object, which is the corresponding setting in the Settings window of the Forms node.
fontbold	true false	false	If true the font uses boldface style.
fontitalic	true false	false	If true the font uses italic style.
fontunderline	true false	false	If true the font uses underline style.
fontsize	String	-1	The font size in points. The special value -1 represents the default size, which means that the size is taken from the parent object (the Forms node) or from the system default size if no parent object defines the size.

A foreground or background color property is represented by a string value. The available colors are: black, blue, cyan, gray, green, magenta, red, white, and yellow, or a custom color may also be defined. The special value default means

that the color is taken from the parent object. Depending on the parent type, this could mean that default is **Inherit** or **Transparent**, referring to the corresponding setting in the **Settings** window in the Form editor. An arbitrary RGB color can be represented by a string of the form rgb(red,green,blue) where red, green, and blue are integers between 0 and 255. Color properties can also be manipulated using the getColor and setColor methods to directly access the red, green, and blue color components. If a color property has the value default, it does not have red, green, and blue values. In this case, the getColor method returns the array [0,0,0].

EXAMPLE CODE

The following example reads the current background color for a form, makes the color darker, and applies the modified color to the same form.

```
int[] rgb = app.form("form1").getColor("background");
for (int i = 0; i < 3; i++)
  rgb[i] /= 2;
app.form("form1").setColor("background", rgb[0], rgb[1], rgb[2]);</pre>
```

The following line of code sets the background color to black:

```
app.form("form1").set("background", "black");
```

The following line of code sets the background color to default which in the case of the background color property corresponds to the Form editor setting **Transparent**.

```
app.form("form1").set("background", "default");
```

The following line of code sets the background color to the RGB values 125, 45, and 43.

```
app.form("form1").set("background", "rgb(125,45,43)");
```

The Main Application Methods

The main application class AppModel has the following methods:

NAME	SYNTAX	DESCRIPTION
mainWindow	MainWindow mainWindow()	Returns the MainWindow object.
form	FormList form()	Returns the list of forms.
form	Form form(String name)	Returns the form with the specified name.

NAME	SYNTAX	DESCRIPTION
declaration	DataSource declaration(String name)	Returns the declaration object (Scalar, Array 1D, Array 2D, ChoiceList, or UnitSet) with the specified name.
hasProperty	boolean hasProperty(String name)	Returns true if there is a modifiable property with the specified name.

The AppMode1 class has the following properties:

PROPERTY	VALUE	DEFAULT	DESCRIPTION
asktosave	true false	false	If true, ask user if changes should be saved before the application is closed.
startmode	edit run	edit	Determines whether the application is opened for editing or running when you double-click the MPH file, including Windows desktop icons.

EXAMPLE CODE

```
app.set("asktosave", true);
```

The following code appends a text string to the application window title.

```
String oldTitle = app.mainWindow().getString("title");
app.mainWindow().set("title", oldTitle+" modified");
```

Main Window

The MainWindow class has the following methods:

NAME	SYNTAX	DESCRIPTION	
menuBar	ItemList menuBar()	Returns the list of items in the menu bar.	
menuBar	<pre>Item menuBar(String name)</pre>	Returns the menu bar item with the specified name.	
toolBar	<pre>ItemList toolBar()</pre>	Returns the list of items in the toolbar.	
toolBar	<pre>Item toolBar(String name)</pre>	Returns the toolbar item with the specified name.	
ribbon	<pre>ItemList ribbon()</pre>	Returns the list of items in the ribbon.	
ribbon	Item ribbon(String name)	Returns the ribbon item with the specified name.	
fileMenu	<pre>ItemList fileMenu()</pre>	Returns the list of items in the file menu.	

NAME	SYNTAX	DESCRIPTION	
fileMenu	Item fileMenu(String name)	Returns the file menu item with the specified name.	
hasProperty	boolean hasProperty(String name)	Returns true if there is a modifiable property with the specified name.	

The menuBar and toolBar items are visible in the application user interface if the menu type is set to **Menu bar** in the **Settings** window of the **Main Window**. The ribbon and fileMenu items are visible in the user interface if the menu type is set to **Ribbon**. It is possible to access and modify items that are not visible based on the menu type setting, but doing so will not have any visible effect in the user interface.

The MainWindow class has the following properties:

PROPERTY	VALUE	DEFAULT	DESCRIPTION
showfilename	true false	true	If true the filename is included in the window title bar title.
title	String	My application	The text to display in the window title bar.

EXAMPLE CODE

app.mainWindow().set("showfilename", false);

Form

The Form class has the following methods:

NAME	SYNTAX	DESCRIPTION
getName	String getName()	Returns the name of this form.
getParentForm	Form getParentForm()	Returns the parent form that contains this form. Useful for local cards in a card stack.
formObject	FormObjectList formObject()	Returns the list of form objects.
formObject	FormObject formObject(String name)	Returns the form object with the specified name.

NAME	SYNTAX	DESCRIPTION
hasProperty	boolean hasProperty(String name)	Returns true if there is a modifiable property with the specified name.
declaration	DataSource declaration(String name)	Returns a form declaration object (Scalar, Array ID, Array 2D, or ChoiceList) with the specified name.
method	MethodList method()	Returns the list of methods.
method	Method method(String name)	Gets a method with the specified name.

The Form class has the following properties:

PROPERTY	VALUE	DEFAULT	DESCRIPTION
icon	String	п п	The name of the background image. Valid values are images defined in Images>Libraries node in the application tree.
iconhalign	left center right fill repeat	center	Horizontal alignment for the background image.
iconvalign	top center bottom fill repeat	center	Vertical alignment for the background image.
title	String	Form N	The form title for an integer N.

EXAMPLE CODE

```
app.form("form1").set("icon", "compute.png");
app.form("form1").formObject("button1").set("enabled", false);
DataSource ds = app.form("form1").declaration("var");
```

Form Object

The FormObject class has the following methods:

NAME	SYNTAX	DESCRIPTION
getName	String getName()	Returns the name of this form object.
getParentForm	Form getParentForm()	Returns the parent form that contains this form object.

NAME	SYNTAX	DESCRIPTION	
getType	String getType()	Returns the form object type name, as defined in the following sections.	
form	FormList form()	For a CardStack form object, returns the list of local cards.	
form	Form form(String name)	For a CardStack form object, returns the local card with the specified name.	
item	<pre>ItemList item()</pre>	For a Toolbar, Graphics or Table form object, returns the list of user-defined buttons.	
item	Item item(String name)	For a Toolbar, Graphics or Table form object, return the user-defined button with the specified name.	
hasProperty	boolean hasProperty(String name)	Returns true if there is a modifiable property with the specified name.	

Most form objects have one or more of the properties listed in "General Properties" on page 59. A form object has a certain property if the corresponding setting is available in the Form editor. Additional properties are supported for several types of form objects. The general properties that are supported and any additional properties for form objects are listed in the following sections.

EXAMPLE CODE

The following code loops over all buttons and disables them:

```
for (FormObject formObject : app.form("form1").formObject()) {
   if ("Button".equals(formObject.getType())) {
      formObject.set("enabled", false);
   }
}
```

The getType method retrieves the type of form object. In the above example the type of form object is Button and the statement

"Button".equals(formObject.getType()) represents a string comparison between the output of the getType method and the string "Button".

The following table lists all form object types that can be returned by getType:

FORM OBJECT TYPE		
ArrayInput	Hyperlink	SelectionInput
Button	Image	Slider
CardStack	InformationCardStack	Spacer
CheckBox	InputField	Table
ComboBox	Line	Text

FORM OBJECT TYPE		
DataDisplay	ListBox	TextLabel
Equation	Log	ToggleButton
FileImport	MessageLog	Toolbar
Form	ProgressBar	Unit
FormCollection	RadioButton	Video
Graphics	ResultsTable	WebPage

ARRAY INPUT

Property	Value	Default	Description
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

Example Code

app.form("form1").formObject("arrayinput1").set("enabled", false);

BUTTON

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
icon	String	н н	The button icon. Valid values are images defined in "Images > Libraries" in the Application Builder.
text	String	Generated automatically	The button text. The text must not be an empty string.
tooltip	String	пп	The button tooltip text.

In the Form editor, if a button has its **Size** setting set to **Large**, it always displays its text property. If the button is **Small**, it either displays the icon or the text

according to the following rule: if the icon property is empty, the text is displayed, if the icon property is not empty, the icon is displayed.

Example Code

```
app.form("form1").formObject("button1").set("enabled", false);
```

CARD STACK

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled visible			See "General Properties" on page 59.

Example Code

```
app.form("form1").formObject("cardstack1").set("visible", false);
```

To access objects in a local card, either use shortcuts or use the form method:

```
app.form("form1").form0bject("cardstack1").form("card1").form0bject("butto n1").set("enabled", false);
```

CHECK BOX

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize fontunderline foreground visible			See "General Properties" on page 59.
text	String	Generated automatically	The check box label text.
tooltip	String	пп	The check box tooltip text.

Example Code

```
app.form("form1").formObject("checkbox1").set("tooltip", "tooltip text");
```

Сомво Вох

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

Example Code

```
app.form("form1").formObject("combobox1").set("foreground", "blue");
```

DATA DISPLAY

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
exponent	superscript E	superscript	When set to superscript, exponents are displayed using superscript font. When set to E, exponents are displayed using the character E followed by the exponent value.
notation	auto scientific decimal	auto	When the value is scientific, numbers are always displayed using scientific notation. When the value is decimal, numbers are never displayed using scientific notation. When the value is auto, the notation depends on the size of the number.
precision	Integer	4	The number of significant digits that are displayed.
showunit	true false	true	Controls if the unit is displayed in addition to numerical values.
tooltip	String	пп	The tooltip text.

Example Code

app.form("form1").formObject("datadisplay1").setColor("background", 192,
192, 192);

EQUATION

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled fontsize foreground visible			See "General Properties" on page 59.
equation	String		The string in LaTeX syntax defining the equation.

Example Code

```
app.form("form1").formObject("equation1").set("visible", false);
```

FILE IMPORT

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
buttontext	String	Browse	Text to display on the button that opens the file browser.
dialogtitle	String	File import	Text to display as dialog title for the file browser dialog. Also displayed as a tooltip for the FileBrowser form object.
filetypes	String[]	{"ALLFILES"}	Defines the list of file types that can be selected in the file browser.

Example Code

```
\label{lem:condition} $$ \operatorname{app.form}("form1").form0bject("fileimport1").set("filetypes", new String[]{"ALL2DCAD"});
```

FORM

A form used as a subform does not have any modifiable properties.

FORM COLLECTION

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

To modify the active pane, change the corresponding declaration variable.

Example Code

This line of code changes the font:

```
app.form("form1").formObject("collection1").set("font", "Arial");
```

The expanded state of sections in form collections can be controlled by:

```
app.form("form1").formObject("formcollection1").expanded("form2", false);
```

The expanded method is only supported by form collections which use sections. The first argument is the tag of the form which is represented by the section. The second argument determines if the sections should be expanded or collapsed.

GRAPHICS

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled visible			See "General Properties" on page 59.
datapick	true false	false	If true, data picking is enabled in the graphics form object.
datapicktarget	ProbeFeature GraphicsData		Defines where the picked data is stored. Valid values are probe features and GraphicsData declarations.
source	ModelEntity		Defines the type of model entity (Plot Group, Geometry, Mesh, Explicit Selection or Player Animation) used to plot in the graphics form object.

Example Code

This line of code displays plot group 5 (pg5) in the graphics object graphics1 in the form with the name Temperature:

```
app.form("Temperature").formObject("graphics1").set("source",
model.result("pg5"));
```

The following line of code using useGraphics is equivalent to the above example: useGraphics(model.result("pg5"), "Temperature/graphics1");

Either method changes the source of the graphics form object and then plots the contents.

To clear the contents of a graphics object, use:

```
app.form("Temperature").formObject("graphics1").set("source",
   (ModelEntity) null);
or equivalently
  useGraphics(null, "Temperature/graphics1");
```

The code below displays the mesh in the model tree node mesh1 in the graphics object graphics1 contained in the card of a card stack:

```
app.form("mesh").formObject("cardstack1").form("card1").formObject("graphi
cs1").set("source", model.mesh("mesh1"));
```

The code below enables data picking for a graphics object and sets the data picking target to a domain point probe:

If a shortcut graphics 1 has been created for the graphics object and a shortcut pdom1 has been created for the probe object, the above can be shortened to:

```
graphics1.set("datapick", true);
graphics1.set("datapicktarget", pdom1);
```

HYPERI INK

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize visible			See "General Properties" on page 59.
text	String	Generated automatically	The text to display on the HyperLink form object.
url	String	пп	The URL to open when the HyperLink is activated.

Example Code

```
with (app.form("form1").formObject("hyperlink1"));
  set("text", "COMSOL");
  set("url", "www.comsol.com");
endwith();
```

IMAGE

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled visible			See "General Properties" on page 59.
icon	String	cube_large.png	Defines the icon name to display in the Image form object. Valid values are images defined in the Images>Libraries node in the application tree.

Example Code

app.form("form1").formObject("image1").set("icon", "compute.png");

INFORMATION CARD STACK

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize fontunderline visible			See "General Properties" on page 59.

Example Code

```
app.form("form1").formObject("infocard1").set("fontunderline", true);
```

INPUT FIELD

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
editable	true false	true	If true then the text in the input field can be edited by the user.
exponent	superscript E	superscript	When set to superscript , exponents are displayed using superscript font. When set to E , exponents are displayed using the character E followed by the exponent value.
inputformatting	on off	off	If the value is on, then numerical values in the input field are formatted according to the exponent, notation and precision properties. When the user is editing the text in the input field, the formatting is temporarily disabled so that the original text can be edited.
maxdouble	double	1000	The maximum allowed double value. This property is only accessible when the Filter setting is set to Double and the corresponding check box is enabled in the Data Validation section.
mindouble	double	O	The minimum allowed double value. This property is only accessible when the Filter setting is set to Double and the corresponding check box is enabled in the Data Validation section.

PROPERTY	VALUE	DEFAULT	DESCRIPTION
maxinteger	Integer	1000	The maximum allowed integer value. This property is only accessible when the Filter setting is set to Integer and the corresponding check box is enabled in the Data Validation section.
mininteger	Integer	0	The minimum allowed integer value. This property is only accessible when the Filter setting is set to Integer and the corresponding check box is enabled in the Data Validation section.
notation	auto scientific decimal	auto	When the value is scientific, numbers are always displayed using scientific notation. When the value is decimal, numbers are never displayed using scientific notation. When the value is auto, the notation depends on the size of the number.
precision	Integer	4	The number of significant digits displayed.
tooltip	String	н	The tooltip displayed when the mouse pointer is located over the input field.

Example Code

app.form("form1").formObject("inputfield1").set("precision", 6);

LINE

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
text	String	пп	Text to display on the line. The text is only displayed for horizontal lines that have Include divider text enabled in the Line object Settings window.
thickness	Integer	1	The line thickness.
linecolor	String	default	The line color.

Example Code

```
app.form("form1").formObject("line1").set("text", "divider text");
app.form("form1").formObject("line1").set("thickness", 10);
app.form("form1").formObject("line1").set("linecolor", blue);
```

LIST BOX

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

```
app.form("form1").formObject("listbox1").set("foreground", "red");
To change the list box contents, modify the corresponding choice list:
app.declaration("choicelist1").appendListRow("new value", "new name");
```

Log

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

Example Code

```
app.form("form1").formObject("log1").set("fontsize", "20");
```

Message Log

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

Example Code

```
app.form("form1").formObject("messages1").set("background", "gray");
```

PROGRESS BAR

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled visible			See "General Properties" on page 59.

To create and update progress information see "Progress Methods" on page 125.

```
app.form("form1").formObject("progressbar1").set("visible", false);
```

RADIO BUTTON

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize fontunderline foreground visible			See "General Properties" on page 59.

To change the display name for a radio button, modify the value in the corresponding choice list.

For a choice list that is used by a radio button, it is not possible to change the value of any row, or to add or remove rows. Only the display name can be changed.

Example Code

```
app.form("form1").formObject("radiobutton1").set("fontitalic", true);
app.declaration("choicelist1").setDisplayName("new name", 0);
```

RESULTS TABLE

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
source	TableFeature		Set the contents of the results table.

To change the contents of the results table use the method useResultsTable or evaluateToResultsTable. See also "GUI-Related Methods" on page 111.

SELECTION INPUT

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
graphics	FormObject		Defines the graphics form object to use when the selection form object is active.
source	SelectionFeature		Defines the model selection the selection form object is connected to.

Example Code

Alternatively, if there are shortcuts sell and g1 to the selectioninput1 and graphics1 form objects:

```
sel1.set("graphics", g1);
```

To change the model selection, assuming sel1 is a shortcut to the selection input form object:

```
sel1.set("source", model.selection("sel2"));
```

SLIDER

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled visible			See "General Properties" on page 59.
max	double	1	The largest possible slider value.
min	double	0	The smallest possible slider value.
steps	integer	5	The number of steps between the min and max values. The number of tick marks is one more than the number of steps.
tooltip	String	нн	The tooltip text.
type	real integer	real	If type has the value integer, then the slider value is restricted to integer values. If type has the value real, the slider value can be a noninteger value.

The min value is allowed to be larger than the max value, in which case the slider behaves as if the values were swapped. The smallest value always corresponds to the left side of the slider.

Example Code

```
app.form("form1").formObject("slider1").set("min", 1);
app.form("form1").formObject("slider1").set("max", 12);
app.form("form1").formObject("slider1").set("steps", 11);
```

SPACER

A spacer object does not have any modifiable properties.

TABLE

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
headers	String[]	Generated automatically	Column headers.
showheaders	boolean	Generated automatically	Show column headers.

To change the contents of the table, change the declaration variables or model entities the table is displaying.

Example Code

```
app.form("form1").formObject("table1").set("enabled", false);
```

TEXT

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
editable	on off	off	If the value is on, the text can be edited by the user of the application. If the value is off, the text can only be changed programmatically.
textalign	left center right	left	Defines how the text is aligned within the text area.
wrap	on off	on	If the value is on, word wrapping is used to break lines that are too long to fit within the text area. If the value is off, long lines may not be completely visible.

```
app.form("form1").formObject("text1").set("textalign", "center");
```

TEXT LABEL

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize fontunderline foreground visible			See "General Properties" on page 59.
text	String	Generated automatically	The text to display in the label when the label is not in multiline mode.
textmulti	String	Generated automatically	The text to display in the label when the label is in multiline mode.

Example Code

```
app.form("form1").formObject("textlabel1").set("text", "custom text");
```

TOGGLE BUTTON

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.
icon	String	н н	The button icon. Valid values are images defined in "Images>Libraries" in the Application Builder.
text	String	Generated automatically	The button text. The text must not be an empty string.
tooltip	String	пп	The button tooltip text.

A button with size large always displays the text, a button with size small displays either the icon or the text. If the icon property is empty, the text is displayed. If the icon property is not empty, the icon is displayed.

TOOLBAR

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

Example Code

app.form("form1").formObject("toolbar1").set("background", "gray");

UNIT

PROPERTY	VALUE	DEFAULT	DESCRIPTION
background enabled font fontbold fontitalic fontsize foreground visible			See "General Properties" on page 59.

Example Code

app.form("form1").formObject("unit1").set("visible", false);

VIDEO

PROPERTY	VALUE	DEFAULT	DESCRIPTION
visible			See "General Properties" on page 59.

Example Code

app.form("form1").formObject("video1").set("visible", false);

WFB PAGE

PROPERTY	VALUE	DEFAULT	DESCRIPTION
visible			See "General Properties" on page 59.
file	String		The file to display. File scheme syntax is supported.
html	String	<html></html>	The HTML code to display.
report	ReportFeature or String		The report feature to display.
type	page url type report	page	Determines which property is used to specify the browser display contents.
url	String	http://www.comsol.com	The URL to display.

Example Code

```
app.form("form1").formObject("webpage1").set("type", "report");
app.form("form1").formObject("webpage1").set("report", "rpt1"));
model.result().report("rpt1"));
model.result().report("rpt1").run();
```

Item

Item objects represent items, toggle items, user defined buttons in Toolbar, Graphics and Table form objects, and submenus in the menu bar, toolbar, ribbon and file menu. The following methods are available:

NAME	SYNTAX	DESCRIPTION
item	<pre>ItemList item()</pre>	Returns the list of subitems.
item	Item item(String name)	Returns the subitem with the specified name.
getParentItem	<pre>Item getParentItem()</pre>	Returns the parent item, or null for a top-level item.
hasProperty	boolean hasProperty(String name)	Returns true if there is a modifiable property with the specified name.

The Item class contains the following properties:

PROPERTY	VALUE	DEFAULT	DESCRIPTION
enabled	on off	on	If the value is on, the item can be activated by the user. If the value is off, the item cannot be activated.
icon	String	Generated automatically	The icon name. Valid values are images defined in Images > Libraries in the Application Builder.
text	String	Generated automatically	The text for a menu or ribbon item.
title	String	Generated automatically	The title text for a menu or submenu.
tooltip	String	пп	The tooltip text.
visible	on off	on	Controls whether the item is visible or not.

In order for an item to be enabled, the enabled property needs to have the value on for the item itself as well as for all of its parents. In other words, disabling an item also disables all of its subitems.

Item objects also include separators. However, separators do not have any accessible properties.

Item objects for user-defined buttons do not have the title and tooltip properties. For Table form objects, predefined items such as "move up" and "move down" do not have any modifiable properties.

EXAMPLE CODE

```
app.mainWindow().menuBar("menu1").set("title", "new title");
app.mainWindow().menuBar("menu1").item("toggle_item1").set("text",
"test");
```

Data Source

A DataSource object is either a Scalar, Array 1D, Array 2D, ChoiceList a UnitSet or a G

SCALAR, ARRAY ID, AND ARRAY 2D METHODS

The methods described in the following table are applicable for Scalar, Array 1D, and Array 2D objects (of types String, Boolean, Integer, Double). These methods are used to manipulate such variable objects during run time.

NAME	SYNTAX	DESCRIPTION
getBoolean	boolean getBoolean()	Gets the Boolean value stored in the data source.
getBooleanArray	boolean[] getBooleanArray()	Gets the Boolean array value stored in the data source.
getBooleanMatrix	boolean[][] getBooleanMatrix()	Gets the Boolean matrix value stored in the data source.
getDouble	<pre>double getDouble()</pre>	Gets the double value stored in the data source.
getDoubleArray	<pre>double[] getDoubleArray()</pre>	Gets the double array value stored in the data source.
getDoubleMatrix	<pre>double[][] getDoubleMatrix()</pre>	Gets the double matrix value stored in the data source.
getInt	<pre>int getInt()</pre>	Gets the int value stored in the data source.
getIntArray	<pre>int[] getIntArray()</pre>	Gets the int array value stored in the data source.
getIntMatrix	<pre>int[][] getIntMatrix()</pre>	Gets the int matrix value stored in the data source.
getString	String getString()	Gets the String value stored in the data source.
getStringArray	String[] geStringArray()	Gets the String array value stored in the data source.
getStringMatrix	String[][] getStringMatrix()	Gets the String matrix value stored in the data source.
set	<pre>set(boolean value) set(boolean[] value) set(boolean[][] value) set(double[] value) set(double[] value) set(double[][] value) set(int value) set(int[] value) set(int[][] value) set(String value) set(String[]] value) set(String[][] value)</pre>	Set the value stored in the data source. Available methods depend on the type of the underlying declaration.

EXAMPLE CODE

```
// Get a scalar double declaration.
DataSource ds = app.declaration("var");
// The 'var' declaration is a scalar double so we use the getDouble method
// to read its value.
double cur = ds.getDouble();
// Modifying the local field 'cur' doesn't affect the value stored in the
// data source 'ds'.
cur = cur + 1;
// Set the value of the data source.
ds.set(cur);
```

CHOICE LIST AND UNIT SET METHODS

The methods described in the following table are applicable for both ChoiceList and UnitSet objects. These methods are used to manipulate choice lists and unit sets during run time.

NAME	SYNTAX	DESCRIPTION
setListRow	<pre>setListRow(String value, String displayName, int row)</pre>	Sets the value and display name for the given row (0-based). If the row is equal to the length of the list, a new row is added.
setList	<pre>setList(String[] values, String[] displayNames)</pre>	Sets all of the values and display names, replacing the contents of the choice list or unit set.
setValue	setValue(String value, int row)	Sets the value for the given row (0-based). If the row is equal to the length of the list, a new row is added with the value and an empty display name.
setDisplayName	<pre>setDisplayName(String displayName, int row)</pre>	Sets the display name for the given row (0-based). If the row is equal to the length of the list, a new row is added with the display name and an empty value.
getValue	String getValue(int row)	Returns the value for the given row (0-based).
getDisplayName	String getDisplayName(int row)	Returns the display name for the given row (0-based).
getDisplayName	String getDisplayName(String value)	Returns the display name for the row with the given value.
getValues	<pre>String[] getValues()</pre>	Returns all values as an array.

NAME	SYNTAX	DESCRIPTION
getDisplayNames	<pre>String[] getDisplayNames()</pre>	Returns all display names as an array.
addListRow	addListRow(String value, String displayName, int row)	Inserts a new row with the given value and display name at the specified row (0-based).
appendListRow	<pre>appendListRow(String value, String displayName)</pre>	Inserts a new row with the given value and display name at the end of the list.
removeListRow	removeListRow(int row)	Removes the given row (0-based) from the list.

Example Code

The code below adds the string Aluminum 3004 to a choice list. Note that the choice list index starts at 0, whereas the material tags start at 1 (mat1, mat2, mat3, and mat4).

```
ChoiceList choiceList = getChoiceList("choicelist1");
choiceList.setListRow("mat4", "Aluminum 3004", 3);
```

For more information on using choice lists for changing materials, see the book *Introduction to Application Builder*.

UNIT SET METHODS

When the object is a UnitSet the following additional methods are also available:

NAME	SYNTAX	DESCRIPTION
set	set(String value)	Switch unit for the unit set.
getString	String getString()	Returns the currently selected value for the unit set.
getString	String getString(String unitList)	Returns the selected unit for the given unit list.

GRAPHICS DATA METHODS

When the object is a GraphicsData the following methods are available:

NAME	SYNTAX	DESCRIPTION
set	set(String name, String value) set(String name, double value) set(String name, double[] value)	Sets a new value for the property with the specified name.
getString	String getString(String name)	Returns the value of the specified property as a string.

NAME	SYNTAX	DESCRIPTION
getDouble	double getDouble(String name)	Returns the value of the specified property as a double value.
getDoubleArray	<pre>double[] getDoubleArray(String name)</pre>	Returns the value of the specified property as a double array value.

The GraphicsData class has the following properties:

PROPERTY	VALUE	DEFAULT	DESCRIPTION
coord	double[]	0, 0, 0	Point location of picked data. Array of I, 2, 3 or 6 elements, corresponding to ID, 2D, 3D, or Smith plot, respectively.
depth	double	0	Point along a line when data picking in a domain. Valid values are between 0 and 1, inclusive.
edim	domain boundary	domain	Geometric entity level.
eval	double	0	Evaluated value of picked data.
method	pointnormal pointdir twopoints none	pointnormal	Method of selecting a point in a 3D geometry.
twopoint	first second	first	Point being picked in the twopoints line entry method.

Example code

The following code enables data picking for the graphics1 object, connects it to the graphicsdata1 object and sets some properties on the graphicsdata1 object:

Method Class

The Method class is used to represent a method. The following method is available for a Method object:

NAME	SYNTAX	DESCRIPTION
run	Object run(Object input)	Run the method with the specified
		input parameters.

The following code exemplifies using a Method object:

```
// Get a Method object representing a Form Method.
Method m = app.form("form1").method("method1");
// The method takes a String parameter and returns a double.
double res = (Double) m.run("input");
```

Form, Form Object, and Item List Methods

The FormList, FormObjectList, and ItemList classes have the following methods:

NAME	SYNTAX	PURPOSE
names	String[] names()	Returns an array of names for all objects in the list.
size	int size()	Returns the number of objects in the list.
index	<pre>int index(String name)</pre>	Returns the 0-based position of the object with a given name in the list.
get	Form get(String name) FormObject get(String name) Item get(String name)	Returns the object with a given name.
get	Form get(int index) FormObject get(int index) Item get(int index)	Returns the object at a certain index.

Additionally the FormList class has the following methods:

NAME	SYNTAX	PURPOSE
hasProperty	boolean hasProperty(String name)	Returns true if there is a modifiable property with the specified name.

It is also possible to use a list in an enhanced for loop to operate on all objects in the list.

In the following example, the background color is set to red in all forms, by looping over all forms:

```
for (Form f : app.form()) { // app.form() is of type FormList
   f.set("background", "red");
}
```

The Built-in Method Library for the Application Builder

This section lists built-in methods available in the Method editor in addition to the methods that operate on the model and application objects. For more information on the model object and its methods, refer to earlier sections of this book and the *Programming Reference Manual*. For more information on the application object, see "The Application Object" on page 55. Some of the listings have associated example code but for more extensive programming examples, see "Programming Examples" on page 150.

The syntax rules are those of the Java® programming language. Note that each line of code needs to end with a semicolon (;), but the semicolon is omitted in the listings below.

Model Utility Methods

The following table summarizes the model utility methods for querying, creating, loading, and saving model objects. The model object is stored on the MPH file format.

NAME	SYNTAX	DESCRIPTION
clearModel	clearModel(Model model) clearModel(String tag)	Remove everything from the model except for the application part and the things you can change on the root node in the Model Builder, such as thumbnail, comment and author.
createModel	Model createModel(String tag)	Creates a new model with the given tag.
createModel	Model createModel()	Create a new model with a unique tag.
getModel	Model getModel(String tag)	Returns the model with a specified tag.
loadModel	Model loadModel(String tag, String filename)	Loads a model with a specified tag from a file.
loadModel	Model loadModel(String filename)	Loads a model from a file. The model is given a unique tag.
loadProtectedModel	Model loadProtectedModel(String tag, String filename, String password)	Loads a password protected model with a specified tag from a file.

NAME	SYNTAX	DESCRIPTION
loadProtectedModel	Model loadProtectedModel(String filename, String password)	Loads a password protected model from a file. The model is given a unique tag.
loadRecoveryModel	Model loadRecoveryModel(String tag, String foldername)	Loads a model from a recovery directory/folder structure.
loadRecoveryModel	Model loadRecoveryModel(String foldername)	Loads a model from a recovery directory/folder structure. The model is given a unique tag.
modelTags	<pre>String[] modelTags()</pre>	Returns an array of model tags for all loaded models, including the embedded model.
removeModel	removeModel(String tag) removeModel(Model model)	Removes a model. The embedded model cannot be removed.
saveModel	<pre>saveModel(Model model, String filename)</pre>	Saves a model to a file. The filename can be a file scheme path or (if allowed by security settings) a server file path.
uniqueModeltag	String uniqueModeltag(String prefix)	Returns a model tag that is not in use.
getComsolVersion	<pre>getComsolVersion()</pre>	Returns the current software version as a string.

Example Code

The code below loads a model using loadModel, presented in the table above. It extracts the x-, y-, and z-coordinates of all mesh nodes and stores them in a 2D double array coords[3][N], where N is the number of mesh nodes. The individual x-, y-, and z- coordinates are available as the length-N 1D arrays coords[0], coords[1], coords[2], respectively. (The node locations can be plotted by using the Cut Point 3D data set in combination with a 3D Point Trajectories plot.)

```
Model extmodel = loadModel("C:\\Paul\\pacemaker_electrode.mph");
SolverFeature step = extmodel.sol("sol1").feature("v1");
XmeshInfo xmi = step.xmeshInfo();
XmeshInfoNodes nodes = xmi.nodes();
double[][] coords = nodes.coords();
```

For more information on methods operating on the model object, see the *Programming Reference Manual*.

Note that to make the code above platform independent for use in an application you can instead use the common application file folder:

```
Model extmodel = loadModel("common:///pacemaker electrode.mph");
```

License Methods

The license methods read the license number and check out or test the licenses of the current session or for an MPH file. This functionality can be used, for example, to limit the use of an application to one or a few license numbers or to dynamically adapt functionality of an application depending on which product licenses are available.

NAME	SYNTAX	DESCRIPTION
checkoutLicense	<pre>boolean checkoutLicense(String product)</pre>	Checks out licenses for all specified products. If not all licenses can be checked out, no licenses are checked out.
checkoutLicenseFor File	boolean checkoutLicenseForFile(String file)	Checks out licenses required to use a given MPH file. If not all required licenses can be checked out, no licenses are checked out.
checkoutLicenseFor FileOnServer	<pre>boolean hasLicenseForFileOnServer(String file);</pre>	Checks out licenses required to use a given MPH file. If not all required licenses can be checked out, no licenses are checked out.
getLicenseNumber	String license = getLicenseNumber()	Returns a string with the license number for the current session.
hasProduct	boolean hasProduct(String product)	Returns true if the COMSOL installation contains the software components required for running the specified products. Code completion can be used to get a list of valid product names.
hasProductForFile	boolean hasProductForFile(String file)	Returns true if the COMSOL installation contains the software components required for running the products required by a given MPH file.
hasProductForFileO nServer	<pre>boolean checkoutLicenseForFileOnServer(String file);</pre>	Returns true if the COMSOL installation contains the software components required for running the products required by a given MPH file.

EXAMPLE CODE

The following code tries to check out a license for the AC/DC Module, and displays an error message if it fails:

```
if (!checkoutLicense("ACDC"))
  alert("There seems to be a problem. Please contact Alice and Bob at
123-456-7890.");
```

You can use this to customize license error messages by calling a method containing this code before any add-on product specific features are used by the application.

In the Application Builder root node you can further select the **Ignore license errors during launch** check box. This will make it possible for users to start an application regardless of which licenses are available. However, this will not work if the application, at startup, uses features required by an add-on product. The application has to be created in such a way that the add-on product specific features are not used in the start-up phase of the application but instead are deferred to later in the work-flow.

To emulate a scenario where there are not enough available licenses you can, for example, disable one or more products in the **Licensed and Used Products in Session** dialog box, available from the **File** menu in the COMSOL Desktop environment.

The following code tests if the COMSOL installation has the capability to use an MPH file:

```
boolean ok = hasProductForFile("model file.mph");
```

Note that even if hasProductForFile return true, in a floating network license situation there may not be any free licenses to check out. If your application is going to process several MPH files and you want to make sure all licenses are checked out before the processing starts, instead use the checkoutLicense or checkoutLicenseForFile methods.

LICENSE FEATURE STRINGS

The following table contains the product strings for all add-on products in the COMSOL 5.5 product suite that can be used by the method checkoutLicense:

PRODUCT/FEATURE	FEATURE NAME
AC/DC Module	ACDC
Acoustics Module	ACOUSTICS
Batteries & Fuel Cells Module	BATTERIESANDFUELCELLS
CAD Import Module	CADIMPORT
CFD Module	CFD

PRODUCT/FEATURE	FEATURE NAME
Chemical Reaction Engineering Module	CHEM
Corrosion Module	CORROSION
Design Module	DESIGN, CADIMPORT
ECAD Import Module	ECADIMPORT
Electrochemistry Module	ELECTROCHEMISTRY
Electrodeposition Module	ELECTRODEPOSITION
Fatigue Module	FATIGUE
File Import for CATIA V5	CATIA5
Geomechanics Module	GEOMECHANICS
Heat Transfer Module	HEATTRANSFER
LiveLink™ for AutoCAD®	LLAUTOCAD, CADIMPORT
LiveLink [™] for PTC® Creo® Parametric ™	LLCREOPARAMETRIC, CADIMPORT
LiveLink™ for Excel®	LLEXCEL
LiveLink™ for Inventor®	LLINVENTOR, CADIMPORT
LiveLink™ for MATLAB®	LLMATLAB
LiveLink™ for Revit®	LLREVIT, CADIMPORT
LiveLink™ for PTC® Pro/ENGINEER®	LLPROENGINEER, CADIMPORT
LiveLink™ for Solid Edge®	LLSOLIDEDGE, CADIMPORT
LiveLink™ for SOLIDWORKS®	LLSOLIDWORKS, CADIMPORT
Material Library	MATLIB
MEMS Module	MEMS
Metal Processing Module	METALPROCESSING
Microfluidics Module	MICROFLUIDICS
Mixer Module	MIXER
Molecular Flow Module	MOLECULARFLOW
Multibody Dynamics Module	MULTIBODYDYNAMICS
Nonlinear Structural Materials Module	NONLINEARSTRUCTMATERIALS
Optimization Module	OPTIMIZATION
Particle Tracing Module	PARTICLETRACING
Pipe Flow Module	PIPEFLOW
Plasma Module	PLASMA
Porous Media Flow Module	POROUSMEDIAFLOW

PRODUCT/FEATURE	FEATURE NAME
Ray Optics Module	RAYOPTICS
RF Module	RF
Rotordynamics Module	ROTORDYNAMICS
Semiconductor Module	SEMICONDUCTOR
Structural Mechanics Module	STRUCTURALMECHANICS
Subsurface Flow Module	SUBSURFACEFLOW
Wave Optics Module	WAVEOPTICS

File Methods

File methods are used to read and write data to a file or portions of a file. Note that higher-level techniques for reading and writing to files are available from within the Application Builder user interface. For more information, see the book *Introduction to Application Builder* and "GUI Command Methods" on page 122.

NAME	SYNTAX	DESCRIPTION
readFile	String readFile(String name)	Returns the contents in the given file name as a string. The string name is the absolute path to a file or a path given by the file scheme syntax.
openFileStreamReader	CsReader openFileStreamReader(String name)	Returns a CsReader that can be used to read line-by-line or character-by-character from the given file name .
openBinaryFileStreamReader	CsBinaryReader openBinaryFileStreamReader(String name)	Returns a CsBinaryReader that can be used to read from the given file byte-by-byte.
readMatrixFromFile	<pre>double[][] readMatrixFromFile(String name)</pre>	Reads the contents of the given file into a double matrix. The file has the same spreadsheet type format as available in the model tree Export node.

NAME	SYNTAX	DESCRIPTION
readStringMatrixFromFile	<pre>String[][] readStringMatrixFromFile(String name)</pre>	Reads the contents of the given file into a string matrix. The file has the same spreadsheet type format as available in the model tree Export node.
readCSVFile	<pre>String[][] readCSVFile(String name)</pre>	Reads a file with comma-separated values (CSV file) into a string matrix. Expects file to use the RFC 4180 format for CSV.
writeFile	<pre>writeFile(String name, String contents)</pre>	Writes the given string contents to the given file name.
writeFile	writeFile(String name, String contents, boolean append)	Writes the given string contents to the given file name. If append is true, then the contents are appended instead of overwritten.
writeFile	<pre>writeFile(String name, double[][] data)</pre>	Writes the array data to the given file. The spreadsheet format is used, which means it can be read by readMatrixFromFile.
writeFile	<pre>writeFile(String name, double[][] data, boolean append)</pre>	Writes the array data to the given file. The spreadsheet format is used, which means it can be read by readMatrixFromFile. If append is true, then the contents are appended instead of overwritten.
writeFile	<pre>writeFile(String name, String[][] data)</pre>	Writes the array data to the given file. The spreadsheet format is used, which means it can be read by readStringMatrixFromFile.
writeFile	<pre>writeFile(String name, String[][] data, boolean append)</pre>	Writes the array data to the given file. The spreadsheet format is used, which means it can be read by readStringMatrixFromFile. If append is true, then the contents are appended instead of overwritten.

NAME	SYNTAX	DESCRIPTION
openFileStreamWriter	CsWriter openFileStreamWriter(String name)	Returns a CsWriter that can write to the given file.
openFileStreamWriter	CsWriter openFileStreamWriter(String name, boolean append)	Returns a CsWriter that can write to the given file. If append is true, then the contents are appended instead of overwritten.
openBinaryFileStreamWriter	CsBinaryWriter openBinaryFileStreamWriter(Stri ng name)	Returns a CsBinaryWriter that can be used to write to the given file byte-by-byte.
openBinaryFileStreamWriter	CsBinaryWriter openBinaryFileStreamWriter(String name, boolean append)	Returns a CsBinaryWriter that can be used to write to the given file byte by byte. If append is true, then the contents are appended instead of overwritten.
writeCSVFile	<pre>writeCSVFile(String name, String[][] data)</pre>	Writes the given string array data to a CSV file. The RFC 4180 format is used for the CSV.
writeCSVFile	<pre>writeCSVFile(String name, String[][] data, boolean append)</pre>	Writes the given string array data to a CSV file. The RFC 4180 format is used for the CSV. If append is true, then the contents are appended instead of overwritten.
writeCSVFile	<pre>writeCSVFile(String name, double[][] data)</pre>	Writes the given double array data to a CSV file. The RFC 4180 format is used for the CSV.
writeCSVFile	<pre>writeCSVFile(String name, double[][] data, boolean append)</pre>	Writes the given double array data to a CSV file. The RFC 4180 format is used for the CSV. If append is true, then the contents are appended instead of overwritten.

NAME	SYNTAX	DESCRIPTION
exists	boolean exists(String name)	Tests whether a file with the given name exists.
		If the name is not a file scheme path name or an absolute path, then the method first finds out whether a file with file scheme path embedded:/// + argument exists. If such a file does not exist, then it tests whether there is a file with a matching name in the current working directory.
deleteFile	deleteFile(String file)	Delete a file with the given name if it exists. The file is deleted on the server,. The name can use a file scheme path.
copyFile	<pre>copyFile(String sourceFile, String destFile)</pre>	Copies a file on the server. Both the source and target names can use file scheme paths.
importFile	<pre>importFile(String name) importFile(String name, String[] fileTypes)</pre>	Displays a file browser dialog box and uploads the selected file to the file declaration with the given name. After this, the uploaded file can be accessed with upload:/// <name>. The optional fileTypes argument can be used to filter which file types are available for selection in the file browser. The easiest way to get a list of valid file types is to use code completion in the method editor.</name>

NAME	SYNTAX	DESCRIPTION
importFile	<pre>importFile(ModelEntity entity, String name)</pre>	Displays a file browser dialog box and uploads the selected file to the Filename text field in the given model object entity. This defines an input file that the application will need at a later stage. For example, the Filename of an interpolation function accessed with model.func(' <tag>')). The uploaded file can be accessed with upload:///<tag>/filename.</tag></tag>
writeExcelFile	<pre>writeExcelFile(String name, String[][] data)</pre>	Writes the given string array data starting from the first cell in the first sheet of an Excel file. This method requires LiveLink™ for Excel®.
writeExcelFile	<pre>writeExcelFile(String name, String sheet, String cell, String[][] data)</pre>	Writes the given string array data starting from the specified cell in the specified sheet of an Excel file. This method requires LiveLink [™] for Excel [®] .
readExcelFile	<pre>String[][] readExcelFile(String name)</pre>	Reads the first sheet of an Excel file, starting from the first cell, into a String[]. This method requires LiveLink [™] for Excel [®] .
readExcelFile	String[][] readExcelFile(String name, String sheet, String cell)	Reads the specified sheet of an Excel file, starting from the specified cell, into a String∏. This method requires LiveLink™ for Excel®.

NAME	SYNTAX	DESCRIPTION
getFilePath	String getFilePath(String name)	Returns the absolute server file path of the server proxy file corresponding to a certain file scheme path, or null if the server proxy file for the given path does not exist. This method can be used to pass the path to, for example, a file using the temp:/// scheme to external code or an application. In addition, this method is used to retrieve the file name of an uploaded file when using the file scheme upload://inputFile, for example by using a File declaration together with a File Import form object.
getClientFileName	String getClientFileName(String name)	Returns the original name of an uploaded file on the client file system (or null if there is no uploaded file matching the given file scheme path). This method is only useful for providing user interface feedback. For example, to get information on which uploaded file is being used. There is no guarantee that the original file would still exist on the client or even that the current client would be the same as the original client.

NAME	SYNTAX	DESCRIPTION
getClientFilePath	String getClientFilePath(String name)	Returns the original path of an uploaded file on the client file system (or null if there is no uploaded file matching the given file scheme path). Returns only the file name part of the path when called from an application running in a web browser. This method is only useful for providing user interface feedback. For example, to get information on which uploaded file is being used. There is no guarantee that the original file would still exist on the client or even that the current client would be the same as the original client.
createDirectory	createDirectory(String name)	Creates a file directory name, see examples below in the Example Code section.

EXAMPLE CODE

This line of code copies the uploaded file file1 to the temp folder with new file name file2.mphbin and then prompts the user to save the file to a any location.

```
copyFile("upload:///file1", "temp:///file2.mphbin");
fileSaveAs("temp:///file2.mphbin");
```

This line of code deletes the file file2.mphbin from the temp folder.

```
deleteFile("temp:///file2.mphbin");
```

This line of code creates a directory in the user folder, as specified in Preferences. createDirectory("user://a/b");

This line of code creates a directory in the Temp folder under C:.

```
createDirectory("C:\\Temp\\a\\b");
```

Operating System Methods

Operating system methods are used for accessing operating system information and commands from an application.

NAME	SYNTAX	DESCRIPTION
executeOSCommand	String executeOSCommand(String command, String params)	Executes the OS command with the given command (full path) and parameters. Execution times out after a default 180 seconds. Returns everything the process printed to its out stream as a string. When applicable, the command is run server side.
executeOSCommand	String executeOSCommand(String command, int timeoutSec, String params)	Executes the OS command with the given command (full path) and parameters. Returns everything the process printed to its out stream as a string. The execution is forcibly stopped after timeoutSec seconds if the command has not finished. To disable the timeout functionality, timeoutSec value 0 can be used. When applicable, the command is run server side.
fileOpen	fileOpen(String name)	Opens the file represented by name with the associated program on the client. Also see the section "Example code".
getUser	String username = getUser()	Returns the username of the user that is running the application. If the application is not run from COMSOL Server, then the value of the preference setting General>Username>Name is returned.
openURL	openURL(String url)	Opens a URL in the default browser on the client.

NAME	SYNTAX	DESCRIPTION
playSound	playSound(String name)	Plays the sounds in the given file on the client. Only .wav files are supported; no external libraries are required.
playSound	playSound(double hz, int millis)	Plays a signal at a given frequency hz and with given duration millis in milliseconds on the client.

EXAMPLE CODE

The line of code below plays one of the sounds available in the data/sounds folder of the COMSOL installation and has been embedded in the application and stored in the Sounds library.

```
playSound("embedded:///success 1.wav");
```


In the command sequence of a form object, this is equivalent to selecting a sound node under **Libraries** and clicking **Run**.

The line of code below opens a PDF file embedded in the application and stored in the File library.


```
fileOpen("embedded:///tubular_reactor.pdf");
```

In the command sequence of a form object, this is equivalent to selecting an **Open File** node under **GUI Commands>File Commands** and clicking **Run**.

As an alternative technique, you can call a method in a command sequence with an input argument, as shown in the example below. The figure below shows a method b_open_pdf that opens a file with filename as an input argument.



The figure below shows the corresponding command sequence for a ribbon menu item.



Note that the same functionality is available from a command sequence by selecting the editor tree node **GUI Commands>File Commands>Open File**.

This line of code opens the COMSOL home page in the default browser: openURL("http://www.comsol.com");

This line of code runs an application by means of an OS command:

```
\label{lem:comsol} execute OSCommand ("C:\COMSOL55\Multiphysics\bin\win64\comsol.exe", "-run", "C:\Work\tubular\_reactor.mph");
```

Email Methods

Email methods are used for sending emails from an application, typically with attachments containing results from a simulation.

NAME	SYNTAX	DESCRIPTION
emailFromAddress	String emailFromAddress()	Returns the email from address from the COMSOL Server or preferences setting.
sendEmail	<pre>sendEmail(String subject, String bodyText)</pre>	Sends an email to the default recipient(s) with the specified subject and body text.
sendEmail	<pre>sendEmail(String subject, String bodyText, ModelEntity modelEntity)</pre>	Sends an email to the default recipient(s) with the specified subject, body text, and zero or more attachments created from Report, Export, and Table nodes in the embedded model.
sendEmail	<pre>sendEmail(String toAddress, String subject, String bodyText, ModelEntity modelEntity)</pre>	Sends an email to the specified recipient(s) with the specified subject, body text, and zero or more attachments created from Report, Export, and Table nodes in the embedded model.
userEmailAddress	String userEmailAddress()	Returns the user email address(es) corresponding to the currently logged in user, or an empty string if the user has not configured an email address.

Email Class Methods

The class EmailMessage can be used to create custom email messages.

NAME	SYNTAX	DESCRIPTION
EmailMessage	<pre>EmailMessage mail = new EmailMessage()</pre>	Creates a new EmailMessage object.
EmailMessage.setSer ver	mail.setServer(String host, int port)	Sets the email (SMTP) server host and port to use for this email message.


NAME	SYNTAX	DESCRIPTION
EmailMessage.setUse r	mail.setUser(String name, String password)	Sets the username and password to use for email (SMTP) server authentication. This method must be called after the setServer method.
EmailMessage.setSec urity	mail.setSecurity(String security)	Sets the connection security type for email (SMTP) server communication. Valid values are 'none', 'starttls' and 'tls'. This method must be called after the setServer method.
EmailMessage.setFro	mail.setFrom(String fromAddress)	Sets the from address.
EmailMessage.setTo	mail.setTo(String to)	Sets the to addresses.
EmailMessage.setCc	mail.setCc(String cc)	Sets the cc addresses.
EmailMessage.setBcc	mail.setBcc(String bcc)	Sets the bcc addresses.
EmailMessage.setSub ject	mail.setSubject(String subject)	Sets the email subject line. Note that newline characters are not allowed.
EmailMessage.setBod yText	mail.setBodyText(String body)	Sets the email body as plain text. An email can contain both a text and an HTML body.
EmailMessage.setBod yHtml	mail.setBodyHtml(String body)	Sets the email body as HTML text. An email can contain both a text and an HTML body.
EmailMessage.attach File	mail.attachFile(String filename)	Adds an attachment from a file. The attachment MIME type is determined by the file name extension.
EmailMessage.attach File	<pre>mail.attachFile(String filename, String mimeType)</pre>	Adds an attachment from a file with the specified MIME type.
EmailMessage.attach FromModel	<pre>mail.attachFromModel(ModelEntity modelEntity)</pre>	Adds an attachment created from a report, export, or table feature in the model.
EmailMessage.attach Text	<pre>mail.attachText(String text, String mimeSubType)</pre>	Adds a text attachment with a specified sub-MIME type, such as plain or HTML.

NAME	SYNTAX	DESCRIPTION
EmailMessage.attach Binary	<pre>mail.attachBinary(byte[] binary, String mimeType)</pre>	Adds an attachment from a byte array with the specified MIME type.
EmailMessage.send	mail.send()	Sends the email to the email (SMTP) server. An email object can only be sent once.

Each to, cc, and bcc address string can contain multiple email addresses separated by a comma or a semicolon character. Whitespace is allowed before and after the separator character.

EMAIL PREFERENCES

To set preferences for an outgoing email (SMTP) server, open the **Email** page of the **Preferences** dialog box, as shown in the figure below.



COMSOL Server provides a similar set of email preferences.

EXAMPLE CODE


The following code sends an email and attaches a report:

```
EmailMessage mail = new EmailMessage();
mail.setTo(email_to);
mail.setSubject("Tubular Reactor Simulation");
mail.setBodyText("The computation has finished. Please find the report attached.");
mail.attachFromModel(model.result().report("rpt1"));
mail.send();
```

This code is run in the Tubular Reactor application, which is available as an application example in the Application Libraries. The figure below shows part of the user interface with an input field for the email address.



The figure below shows the corresponding form object and **Settings** window.



The following code is similar but also configures the email server settings.

```
EmailMessage mail = new EmailMessage();
mail.setServer("smtp.myemail.com", 587);
mail.setUser("user@myemail.com", "password");
mail.setSecurity("starttls");
mail.setFrom("user@myemail.com");
mail.setTo("otheruser@somedomain.com");
mail.setSubject("Tubular reaction simulation");
mail.setBodyText("The computation has finished");
mail.send();
```

GUI-Related Methods

The graphical user interface (GUI) related methods are used for displaying dialog boxes with messages, editing form objects and user interface content, getting run-time properties of the application user interface, and running methods.

NAME	SYNTAX	DESCRIPTION
Call a method directly	<methodname>()</methodname>	Call a method from the Methods list by using its name, for example, method1(), method2().
callMethod	callMethod(String name)	Alternate way to call a method from the Methods list; used internally and in cases of name collisions.
useGraphics	useGraphics(ModelEntity entity, String name) useGraphics(ModelEntity entity, FormObject graphics)	Plots the given entity (Plot Group, Geometry, Mesh, Explicit Selection or Player Animation) in the graphics form object given by the name, name path, or graphics form object in the second argument.
useForm	useForm(String name)	Shows the form with the given name in the current main window. Equivalent to the use method of a Form object; see below.
closeDialog	closeDialog(String name)	Closes the form, shown as a dialog box, with the given name.

NAME	SYNTAX	DESCRIPTION
dialog	dialog(String name)	Shows the form with the given name as a dialog box. Equivalent to the dialog method of a Form object; see below.
alert	alert(String text)	Stops execution and displays an alert message with the given text.
alert	alert(String text, String title	Stops execution and displays an alert message with the given text and title.
confirm	String confirm(String text)	Stops execution and displays a confirmation dialog box with the given text. It also displays two buttons, "Yes" and "No". The method returns "Yes" or "No" depending on what the user clicks.
confirm	String confirm(String text, Str title)	Stops execution and displays a confirmation dialog box with the given text and title. It also displays two buttons, "Yes" and "No". The method returns "Yes" or "No" depending on what the user clicks.
confirm	String confirm(String text, Str title, String yes, String no)	Stops execution and displays a confirmation dialog box with the given text and title. It also displays two buttons with the given strings as labels. The method returns the label of the button that the user clicks.

NAME	SYNTAX	DESCRIPTION
confirm	String confirm(String text, String title, String yes, String no, String cancel)	Stops execution and displays a confirmation dialog box with the given text and title. It also displays three buttons with the given strings as labels. The method returns the label of the button that the user clicks.
error	error(String message)	Stops execution and opens an error dialog box with the given message.
error	error(String message, Throwable cause)	Stops execution and opens an error dialog box with the given message including the underlying cause of class Throwable, the general Java exception class, or one of its subclasses, such as RuntimeException. This can be used to "wrap" native COMSOL Multiphysics error messages with custom error messages.
request	String request(String text)	Stops execution and displays a dialog box with a text field, requesting input from the user. The given text is the label of the text field. The method returns the entered text or null if the cancel button is clicked.
request	String request(String text, String defaultString)	Stops execution and displays a dialog box with a text field, requesting input from the user. The given text is the label of the text field and the default string is the text initially shown in the text field. The method returns the entered text or null if the cancel button is clicked.

NAME	SYNTAX	DESCRIPTION
request	String request(String text, String title, String defaultString)	Stops execution and displays a dialog box with a text field, requesting input from the user. The given text is the label of the text field, the default string is the text initially shown in the text field, and the title is the title of the dialog box. The method returns the entered text or null if the cancel button is clicked.
message	message(String message)	Sends a message to the message log if available in the application.
message	message(arg)	Sends a message arg to the message log. For an application this requires that a message log is added to the application user interface. The input argument arg can be a scalar, ID array, or 2D array of the types string, double, int or Boolean.
evaluateToResultsTable	evaluateToResultsTable(NumericalFe ature entity, String name, boolean clear) evaluateToResultsTable(NumericalFe ature entity, FormObject graphics, boolean clear)	Evaluates the given entity, a Derived Value, in the table object given by the name, name path, or graphics form object in the second argument, which will then be the default target for the evaluations of the Derived Value. If the third argument is true, the table is cleared before adding the new data, otherwise the data is appended.

NAME	SYNTAX	DESCRIPTION
evaluateToDoubleArray2D	<pre>double[][] evaluateToDoubleArray2D(NumericalF eature entity)</pre>	Evaluates the given entity, a Derived Value, and returns the non-parameter column part of the real table that is produced as a double matrix. All settings in the numerical feature are respected, but those in the current table connected to the numerical feature are ignored.
evaluateToIntegerArray2D	<pre>int[][] evaluateToIntegerArray2D(Numerical Feature entity)</pre>	Evaluates the given entity, a Derived Value, and returns the non-parameter column part of the real table that is produced as an integer matrix. All settings in the numerical feature are respected, but those in the current table connected to the numerical feature are ignored.
evaluateToStringArray2D	String[][] evaluateToStringArray2D(NumericalF eature entity)	Evaluates the given entity, a Derived Value, and returns the non-parameter column part of the, potentially complex, table that is produced as a string matrix. All settings in the numerical feature are respected but those in the current table connected to the numerical feature are ignored.
useResultsTable	useResultsTable(TableFeature tableFeature, String resultsTable) useResultsTable(TableFeature tableFeature, FormObject resultsTable)	Shows the values from the tableFeature in the resultsTable form object.

NAME	SYNTAX	DESCRIPTION
getChoiceList	ChoiceList getChoiceList(String name)	Returns an object of the type ChoiceList, representing a choice list node under the declarations branch. The type ChoiceList has methods that make it easier to change the matrix value with respect to changing and accessing values and display names individually.
setFormObjectEnabled	<pre>setFormObjectEnabled(String name, boolean enabled)</pre>	Sets the enable state for the form object specified by the name or name path.
setFormObjectVisible	<pre>setFormObjectVisible(String name, boolean visible)</pre>	Sets the visible state for the form object specified by the name or name path.
setFormObjectText	<pre>setFormObjectText(String name, String text)</pre>	Sets the text for the form object specified by the name or name path in the second argument. This method throws an error if it is impossible to set a text for the specified form object.
setFormObjectEditable	setFormObjectEditable(String name, boolean editable)	Sets the editable state for the form object specified by the name or name path. This functionality is only available for text field objects.
setMenuBarItemEnabled	setMenuBarItemEnabled(String name, boolean enabled)	Sets the enable state for the menu bar item specified by the name or name path (from menu bar) in the first argument.
setMainToolbarItemEnabled	setMainToolbarItemEnabled(String name, boolean enabled)	Sets the enable state for the main toolbar item specified by the name or name path (from main toolbar) in the first argument.

NAME	SYNTAX	DESCRIPTION
setFileMenuItemEnabled	setFileMenuItemEnabled(String name, boolean enabled)	Sets the enable state for the file menu item specified by the name or name path (from file menu) in the first argument.
setRibbonItemEnabled	setRibbonItemEnabled(String name, boolean enabled)	Sets the enable state for the ribbon item specified by the name or name path (from main window) in the first argument.
setToolbarItemEnabled	setToolbarItemEnabled(String name, boolean enabled)	Sets the enable state for the toolbar form object item specified by the name or name path in the first argument.
useView	<pre>useView(View view, String name) useView(View view, FormObject graphics)</pre>	Applies a view to the graphics contents given by the name, name path, or graphics form object in the second argument.
resetView	resetView(String name) resetView(FormObject graphics)	Resets the view to its initial state in the graphics contents given by the name, name path, or graphics form object in the second argument.
getView	ViewBase getView(String name) ViewBase getView(FormObject graphics)	Returns the view currently used by the graphics contents given by the name, name path, or graphics form object in the second argument.
setWebPageSource	setWebPageSource(String name, String source)	Sets the source for the form object specified by the name or name path in the first argument. This method throws an error if the name does not refer to a Web Page form object.

NAME	SYNTAX	DESCRIPTION
getScreenHeight	<pre>int getScreenHeight()</pre>	Returns the height in pixels of the primary screen on client system, or of the browser window if Web Client is used.
getScreenWidth	<pre>int getScreenWidth()</pre>	Returns the width in pixels of the primary screen on client system, or of the browser window if Web Client is used.

ALERTS AND MESSAGES

The methods alert, confirm, and request display a dialog box with a text string and optional user input. The following example uses confirm to ask the user if a direct or an iterative solver should be used in an application. Based on the answer, the alert function is then used to show the estimated memory requirement for the selected solver type in a message dialog box:

```
String answer = confirm("Which solver do you want to use?",
"Solver Selection","Direct", "Iterative");
if(answer.equals("Direct")) {
    alert("Using the direct solver will require about 4GB of memory when
    solving.");
} else {
    alert("Using the iterative solver will require about 2GB of memory when
    solving.");
}
```

EXAMPLE CODE

The following code changes the camera position and updates the graphics for each change.

```
 useView(model.view("view1"), "/form1/graphics1"); \\ for (int i = 0; i < 25; i++) \{ \\ sleep(2000); \\ model.view("view1").camera().set("zoomanglefull", 12-i*5.0/25); \\ useGraphics(model.geom("geom1"), "/form1/graphics1"); \\ \end{aligned}
```

This line of code displays plot group 5 (pg5) in the graphics object graphics1 in the form with the name Temperature:

```
useGraphics(model.result("pg5"), "/Temperature/graphics1");
```

The code below displays the mesh in the model tree node mesh1 in the graphics object graphics1 contained in the card of a card stack. The second line runs a zoom extents command to ensure proper visualization of the mesh.

}

```
useGraphics(model.mesh("mesh1"), "/mesh/cardstack1/card1/graphics1");
zoomExtents("/mesh/cardstack1/card1/graphics1");
```

To clear the contents of a graphics object use a call such as

```
useGraphics(null, "/form1/graphics1")
```

The code below displays a request dialog box that lets the user type in a file name for an HTML report. If the user has typed a file name, then a report is generated.

```
String answerh = request("Enter file name", "File Name", "Untitled.html");
if(answerh != null){
  model.result().report("rpt1").set("format", "html");
  model.result().report("rpt1").set("filename", "user:///"+answerh);
  model.result().report("rpt1").run();
}
```


The code below is similar to the code above, but in this case the report is saved in Microsoft[®] Word[®] format (.docx).

```
String answerw = request("Enter file name", "File Name", "Untitled.docx");
if(answerw != null){
   model.result().report("rpt2").set("format", "docx");
   model.result().report("rpt2").set("filename", "user:///"+answerw);
   model.result().report("rpt2").run();
}
```

This line of code sets the view of the graphics object form1/graphics1 to **View 5**, as defined in the model tree:

```
useView(model.view("view5"), "form1/graphics1");
```

You can use **Data Access** in combination with **Editor Tools** to create a slider or an input field that sets the transparency level (alpha) of a plot group. The figure below shows a **Settings** window of a slider with the transparency level as **Source**.




In this case you need to create a method for updating the view that is called to handle an event from the slider or form object. In the example above, the slider uses a **Local method** defined in the **Events** section. This method contains one line of code that updates the view:

```
useView(getView("/form1/graphics1"), "/form1/graphics1");
```

Note that different transparency levels are not supported when accessing an application from a browser using COMSOL Server.

Note that you can also set a view from the command sequence of, for example, a button: select a view subnode under the **Views** node in the editor tree and click the **Plot** button under the tree.



This line of code sets the URL source of the form object webpage1 to the COMSOL web page:

```
setWebPageSource("/form1/webpage1", "http://www.comsol.com");
```

This line of code forms a string containing the screen width and height:

```
screenSize =
toString(getScreenWidth())+"-by-"+toString(getScreenHeight());
```

You can present the string with an input field or a data display object using this string as a source (the string screenSize needs to be declared first).

GUI Command Methods

The GUI command methods correspond to the **GUI Commands** node in the editor tree. The editor tree is displayed in, for example, the **Choose Commands to Run** section in the **Settings** window for a button object in the Application Builder.

-		
NAME	SYNTAX	DESCRIPTION
clearAllMeshes	clearAllMeshes()	Clears all meshes.
clearAllSolutions	clearAllSolutions()	Clears all solutions.
clearSelection	<pre>clearSelection(String graphics) clearSelection(FormObject graphics)</pre>	Clears the selection in the given graphics object.
exit	exit()	Exits the application.
fileOpen	fileOpen(String name)	Opens a file with the associated program on the client.
fileSaveAs	fileSaveAs(String file)	Downloads a file to the client. See also the section "Example code".
printGraphics	<pre>printGraphics(String graphicsName) printGraphics(FormObject graphics)</pre>	Prints the given graphics object.
saveApplication	saveApplication()	Saves the application.
saveApplicationAs	saveApplicationAs()	Saves the application under a different name. (Or as an MPH file.)
scenelight	<pre>sceneLight(String graphicsName) sceneLight(FormObject graphics)</pre>	Toggles scene light in the given graphics object.
selectAll	<pre>selectAll(String graphics) selectAll(FormObject graphics)</pre>	Sets the selection to all entities in the given graphics object.
transparency	transparency(String graphicsName) transparency(FormObject graphics)	Toggles transparency in the given graphics object.
zoomExtents	zoomExtents(String graphicsName) zoomExtents(FormObject graphics)	Makes the entire model visible within the extent of the given graphics object.

EXAMPLE CODE

For examples of how to use fileSaveAs, see the Introduction to Application Builder.

You can create an application that saves and exits automatically by running the following lines of code, for example, after solving:

```
saveModel(model, "C:\\COMSOL\\file.mph");
```

```
exit();
Or
  saveModel(model, "common:///file.mph");
  exit();
```

This is useful in a COMSOL Server setting since using exit() in this way will free up any licenses that are checked out.

Debug Methods

The debug method is used to display variable contents in the **Debug Log** window.

NAME	SYNTAX	DESCRIPTION
clearDebugLog	<pre>clearDebugLog()</pre>	Clears the Debug Log window.
debugLog	debugLog(arg)	Prints the value of arg to the Debug Log window. The input argument arg can be a scalar, ID array, or 2D array of the types string, double, int or Boolean.

EXAMPLE CODE

The code below prints strings and doubles to the Debug Log window.

```
xcoords[i] = Math.cos(2.0*Math.PI*divid);
ycoords[i] = Math.sin(2.0*Math.PI*divid);
debugLog("These are component values for case 1:");
debugLog("x:");
debugLog(xcoords[i]);
debugLog(ycoords[i]);
```

Methods for External C Libraries

The methods for external C libraries are used for linking Application Builder methods with compiled C-code.

EXTERNAL METHOD

NAME	SYNTAX	DESCRIPTION
external	External external(String name)	Returns an interface to an external C (native) library given by the name of the library feature. The External class uses the Java Native Interface (JNI) framework.

For more information, see the Application Builder Reference Manual.

METHODS RETURNED BY THE EXTERNAL METHOD

The external method returns an object of type External with the following methods:

NAME	SYNTAX	DESCRIPTION
invoke	long invoke(String method, Object arguments)	Invokes the named native method in the library with the supplied arguments. Strings are converted to char *. Returns the value returned by the method.
invokeWideString	long invokeWideString(String method, Object arguments)	Invokes the named native method in the library with the supplied arguments. Strings are converted to wchar_t *. Returns the value returned by the method.
close	void close()	Releases the library and frees resources. If you do not call this method, it is automatically invoked when the external library is no longer needed.

Progress Methods

Progress methods are used to create and update progress information in the Status bar, in a progress form object, and in a dialog box.

NAME	SYNTAX	DESCRIPTION
setProgressInterval	setProgressInterval(String message, int intervalStart, int intervalEnd)	Sets a progress interval to use for the top-level progress and display message at that level. The top level will go from intervalStart to intervalEnd as the second level goes from 0 to 100. As the second level increases, the top level is increased by (intervalEnd - intervalStart) * (second level progress (0-100) / 100). The value for intervalStart must be between 0 and intervalEnd, and the value for intervalStart and 100. Calling this method implicitly resets any manual progress previously set by calls to setProgress().
setProgress	setProgress(int value, String message)	Sets a value for the user-controlled progress level. By default, this is the top level, but if a progress interval is active (setProgressInterval has been called and resetProgress has not been called after that), then it is the second level.
setProgress	setProgress(int value)	Same as setProgress (message, value), but uses the latest message or an empty string (if no message has been set).

NAME	SYNTAX	DESCRIPTION
resetProgress	resetProgress()	Removes all progress levels and resets progress to 0 and the message to an empty string.
showIndeterminateProgress	<pre>showIndeterminateProgress(String message)</pre>	Shows a progress dialog box with an indeterminate progress bar, given message and a cancel button.
showIndeterminateProgress	showIndeterminateProgress(String message, boolean cancelButton)	Shows a progress dialog box with an indeterminate progress bar, given message and an optional cancel button.
showProgress	showProgress()	Shows a progress dialog box with a cancel button. No model progress is included.
showProgress	showProgress(boolean modelProgress)	Shows a progress dialog box with a cancel button and an optional model progress.
showProgress	showProgress(boolean modelProgress, boolean addSecondLevel)	Shows a progress dialog box with a cancel button, optional model progress, and one or two levels of progress information. Two levels can only be used if modelProgress is true.
showProgress	showProgress(boolean modelProgress, boolean addSecondLevel, boolean cancelButton)	Shows a progress dialog box with optional model progress, one or two levels, and possibly a cancel button. Two levels can only be used if modelProgress is true.
closeProgress	closeProgress()	Closes the currently shown progress dialog box.

NAME	SYNTAX	DESCRIPTION
startProgress	startProgress(String name) startProgress(FormObject progressBar)	Resets the value of the given progress bar form object name to 0. The progress bar to control can be specified with an absolute path, such as form1/progressbar1, or a name relative to the context from which the method was called. Nothing is done if no progress bar corresponding to the given name is found.
setProgressBar	setProgressBar(String name, int workDone, String message) setProgressBar(FormObject progressBar, int workDone, String message)	Sets the value of the given progress bar form object name in the range 0-100 and the associated progress message. Values out of range are converted to 0 or 100. The progress bar to control can be specified with an absolute path, such as form1/progressbar1, or a name relative to the context from which the method was called. Nothing is done if no progress bar corresponding to the given name is found, or if the progress bar is used for showing model progress.
setProgressBar	<pre>setProgressBar(String name, int workDone) setProgressBar(FormObject progressBar, int workDone)</pre>	Same as above, but does not update the progress message.

EXAMPLE CODE

showProgress(true, true, true);

 $/^{\star}$ Opens a progress dialog box with cancel button showing two levels of progress. The values shown in progress dialog box will be updated to match the two levels of progress. $^{\star}/$

setProgressInterval("Preparing application", 0, 20);

/* Sets the current progress scale to go from 0 to 20. This means that the top-level progress will go from 0 to 20 when second-level progress goes from 0 to 100. $^{\star}/$

```
setProgress(0, "Init step 1");
/* Sets the second-level progress to 0 and the second-level progress message
to "Init step 1". */
// do some work
setProgress(40):
/* Sets the second-level progress to 40, this causes the top-level progress
to be updated to 8 (40 % of 0-20). */
// do some work
setProgress(80, "Init step 2");
/* Sets the second-level progress to 80 and the progress message to "Init
step 2". The top-level message is still "Preparing application" and
top-level progress is now 16. */
// do some work
setProgressInterval("Meshing", 20, 40);
/* Sets the top-level interval to 20 - 40 and the progress message to
"Meshing" at this point the value shown at the top-level will be 20. The
second-level progress is cleared when the top-level interval is changed. */
<call-meshing algorithm>
/* The progress messages and values from the meshing algorithm are shown at
the second-level progress. The top-level progress message will be "Meshing",
but the top-level progress advances from 20 to 40 while second-level
progress advances from 0 to 100. */
setProgressInterval("Solving", 40, 100);
/* The top-level progress message is changed to "Solving" and its value to
40.
<call-solver>
/* Similar to meshing, the progress messages and values from the solver are
shown in the second-level progress bar and the top-level progress value goes
from 40 to 100 while the solver progress goes from 0 to 100. */
closeProgress();
```

Application Progress Information

Progress information can be displayed in three different ways: in the Status bar, in a progress form object, and in a dialog box. Application progress information is controlled by the setProgress methods, which take as their input an integer between 0 and 100 and an optional message. The integer represents how far the displayed progress bar has progressed. If no message is supplied, the last message provided is used. For example:

```
setProgress(10, "Computing data")
setProgress(25)
```

This will keep Computing data as the progress message.

Use the setProgress method by itself if you want to display custom progress in the task and status bar. Once you have done this, that progress bar will no longer be updated by progress information from the COMSOL model, but will be completely dependent on further calls to setProgress for changes in its value. Precede it with a call to showProgress to also display the built-in progress dialog box, see below.

Note that progress information from the COMSOL model will not be shown in between calls to setProgress. Progress is reset between method calls. If you want to combine custom steps of progress in methods with built-in model progress, then use setProgressInterval instead.

With setProgressInterval, you can control the top two levels of progress information. The second level can be displayed in a progress dialog box and a progress bar form object, see the code segment below. The second progress level, controlled by your own custom progress calculation, is connected to the first level such that one interval at the top level corresponds to the entire second level. Thus if the interval is 0–50, when the second level progress reaches 40, for example, the first level will be set to $20 \ (= (40/100)*50)$.

Important uses of the method setProgressInterval are listed below:

- Combining calls to the COMSOL model so that you get continuous progress going from 0–100.
- Computing several studies as well as evaluating several plots. Call setProgressInterval before each call to the built-in methods with an interval that approximates how much time each model computation takes. For example:

```
setProgressInterval("Computing solution", 0, 80);
model.study("std1").run();
setProgressInterval("Plotting", 80, 100);
useGraphics(model.result("pg3"), "energy response plot/graphics1");
```

• Combining one or more calls to built-in COMSOL methods with custom methods that in themselves take significant time. In this case, use setProgressInterval as in the previous example, followed by your own custom code with appropriate calls to setProgress. These calls should run from 0 to 100 as they are controlling the second progress level. For example:

```
setProgressInterval("Computing solution", 0, 60);
model.study("std1").run();
setProgressInterval("Working", 60, 80);
setProgress(0, "Specific message about what I'm doing");
// ...
// Code that does something
// ...
setProgress(60);
```

If you, in a running application, wish to no longer use progress intervals, call resetProgress to return to the original state. This will also reset progress to 0.

The Progress Dialog Box

A progress dialog box can be used to display application progress as described in the previous section. The progress dialog has the following options:

- Whether to show model progress or not. When off, no progress from the model part of the application is forwarded to the progress dialog.
- Whether to show one or two progress levels in the progress dialog.
- Whether to include a cancel button. Cancel also works for user-defined methods, as it halts execution when the next line in the method is reached.

Use the showProgress methods to enable or disable these options. To close the progress dialog, use the closeProgress method.

You can show a progress dialog with an indeterminate progress bar that keeps spinning until you close the progress dialog. Only one progress dialog can be shown at a time. Use the showIndeterminateProgress methods to display this progress dialog.

The Progress Bar Form Object

The **Progress Bar** form object can either show overall application progress information or customized partial progress information. If you have selected the **Include model progress** check box in the **Settings** window of the **Main Window** node, then the overall application progress information becomes available.

When **Include model progress** is selected, the progress bar will show the same information as the progress dialog box. That is, one or two levels of progress information and a cancel button, depending on the settings in the form object.

When **Include model progress** is cleared, you control the progress bar through the setProgressBar methods. These take the path name of the progress bar form object, for example, main/progressbar1.

Date and Time Methods

The date and time methods are used to retrieve the current date and time as well as information on computation times.

NAME	SYNTAX	DESCRIPTION
currentDate	String currentDate()	Returns the current date as a string (formatted according to the server's defaults) for the current date.
currentTime	String currentTime()	Returns the current time as a string (not including date, and formatted according to the server defaults).
formattedTime	String formattedTime(long timeInMs, String format)	Returns a formatted time using the given format. The format can either be a time unit or a text describing a longer format. Supported formats are: 'hr:min:sec' which returns the time in hours, minutes and seconds in the form X hr Y min Z sec. 'h:min:s' which returns the
		time in hours, minutes and seconds in the form X h Y min Z s. 'detailed' which returns the time in seconds and also includes more readable units for longer times.
sleep	<pre>sleep(long timeInMs)</pre>	Sleep for the specified number of milliseconds.
timeStamp	<pre>long timeStamp()</pre>	Current time in milliseconds since midnight, January 1, 1970 UTC.

NAME	SYNTAX	DESCRIPTION
getExpectedComputa tionTime	<pre>model.setExpectedComputationTime(String format)</pre>	Returns a string describing the approximate computation time of the application. The string can be altered by the method setExpectedComputationTime.
setLastComputation Time	model.setLastComputationTime(long time)	Set the last computation time, overwriting the automatically generated time. You can use the timeStamp method to record time differences and set the measured time in ms (a long integer).
getLastComputation Time	String model.getLastComputationTime (String format)	Returns the last computation time in the given format. The format can either be a time unit or text describing a longer format. Currently supported formats are: hr:min:sec Returns the time in hours, minutes, and seconds in the format X h Y min Z sec. h:min:s Returns the time in hours, minutes, and seconds in the format X h Y min Z s. detailed Returns the time in seconds and also includes more readable units for longer times. This format is localized and the output is translated to the current language setting. For example, you can retrieve the time in ms by using getlastComputationTime("ms").

EXAMPLE CODE

The following code overrides the built-in computation time that is available in the information nodes in the model tree.

```
long t0 = timeStamp(); // initialize record of computation time
// code and computations
model.setLastComputationTime(timeStamp()-t0); // record computation time
```

If it is possible to give a rough estimate of the computation time based on the given inputs of an application, you can update the expected computation time and display it in an information card stack or a text object. Assume that there is an integer input called objects that controls the number of objects in a geometry array and that the computation roughly increases linearly with this number. The following code adjusts the expected computation time accordingly.

```
// Number of minutes of computation time per object
int minutes = objects*2.1;
model.setExpectedComputationTime("About " + minutes + " minutes" );
Sleep
```

The code below makes the application idle for 1000 ms.

```
long delay = 1000;
sleep(delay);
```

This technique can be used to display graphics in a sequence.

For more information on information nodes and information cards, as well as the sleep method, see the book *Introduction to Application Builder*.

Conversion Methods

Conversion methods are used to convert between the different data types Booleans, integers, doubles, strings, and arrays. These methods are shorthand versions of conversion methods in the standard Java libraries.

NAME	SYNTAX	DESCRIPTION
toBoolean	boolean toBoolean(String str)	Converts the given string to a Boolean. ('true' returns true, all other strings return false).
toBoolean	boolean [] toBoolean(String[] strs)	Converts all the strings in the given array to Booleans ('true' returns true, all other strings return false) and returns a Boolean array.
toBoolean	boolean [][] toBoolean(String[][] strs)	Converts all the strings in the given matrix to Booleans ('true' returns true, all other strings return false) and returns a Boolean matrix.
toDouble	double toDouble(String str)	Converts the given string to a double.
toDouble	<pre>double[] toDouble(String strs)</pre>	Converts all the strings in the given arrray to doubles and returns a double array.
toDouble	<pre>double[][] toDouble(String[] strs)</pre>	Converts all the strings in the given matrix to doubles and returns a double matrix.
toDouble	double toDouble(float flt)	Converts the given float to a double.
toDouble	<pre>double[] toDouble(float flt)</pre>	Converts all the floats in the given arrray to doubles and returns a double array.
toDouble	<pre>double[][] toDouble(float[] flt)</pre>	Converts all the floats in the given matrix to doubles and returns a double matrix.
toInt	<pre>int toInt(String str)</pre>	Converts the given string to an integer.
toInt	<pre>int[] toInt(String strs)</pre>	Converts all the strings in the given arrray to integers and returns an integer array.

NAME	SYNTAX	DESCRIPTION
toInt	<pre>int[][] toInt(String[] strs)</pre>	Converts all the strings in the given matrix to integers and returns an integer matrix.
toString	String toString(int value)	Converts the given integer to a string.
toString	String toString(double value)	Converts the given double to a string.
toString	String toString(boolean value)	Converts the given Boolean to a string.
toString	String toString(double value, int decimals)	Converts the given double to a string with the given number of decimals.
toString	String toString(double value, int decimals,boolean remove)	Converts the given double to a string with the given number of decimals with trailing zeros removed if the Boolean remove is true. For example, 10.0000001 with number of decimals set to 3 will return 10 rather than 10.000.
toString	String toString(double value, String format)	Converts the given double to a string using the given format specifier, which is the same as <code>java.util.Formatter</code> . See the corresponding Java format string documentation for more information.
toString	String[] toString(double[] darray)	Converts all the doubles in the given array to strings and returns a string array.
toString	String[][] toString(double[][] dmatrix)	Converts all the doubles in the given matrix to strings and returns a string matrix.
toString	String[] toString(int[] iarray)	Converts all the integers in the given array to strings and returns a string array.
toString	<pre>String[][] toString(int[][] imatrix)</pre>	Converts all the integers in the given matrix to strings and returns a string matrix.

NAME	SYNTAX	DESCRIPTION
toString	String[] toString(boolean[] barray)	Converts all the Booleans in the given array to strings and returns a string array.
toString	<pre>String[][] toString(boolean[][] bmatrix)</pre>	Converts all the Booleans in the given matrix to strings and returns a string matrix.

Array Methods

Array methods are used to add, remove, insert, and extract subsets of 1D and 2D arrays.

NAME	SYNTAX	DESCRIPTION
getColumn	<pre>String[] getColumn(String[][] matrix, int column)</pre>	Returns a String[] for a specified column in the matrix. Useful when values have been read from a file and only certain columns should be shown in a table.
getColumn	<pre>double[] getColumn(double[][] matrix, int column)</pre>	Returns a double[] for a specified column in the matrix.
getColumn	<pre>int[] getColumn(int[][] matrix, int column)</pre>	Returns an int[] for a specified column in the matrix.
getColumn	<pre>boolean[] getColumn(boolean[][] matrix, int column)</pre>	Returns a boolean[] for a specified column in the matrix.
getSubMatrix	<pre>String[][] getSubMatrix(String[][] matrix, int startCol, int endCol, int startRow, int endRow)</pre>	Returns a rectangular submatrix of the input matrix spanning columns from startCol to endCol, and rows from startRow to endRow.
getSubMatrix	<pre>double[][] getSubMatrix(double[][] matrix, int startCol,int endCol, int startRow, int endRow)</pre>	Returns a rectangular submatrix of the input matrix spanning columns from startCol to endCol, and rows from startRow to endRow.

NAME	SYNTAX	DESCRIPTION
getSubMatrix	<pre>int[][] getSubMatrix(int[][] matrix, int startCol, int endCol, int startRow, int endRow)</pre>	Returns a rectangular submatrix of the input matrix spanning columns from startCol to endCol, and rows from startRow to endRow.
getSubMatrix	<pre>boolean[][] getSubMatrix(boolean[][] matrix, int startCol, int endCol, int startRow, int endRow)</pre>	Returns a rectangular submatrix of the input matrix spanning columns from startCol to endCol, and rows from startRow to endRow.
insert	<pre>String[] insert(String[] array, String value, int index)</pre>	Inserts an element at position index in an array and returns the expanded array.
insert	<pre>double[] insert(double[] array, double value, int index)</pre>	Inserts an element at position index in an array and returns the expanded array.
insert	<pre>int[] insert(int[] array, int value, int index)</pre>	Inserts an element at position index in an array and returns the expanded array.
insert	<pre>boolean[] insert(boolean[] array, boolean value, int index)</pre>	Inserts an element at position index in an array and returns the expanded array.
insert	<pre>String[] insert(String[] array, String[] value, int[] index)</pre>	Inserts elements in an array at positions given by the index array and returns the expanded array.
insert	<pre>double[] insert(double[] array, double[] value, int[] index)</pre>	Inserts elements in an array at positions given by the index array and returns the expanded array.
insert	<pre>int[] insert(int[] array, int[] value, int[] index)</pre>	Inserts elements in an array at positions given by the index array and returns the expanded array.
insert	<pre>boolean[] insert(boolean[] array, boolean[] value, int[] index)</pre>	Inserts elements in an array at positions given by the index array and returns the expanded array.
append	String[] append(String[] array, String value)	Adds an element to the end of an array and returns the expanded array.
append	<pre>double[] append(double[] array, double value)</pre>	Adds an element to the end of an array and returns the expanded array.

NAME	SYNTAX	DESCRIPTION
append	<pre>int[] append(int[] array, int value)</pre>	Adds an element to the end of an array and returns the expanded array.
append	<pre>boolean[] append(boolean[] array, boolean value)</pre>	Adds an element to the end of an array and returns the expanded array.
append	<pre>String[] append(String[] array, String[] value)</pre>	Adds elements to the end of an array and returns the expanded array.
append	<pre>double[] append(double[] array, double[] value)</pre>	Adds elements to the end of an array and returns the expanded array.
append	<pre>int[] append(int[] array, int[] value)</pre>	Adds elements to the end of an array and returns the expanded array.
append	<pre>boolean[] append(boolean[] array, boolean[] value)</pre>	Adds elements to the end of an array and returns the expanded array.
remove	<pre>String[] remove(String[] array, int index)</pre>	Removes an element from an array and returns the shortened array.
remove	<pre>double[] remove(double[] array, int index)</pre>	Removes an element from an array and returns the shortened array.
remove	<pre>int[] remove(int[] array, int index)</pre>	Removes an element from an array and returns the shortened array.
remove	<pre>boolean[] remove(boolean[] array, int index)</pre>	Removes an element from an array and returns the shortened array.
remove	<pre>String[] remove(String[] array, int[] index)</pre>	Removes elements from an array and returns the shortened array.
remove	<pre>double[] remove(double[] array, int[] index)</pre>	Removes elements from an array and returns the shortened array.
remove	<pre>int[] remove(int[] array, int[] index)</pre>	Removes elements from an array and returns the shortened array.
remove	<pre>boolean[] remove(boolean[] array, int[] index)</pre>	Removes elements from an array and returns the shortened array.

NAME	SYNTAX	DESCRIPTION
insertRow	<pre>String[][] insertRow(String[][] matrix, String[] value, int rowIndex)</pre>	Inserts a row into a rectangular 2D array and returns the expanded array.
insertRow	<pre>double[][] insertRow(double[][] matrix, double[] value, int rowIndex)</pre>	Inserts a row into a rectangular 2D array and returns the expanded array.
insertRow	<pre>int[][] insertRow(int[][] matrix, int[] value, int rowIndex)</pre>	Inserts a row into a rectangular 2D array and returns the expanded array.
insertRow	<pre>boolean[][] insertRow(boolean[][] matrix, boolean[] value, int rowIndex)</pre>	Inserts a row into a rectangular 2D array and returns the expanded array.
insertRow	<pre>String[][] insertRow(String[][] matrix, String[][] value, int[] rowIndex)</pre>	Adds rows to a rectangular 2D array and returns the expanded array.
insertRow	<pre>double[][] insertRow(double[][] matrix, double[][] value, int[] rowIndex)</pre>	Adds rows to a rectangular 2D array and returns the expanded array.
insertRow	<pre>int[][] insertRow(int[][] matrix, int[][] value, int[] rowIndex)</pre>	Adds rows to a rectangular 2D array and returns the expanded array.
insertRow	<pre>boolean[][] insertRow(boolean[][] matrix, boolean[][] value, int[] rowIndex)</pre>	Adds rows to a rectangular 2D array and returns the expanded array.
replaceRow	<pre>String[][] replaceRow(String[][] matrix, String[] value, int rowIndex)</pre>	Replaces a row in a rectangular 2D array and returns the array.
replaceRow	<pre>double[][] replaceRow(double[][] matrix, double[] value, int rowIndex)</pre>	Replaces a row in a rectangular 2D array and returns the array.
replaceRow	<pre>int[][] replaceRow(int[][] matrix, int[] value, int rowIndex)</pre>	Replaces a row in a rectangular 2D array and returns the array.
replaceRow	<pre>boolean[][] replaceRow(boolean[][] matrix, boolean[] value, int rowIndex)</pre>	Replaces a row in a rectangular 2D array and returns the array.
replaceRow	<pre>String[][] replaceRow(String[][] matrix, String[][] value, int[] rowIndex)</pre>	Replaces rows in a rectangular 2D array and returns the array.
replaceRow	<pre>double[][] replaceRow(double[][] matrix, double[][] value, int[] rowIndex)</pre>	Replaces rows in a rectangular 2D array and returns the array.
replaceRow	<pre>int[][] replaceRow(int[][] matrix, int[][] value, int[] rowIndex)</pre>	Replaces rows in a rectangular 2D array and returns the array.

NAME	SYNTAX	DESCRIPTION
replaceRow	<pre>boolean[][] replaceRow(boolean[][] matrix, boolean[][] value, int[] rowIndex)</pre>	Replaces rows in a rectangular 2D array and returns the array.
appendRow	<pre>String[][] appendRow(String[][] matrix, String[] value)</pre>	Adds a row to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>double[][] appendRow(double[][] matrix, double[] value)</pre>	Adds a row to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>int[][] appendRow(int[][] matrix, int[] value)</pre>	Adds a row to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>boolean[][] appendRow(boolean[][] matrix, boolean[] value)</pre>	Adds a row to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>String[][] appendRow(String[][] matrix, String[][] value)</pre>	Adds rows to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>double[][] appendRow(double[][] matrix, double[][] value)</pre>	Adds rows to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>int[][] appendRow(int[][] matrix, int[][] value)</pre>	Adds rows to the end of a rectangular 2D array and returns the expanded array.
appendRow	<pre>boolean[][] appendRow(boolean[][] matrix, boolean[][] value)</pre>	Adds rows to the end of a rectangular 2D array and returns the expanded array.
removeRow	<pre>String[][] removeRow(String[][] matrix, int rowIndex)</pre>	Removes a row from a 2D array and returns the smaller array.
removeRow	<pre>double[][] removeRow(double[][] matrix, int rowIndex)</pre>	Removes a row from a 2D array and returns the smaller array.
removeRow	<pre>int[][] removeRow(int[][] matrix, int rowIndex)</pre>	Removes a row from a 2D array and returns the smaller array.
removeRow	<pre>boolean[][] removeRow(boolean[][] matrix, int rowIndex)</pre>	Removes a row from a 2D array and returns the smaller array.
removeRow	<pre>String[][] removeRow(String[][] matrix, int[] rowIndex)</pre>	Removes rows from a 2D array and returns the reduced array.
removeRow	<pre>double[][] removeRow(double[][] matrix, int[] rowIndex)</pre>	Removes rows from a 2D array and returns the reduced array.

NAME	SYNTAX	DESCRIPTION
removeRow	<pre>int[][] removeRow(int[][] matrix, int[] rowIndex)</pre>	Removes rows from a 2D array and returns the reduced array.
removeRow	<pre>boolean[][] removeRow(boolean[][] matrix, int[] rowIndex)</pre>	Removes rows from a 2D array and returns the reduced array.
insertColumn	<pre>String[][] insertColumn(String[][] matrix, String[] value, int columnIndex)</pre>	Adds a column into a rectangular 2D array and returns the expanded array.
insertColumn	<pre>double[][] insertColumn(double[][] matrix, double[] value, int columnIndex)</pre>	Adds a column into a rectangular 2D array and returns the expanded array.
insertColumn	<pre>int[][] insertColumn(int[][] matrix, int[] value, int columnIndex)</pre>	Adds a column into a rectangular 2D array and returns the expanded array.
insertColumn	<pre>boolean[][] insertColumn(boolean[][] matrix, boolean[] value, int columnIndex)</pre>	Adds a column into a rectangular 2D array and returns the expanded array.
insertColumn	<pre>String[][] insertColumn(String[][] matrix, String[][] value, int[] columnIndex)</pre>	Adds columns to a rectangular 2D array and returns the expanded array.
insertColumn	<pre>double[][] insertColumn(double[][] matrix, double[][] value, int[] columnIndex)</pre>	Adds columns to a rectangular 2D array and returns the expanded array.
insertColumn	<pre>int[][] insertColumn(int[][] matrix, int[][] value, int[] columnIndex)</pre>	Adds columns to a rectangular 2D array and returns the expanded array.
insertColumn	<pre>boolean[][] insertColumn(boolean[][] matrix, boolean[][] value, int[] columnIndex)</pre>	Adds columns to a rectangular 2D array and returns the expanded array.
replaceColumn	<pre>String[][] replaceColumn(String[][] matrix, String[] value, int columnIndex)</pre>	Replaces a column in a rectangular 2D array and returns the array.
replaceColumn	<pre>double[][] replaceColumn(double[][] matrix, double[] value, int columnIndex)</pre>	Replaces a column in a rectangular 2D array and returns the array.
replaceColumn	<pre>int[][] replaceColumn(int[][] matrix, int[] value, int columnIndex)</pre>	Replaces a column in a rectangular 2D array and returns the array.

NAME	SYNTAX	DESCRIPTION
replaceColumn	<pre>boolean[][] replaceColumn(boolean[][] matrix, boolean[] value, int columnIndex)</pre>	Replaces a column in a rectangular 2D array and returns the array.
replaceColumn	<pre>String[][] replaceColumn(String[][] matrix, String[][] value, int[] columnIndex)</pre>	Replaces columns in a rectangular 2D array and returns the array.
replaceColumn	<pre>double[][] replaceColumn(double[][] matrix, double[][] value, int[] columnIndex)</pre>	Replaces columns in a rectangular 2D array and returns the array.
replaceColumn	<pre>int[][] replaceColumn(int[][] matrix, int[][] value, int[] columnIndex)</pre>	Replaces columns in a rectangular 2D array and returns the array.
replaceColumn	<pre>boolean[][] replaceColumn(boolean[][] matrix, boolean[][] value, int[] columnIndex)</pre>	Replaces columns in a rectangular 2D array and returns the array.
appendColumn	<pre>String[][] appendColumn(String[][] matrix, String[] value)</pre>	Adds a column at the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>double[][] appendColumn(double[][] matrix, double[] value)</pre>	Adds a column at the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>int[][] appendColumn(int[][] matrix, int[] value)</pre>	Adds a column at the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>boolean[][] appendColumn(boolean[][] matrix, boolean[] value)</pre>	Adds a column at the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>String[][] appendColumn(String[][] matrix, String[][] value)</pre>	Adds columns to the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>double[][] appendColumn(double[][] matrix, double[][] value)</pre>	Adds columns to the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>int[][] appendColumn(int[][] matrix, int[][] value)</pre>	Adds columns to the end of a rectangular 2D array and returns the expanded array.
appendColumn	<pre>boolean[][] appendColumn(boolean[][] matrix, boolean[][] value)</pre>	Adds columns to the end of a rectangular 2D array and returns the expanded array.
removeColumn	<pre>String[][] removeColumn(String[][] matrix, int columnIndex)</pre>	Removes a column from a rectangular 2D array and returns the smaller array.

NAME	SYNTAX	DESCRIPTION
removeColumn	<pre>double[][] removeColumn(double[][] matrix, int columnIndex)</pre>	Removes a column from a rectangular 2D array and returns the smaller array.
removeColumn	<pre>int[][] removeColumn(int[][] matrix, int columnIndex)</pre>	Removes a column from a rectangular 2D array and returns the smaller array.
removeColumn	<pre>boolean[][] removeColumn(boolean[][] matrix, int columnIndex)</pre>	Removes a column from a rectangular 2D array and returns the smaller array.
removeColumn	<pre>String[][] removeColumn(String[][] matrix, int[] columnIndex)</pre>	Removes columns from a rectangular 2D array and returns the reduced array.
removeColumn	<pre>double[][] removeColumn(double[][] matrix, int[] columnIndex)</pre>	Removes columns from a rectangular 2D array and returns the reduced array.
removeColumn	<pre>int[][] removeColumn(int[][] matrix, int[] columnIndex)</pre>	Removes columns from a rectangular 2D array and returns the reduced array.
removeColumn	<pre>boolean[][] removeColumn(boolean[][] matrix, int[] columnIndex)</pre>	Removes columns from a rectangular 2D array and returns the reduced array.
matrixSize	<pre>int[] matrixSize(String[][] matrix)</pre>	Returns the number of rows and columns of a matrix as an integer array of length 2.
matrixSize	<pre>int[] matrixSize(double[][] matrix)</pre>	Returns the number of rows and columns of a matrix as an integer array of length 2.
matrixSize	<pre>int[] matrixSize(int[][] matrix)</pre>	Returns the number of rows and columns of a matrix as an integer array of length 2.
matrixSize	<pre>int[] matrixSize(boolean[][] matrix)</pre>	Returns the number of rows and columns of a matrix as an integer array of length 2.
transpose	<pre>String[][] transpose(String[][] matrix)</pre>	Returns the transpose of a matrix.
transpose	<pre>double[][] transpose(double[][] matrix)</pre>	Returns the transpose of a matrix.

NAME	SYNTAX	DESCRIPTION
transpose	<pre>int[][] transpose(int[][] matrix)</pre>	Returns the transpose of a matrix.
transpose	<pre>boolean[][] transpose(boolean[][] matrix)</pre>	Returns the transpose of a matrix.

String Methods

String methods are used to process string variables and string arrays.

NAME	SYNTAX	DESCRIPTION
concat	String concat(String separator, String strs)	Concatenates the given varargs-array of strings into a single string using the given separator.
concat	String[] concat(String colSepar, String rowSepar, String[] matr)	Concatenates the given string matrix (which can be given as a varargs of rows) into a single string. Puts colSepar between values of columns of a row, and rowSepar between rows.
contains	boolean contains(String[] strs, String str)	Returns true if the given string array strs contains the given string str.
find	<pre>int[] find(String[] strs, String str)</pre>	Returns an array with the indices to all occurrences of str in strs.
findIn	<pre>int findIn(String[] strs, String str)</pre>	Returns the index to the first occurrence of str in strs or -1 if no match.
findIn	<pre>int findIn(String str, String toFind)</pre>	Returns the first index of str that is the start of the substring toFind. If there is no substring matching toFind in str, -1 is returned.
length	int length(String str)	Returns the length of the string str.
replace	String replace(String str, String orig, String replacement)	Returns a string where orig has been replaced by replacement.

NAME	SYNTAX	DESCRIPTION
split	<pre>String[] split(String str)</pre>	Returns an array of strings by splitting the given string at spaces.
split	String[] split(String str, String separator)	Returns an array of strings by splitting the given string at the given separator.
substring	String substring(String str, int start, int length)	Returns a substring with the given length starting at the given position.
unique	String[] unique(String[] strs)	Returns an array of strings with the unique values in the given array of strings.

Collection Methods

Collection methods are used to copy, compare, sort, and merge variables and arrays.

NAME	SYNTAX	DESCRIPTION
сору	<pre>String[] copy(String toCopy)</pre>	Returns a copy of the given array of strings, which can also be specified as a varargs of strings.
сору	<pre>String[][] copy(String[] toCopy)</pre>	Returns a copy of the given string matrix, which can also be specified as a varargs of rows (string arrays).
сору	<pre>double[] copy(double toCopy)</pre>	Returns a copy of the given array of doubles, which can also be specified as a varargs of doubles.
сору	<pre>double[][] copy(double[] toCopy)</pre>	Returns a copy of the given double matrix, which can also be specified as a varargs of rows (double arrays).
сору	<pre>int[] copy(int toCopy)</pre>	Returns a copy of the given array of integers, which can also be specified as a varargs of integers.
сору	<pre>int[][] copy(int[] toCopy)</pre>	Returns a copy of the given integer matrix, which can also be specified as a varargs of rows (integer arrays).

NAME	SYNTAX	DESCRIPTION
сору	<pre>boolean[] copy(boolean toCopy)</pre>	Returns a copy of the given array of booleans, which can also be specified as a varargs of booleans.
сору	<pre>boolean[][] copy(boolean[] toCopy)</pre>	Returns a copy of the given boolean matrix, which can also be specified as a vararags of rows (boolean arrays).
equals	<pre>boolean equals(String[] str1, String[] str2)</pre>	Returns true if all strings in the given array are equal and they have the same number of elements.
equals	<pre>boolean equals(String[][] matr1, String[][] matr2)</pre>	Returns true if all strings in the given matrix are equal and they have the same number of elements.
equals	<pre>boolean equals(int[] ints1, int[] ints2)</pre>	Returns true if all integers in the given array are equal and they have the same number of elements.
equals	<pre>boolean equals(int[][] ints1, int[][] ints2)</pre>	Returns true if all integers in the given matrix are equal and they have the same number of elements.
equals	boolean equals(double dl1, double dl2, double relErrorTolerance)	Compares whether the relative error of two doubles is within allowed tolerance using abs((a - b) / b), where b is the larger of the doubles (by absolute value).
equals	boolean equals(double dl1, double dl2)	Same as above, but uses a default relErrorTolerance of 0.0001.
equals	boolean equals(double[] dbls1, double[] dbls2, double relErrorTolerance)	Compares the relative errors (~ abs((a - b) / b) of elements in the arrays pairwise and returns true if all relative errors are below relErrorTolerance and the arrays have the same number of elements.
equals	<pre>boolean equals(double[] dbls1, double[] dbls2)</pre>	Same as above, but uses a default relErrorTolerance of 0.0001.

NAME	SYNTAX	DESCRIPTION
equals	<pre>boolean equals(double[][] dbls1, double[][] dbls2, double relErrorTolerance)</pre>	Compares the relative errors (~ abs((a - b) / b) of elements in the matrices pairwise and returns true if all relative errors are below relErrorTolerance and the matrices have the same number of elements.
equals	<pre>boolean equals(double[][] dbls1, double[][] dbls2)</pre>	Same as above, but uses a default relErrorTolerance of 0.0001.
sort	<pre>sort(String[] strs)</pre>	Sorts the given array of strings. NOTE: The array is sorted in place.
sort	<pre>sort(int[] ints)</pre>	Sorts the given array of integers. NOTE: The array is sorted in place.
sort	<pre>sort(double[] doubles)</pre>	Sorts the given array of doubles. NOTE: The array is sorted in place.
sort	<pre>sort(String[][] strs)</pre>	Sorts the given 2D array of strings. The columns are sorted by their row values from top to bottom. NOTE: The array is sorted in place.
sort	<pre>sort(int[][] ints)</pre>	Sorts the given 2D array of integers. The columns are sorted by their row values from top to bottom. NOTE: The array is sorted in place.
sort	<pre>sort(double[][] doubles)</pre>	Sorts the given 2D array of doubles. The columns are sorted by their row values from top to bottom. NOTE: The array is sorted in place.
merge	<pre>merge(String[] toMerge)</pre>	Returns an array of strings with all strings merged from the given arrays.

NAME	SYNTAX	DESCRIPTION
merge	<pre>merge(int[] toMerge)</pre>	Returns an array of integers with all integers merged from the two given arrays.
merge	merge(double[] toMerge)	Returns an array of doubles with all doubles merged from the two given arrays.

Model Builder Methods for Use in Add-ins

For writing add-in method code that operates on the current component, current mesh, current physics etc. use the methods in the table below.

NAME	SYNTAX	DESCRIPTION
getCurrentComponent	<pre>getCurrentComponent()</pre>	Returns an object of the type ModelNode for the current component.
getCurrentMesh	<pre>getCurrentMesh()</pre>	Returns an object of the type MeshSequence for the current mesh.
getCurrentNode	getCurrentNode()	Returns an object of the type ModelEntity for the current component.
getCurrentPhysics	<pre>getCurrentPhysics()</pre>	Returns an object of the type Physics for the current physics interface.
getCurrentPlotGroup	<pre>getCurrentPlotGroup()</pre>	Returns an object of the type ResultFeature for the current component.
getCurrentStudy	getCurrentStudy()	Returns an object of the type Study for the current component.
selectNode	selectNode(ModelEntity entity)	Selects a model tree node and displays its Settings window after the execution of a method from the Model Builder.

These methods return the corresponding entity such that the method code in an add-in can operate on it. When called from an application a method in this

category returns null. Also, null is returned if no entity of the corresponding type exists such that nothing is current.

To learn more about using these methods you can review the Application Builder settings for one of the built-in add-ins by opening the corresponding MPH file. In a typical Windows[®] installation the built-in add-in library is located at

C:\Program Files\COMSOL\COMSOL55\Multiphysics\addins

Programming Examples

This section contains examples that illustrate solving practical tasks by accessing and manipulating the model object and using the built-in methods. Note that additional examples of user-defined methods are provided in the example applications of the Application Libraries accessible from the **File** menu.

Running the Examples

To run the code in the examples below, you can create a method for use in a model or application. You can, for example, choose the option **Blank Model** in the Model Wizard. To create a new method, go to the **Developer** tab in the Model Builder and click the **New Method** button in the ribbon. In the Application Builder, paste the code into the new method. Finally, you can run the code from the **Developer** tab in the Model Builder by choosing the method you just created from the **Run Method** toolbar menu.

Visualization Without Solution Data: Grid Data Sets

The section "Results" on page 48 shows how to write code for various parts of the Results node in the model tree, including **Data Sets**, **Tables**, and **Plot Groups**. These examples assume that you have solution data available from solving, for example, a heat transfer, CFD, or structural mechanics problem.

You can also create visualizations without having associated solution data by either using grid data sets or using low-level functionality only available through methods. You can, for example, write code for plotting points and triangles without any associated solution data. These techniques are useful when creating applications where customized plot functionality is needed. This section shows how to use grid data sets, and the next section shows how to use low-level functionality.

PLOTTING A UNIT SPHERE USING A GRID DATA SET

Grid data sets are available in the Model Builder and can be used in applications for the sole purpose of visualization without any associated solution data. The code below creates a visualization of a unit sphere as an isosurface with the *z*-coordinate as color data.

```
model.func().create("an1", "Analytic");
model.result().dataset().create("grid1", "Grid3D");
with(model.result().dataset("grid1"));
  set("source", "data");
  set("parmin1", -1);
set("parmax1", +1);
set("parmin2", -1);
  set("parmax2", +1);
  set("parmin3", -1);
  set("parmax3", +1);
  set("source", "function");
  set("function", "an1");
endwith();
model.result().create("pg1", "PlotGroup3D");
model.result("pg1").create("iso1", "Isosurface");
with(model.result("pg1").feature("iso1"));
  set("expr", "x^2+y^2+z^2-1");
  set("levelmethod", "levels");
  set("levels", 0.0);
endwith();
model.result("pg1").feature("iso1").create("col1", "Color");
with(model.result("pq1").feature("iso1").feature("col1"));
  set("expr", "z");
endwith();
model.result("pg1").run();
```

If there is no solution-based **Data set** available, then the **Grid3D** data set needs to have a **Function** as its **Source**. In the example above, a default Analytic function is created with tag an1. A default **Analytic** function corresponds to f(x) = x, and its only purpose is to give the grid data set an evaluation context.

Note: The alternative is to solve a physics problem on a mesh and reference the corresponding solution data set. The method of referencing a **Function** makes it possible to create visualizations without solution data.

The source for the **Grid3D** data set with tag grid1 is set to function, and finally, the function property of grid1 is set to an1.

The **Grid3D** data set has options for max and min parameter bounds, shown in the example code above. An additional grid resolution option is not shown in this example. However, you can learn about its syntax by using **Record Code** from the Model Builder.

Visualization of Points, Curves, and Surfaces

The following examples describe low-level functionality for visualization that is only available from methods and is not associated with any solution data. For visualization based on solution data, see the section "Results" on page 48.

The examples below illustrate using the following plot types:

- · Point Data
- · Line Data
- Surface Data
- Tube Data
- Arrow Data
- Annotation Data

Once created, the plot type names are visible in the **Settings** window of each plot. In addition to the properties modified by the examples below, in the **Settings** window of these plot types, you can see the number of geometric entities created, such as number of points, line segments, and triangles. Just as for other types of plots, you can also change the **Range** of color and data, as well as **Coloring and Style**.

POINTS IN 2D

The following code plots a circle of points using the **Point Data** plot type.

```
// A circle of points
  String pgTag = model.result().uniquetag("pg");
  ResultFeature pg = model.result().create(pgTag, 2);
  ResultFeature plot = pg.create("pt1", "PointData");
  int N = 17;
  double[][] p = new double[2][N];
  double[] color = new double[N];
  double R = 1000;
  for (int i = 0; i < N; i++) {
    double angle = i*2*Math.PI/N;
    p[0][i] = R*Math.cos(angle);
    p[1][i] = R*Math.sin(angle);
    color[i] = p[1][i];
  plot.set("pointdata", p)
    .set("colordata", color)
.set("coloring", "colortable");
  plot.run();
Comments
The first line
  String pgTag = model.result().uniquetag("pg");
```

creates a unique tag for the plot group to be created. This is useful if you intend to add a varying number of plot groups in your model or application.

The line

```
ResultFeature pg = model.result().create(pgTag, 2);
```

creates a **2D Plot Group** using the newly created unique tag. The second argument to create defines the dimension of the plot group (2 for 2D, 3 for 3D, etc.).

The line

```
ResultFeature plot = pg.create("pt1", "PointData");
```

creates a plot of the type PointData. This plot type is only available through methods.

The middle part of the example code generates the points making up the circle. The point coordinates are stored in the 2-by-N array p, along with color data in the array color of length N. The color data is, in this example, simply based on the index of the points and is used to control the coloring of each point based on a color table.

The last few lines populate the fields of the **Point Data** plot.

```
plot.set("pointdata", p)
   .set("colordata", color)
   .set("coloring", "colortable");
```

The property pointdata takes the 2-by-N array p as its input. The options for the coloring property are colortable or uniform.

To learn about the syntax for the additional properties available for a **Point Data** plot, you can run the above code in a blank model, browse to the **Settings** window for the **Point Data** plot, click **Record Code**, and change the corresponding plot properties. Note that the name of the plot type in the **Settings** window of the plot in the model tree is **Point Data**.

TURNING OFF MODEL HISTORY

When using this type of low-level functionality for larger sets of data, such as a large number of points, the stored model history may become excessively large. Because of this, it is recommended to temporarily turn off model history recording when using this type of functionality; see "Turning Off and Reset The Model History" on page 52.

POINTS IN 3D

The following code plots points in an undulating pattern in 3D using the **Point Data** plot type.

```
// Undulating points in 3D
```

```
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("pt1", "PointData");
int N = 37;
double[][] p = new double[3][N];
double[] color = new double[N];
double R = 1000;
for (int i = 0; i < N; i++) {
  double angle = i*2*Math.PI/N;
  p[0][i] = R*Math.cos(angle);
  p[1][i] = R*Math.sin(angle);
  p[2][i] = R*Math.cos(3*angle);
 color[i] = p[1][i];
plot.set("pointdata", p)
  .set("colordata", color)
  .set("coloring", "colortable")
  .set("sphereradiusscale", 1);
plot.run();
selectNode(pg);
```

When plotting 3D points the line

```
model.result().create(pgTag, 3);
```

has the second argument set to 3 in order to create a **3D Plot Group**. In 3D, the point coordinates, p is a 3-by-N array.

The line

```
.set("sphereradiusscale", 1);
```

controls the radius of the sphere used to render each point.

To automatically display the newly created plot, the line

```
selectNode(pg);
```

is added last in the code segment.

To get a denser set of points, you can increase the integer N to, say, 370.

CURVE IN 3D

The following code plots line segments in the shape of a 3D helix using the **Line Data** plot type.

```
// A 3D helix from line segments

String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("line1", "LineData");
int N = 100;
double[][] p = new double[3][N];
int[][] t = new int[2][N-1];
for (int i = 0; i < N; i++) {
   double s = 4*Math.PI*i/N;</pre>
```

```
p[0][i] = s/5;
p[1][i] = Math.sin(s);
p[2][i] = Math.cos(s);
if (i > 0) {
    t[0][i-1] = i-1;
    t[1][i-1] = i;
}
}
plot.set("pointdata", p)
    .set("elementdata", t);
plot.run();
selectNode(pg);
```

The line

```
ResultFeature plot = pg.create("line1", "LineData");
```

creates a plot of the type LineData. This plot type is only available through methods. Just as for **Point Data** plots, the point coordinates p is a 3-by-N array. In addition to pointdata, the LineData plot type takes elementdata as its input. In the example, this is represented by the 2-by-N array t and contains indexes to the columns of p, corresponding to the start and end points of the lines.

In a similar way, line segments can be plotted in 2D by creating a 2D plot group and by letting the point coordinates be a 2-by-N array. See also "Points in 2D" on page 152.

TRIANGULATED SHAPE IN 2D

The following code plots triangles in the shape of a 2D pentagon by using the **Surface Data** plot type.

```
// A 2D pentagon from triangles
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 2);
ResultFeature plot = pg.create("surf1", "SurfaceData");
int N = 5;
double[][] p = new double[2][N+1];
int[][] t = new int[3][N];
0 = [0][0]q
p[1][0] = 0;
for (int i = 0; i < N; i++) {
  double angle = i*2*Math.PI/N;
  p[0][i+1] = Math.cos(angle);
  p[1][i+1] = Math.sin(angle);
  t[0][i] = 0;
  t[1][i] = i+1;
  t[2][i] = 1+(i+1)%N;
plot.set("pointdata", p)
  .set("elementdata", t);
plot.run();
```

```
selectNode(pg);
```

The line

```
ResultFeature plot = pg.create("surf1", "SurfaceData");
```

creates a plot of the type SurfaceData. This plot type is only available through methods. Just as for 2D **Point Data** plots, the point coordinates p is a 2-by-N array. In addition to pointdata, and similar to the LineData plot type, the SurfData plot type takes elementdata as its input. In the example, this is represented by the 3-by-N array t and contains indexes to the columns of p, corresponding to the vertexes of the triangles. The ordering of the point indexes in the array t is not important for 2D Surface Data plots.

FUNCTION SURFACE IN 3D

The following code plots triangles in the shape of a 3D rotationally symmetric sinc-function surface by using the **Surface Data** plot type.

```
// A 3D sinc(r) function surface
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("surf1", "SurfaceData");
int Nx = 51;
int Ny = 51;
double[][] p = new double[3][Nx*Ny];
int[][] t = new int[3][2*(Nx-1)*(Ny-1)];
double[] color = new double[Nx*Ny];
int pos = 0;
for (int i = 0; i < Ny; i++) {
  for (int j = 0; j < Nx; j++) {
    double x = 20*(j-Nx/2)/Nx;
    double y = 20*(i-Ny/2)/Ny;
    double r = Math.sqrt(x*x+y*y);
    double z = 4*((r == 0) ? 1 : (Math.sin(r)/r));
    p[0][pos] = x;
    p[1][pos] = y;
    p[2][pos] = z;
    color[pos] = z;
   pos++;
  }
}
pos = 0;
for (int i = 0; i < Ny-1; i++) {
  for (int j = 0; j < Nx-1; j++) {
    int p00 = Nx*i+j;
    int p01 = Nx*i+j+1;
    int p10 = Nx*(i+1)+j;
    int p11 = Nx*(i+1)+j+1;
    t[0][pos] = p00;
    t[1][pos] = p01;
    t[2][pos] = p11;
```

```
pos++;
  t[0][pos] = p00;
  t[1][pos] = p11;
  t[2][pos] = p10;
  pos++;
}
}
plot.set("pointdata", p)
  .set("elementdata", t)
  .set("colordata", color)
  .set("coloring", "colortable");
plot.run();
selectNode(pg);
```

This example is similar to "Triangulated Shape in 2D" on page 155, but with the point array being a 3-by-N array for 3D surfaces. For **Surface Data** plots in 3D, the ordering of the indexes in the elementdata array t matters. It determines the direction of the surface normal, which is used for the lighting effect when using **Scene Light** in the **Graphics** window. The surface normal of a triangle is determined according to the "right-hand rule". In mathematical terms, the surface normal is defined as the vector product:

```
\mathbf{n} = (\mathbf{p}[t[1]] - \mathbf{p}[t[0]]) \times (\mathbf{p}[t[2]] - \mathbf{p}[t[0]])
```

where the indexes into t represent the rows in one of the columns of t and p represents a column in the array of points p.

To ensure that the lighting effect produces expected results, the triangle surface normal directions need to consistently point in the same direction as the intended overall surface normal direction. As an alternative to making sure that the indexes come in the correct order, the normal direction may be given as an additional input to a **Surface Data** plot. This is shown in the next example section, Sphere in 3D

SPHERE IN 3D

The following code plots triangles in the shape of a 3D sphere by using the **Surface Data** plot type.

```
// A coarse sphere with user-supplied normals
int Nx = 20;
int Ny = 10;
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("surf1", "SurfaceData");
double[][] p = new double[3][Nx*Ny];
double[][] normals = new double[3][Nx*Ny];
int[][] t = new int[3][2*(Nx-1)*(Ny-1)];
double[] color = new double[Nx*Ny];
```

```
int pos = 0;
double R = 10;
for (int i = 0; i < Ny; i++) {
  for (int i = 0; i < Nx; i++) {
    double theta = Math.PI*i/(Ny-1);
    double phi = 2*Math.PI*j/(Nx-1);
    double x = R*Math.sin(theta)*Math.cos(phi);
    double y = R*Math.sin(theta)*Math.sin(phi);
    double z = R*Math.cos(theta);
    p[0][pos] = x;
    p[1][pos] = y;
    p[2][pos] = z;
    normals[0][pos] = x;
    normals[1][pos] = y;
    normals[2][pos] = z;
    color[pos] = z;
    pos++;
 }
}
pos = 0;
for (int i = 0; i < Ny-1; i++) {
  for (int j = 0; j < Nx-1; j++) {
    int p00 = Nx*i+j;
    int p01 = Nx*i+j+1;
    int p10 = Nx*(i+1)+j;
    int p11 = Nx*(i+1)+j+1;
    t[0][pos] = p00;
    t[1][pos] = p01;
    t[2][pos] = p11;
    pos++;
    t[0][pos] = p00;
    t[1][pos] = p11;
    t[2][pos] = p10;
   pos++;
  }
plot.set("pointdata", p)
  .set("elementdata", t)
  .set("colordata", color)
  .set("normaldata", normals)
  .set("coloring", "colortable");
plot.run();
selectNode(pg);
```

In this example, information about the surface normal direction is not given implicitly by the triangle orientation, but instead explicitly by the parameter normaldata by means of the 3-by-Nx*Ny array normals containing surface normal vectors at each point. The normal vectors do not need to be normalized; only the direction is used. The coloring of the sphere is based on the *z*-coordinate of each triangle point and is stored for each point in the 3-by-Nx*Ny array color.

The sphere is constructed from a discrete grid defined in terms of spherical coordinate angles, where each grid cell is divided into two triangles. The number of triangles t is then given by 2*(Nx-1)*(Ny-1).

TUBE PLOT IN 3D, LOGARITHMIC SPIRAL

The following code plots a tube in 3D in the shape of a logarithmic spiral by using the **Tube Data** plot type.

```
// A logarithmic tube spiral in 3D
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("tube1", "TubeData");
int N = 1000;
double[][] p = new double[3][N];
double[] radius = new double[N];
double[] color = new double[N];
for (int i = 0; i < N; i++) {
  double par = 0.005*i;
  p[0][i] = Math.exp(par)*Math.cos(10*par);
  p[1][i] = Math.exp(par)*Math.sin(10*par);
  p[2][i] = 0.1*i;
  radius[i] = 0.2*Math.sqrt(i+1);
  color[i] = i;
plot.set("pointdata", p)
  .set("radiusdata", radius)
  .set("colordata", color)
  .set("coloring", "colortable");
plot.run();
selectNode(pg);
```

Comments

A **Tube Data** plot is similar to a **Point Data**, plot but with an absolute radius array given as an argument to radiusdata. For the **Point Data** plot type, there is a similar sphereradiusscale.

ARROWS IN 2D

The following code plots arrows in a circular pattern by using the **Arrow Data** plot type.

```
// Arrows in a circular pattern in 2D
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 2);
ResultFeature plot = pg.create("arrow1", "ArrowData");
int N = 17;
double[][] p = new double[2][N];
double[][] vec = new double[2][N];
double len = 0.2;
for (int i = 0; i < N; i++) {</pre>
```

```
double angle = 2*Math.PI*i/N;
p[0][i] = Math.cos(angle);
p[1][i] = Math.sin(angle);
vec[0][i] = -len*p[0][i];
vec[1][i] = -len*p[1][i];
}
plot.set("pointdata", p)
    .set("vectordata", vec);
plot.run();
selectNode(pg);
```

An **Arrow Data** plot associates an array of vectors, in the example vec, to each point p.

ARROWS IN 3D

The following code plots arrows in a logarithmic spiral pattern by using the **Arrow Data** plot type.

```
// Arrows in a logarithmic spiral pattern in 3D
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("arrow1", "ArrowData");
int N = 1000;
double[][] p = new double[3][N];
double[][] vec = new double[3][N];
double[] color = new double[N];
for (int i = 0; i < N; i++) {
  double par = 0.005*i;
  p[0][i] = Math.exp(par)*Math.cos(10*par);
  p[1][i] = Math.exp(par)*Math.sin(10*par);
  p[2][i] = 0.1*i;
  double len = Math.sqrt(p[0][i]*p[0][i]*p[1][i]*p[1][i]*p[2][i]*p[2][i]);
  for (int j = 0; j < 3; j++) {
    vec[j][i] = 4*p[j][i]/len;
  color[i] = i;
plot.set("pointdata", p)
  .set("vectordata", vec)
  .set("colordata", color)
.set("coloring", "colortable");
plot.run();
selectNode(pg);
```

Comments

In this example, in addition to the example in the section "Arrows in 2D", color data is used based on the point index.

Annotations in 2D

The following code renders text strings in a circular pattern by using the **Annotation Data** plot type.

```
// Letters in a circlular pattern in 2D
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 2);

for (int i = 0; i < 26; i++) {
    double angle = 2*Math.PI*i/26;
    ResultFeature plot = pg.create("ann"+i, "AnnotationData");
    plot.set("pos", new double[]{Math.cos(angle), Math.sin(angle)})
    .set("text", "ABCDEFGHIJKLMNOPQRSTUVWXYZ".substring(i, i+1))
    .set("showpoint", false);
}
pg.run();
selectNode(pg);</pre>
```

Comments

The property pos takes as its input an array of length 2 representing 2D coordinates for the position of the string to be rendered. The property text takes as its input the string to be rendered. The Boolean property showpoint determines if a point, at the 2D coordinate position, should be rendered or not.

ANNOTATIONS IN 3D WITH LATEX SYNTAX

The following code renders text strings with Greek letters of different colors at the corners of a cube by using the **Annotation Data** plot type.

```
// Greek letters at the corners of a cube
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
"\\zeta", "\\eta", "\\theta"};
String[] colors = {"black", "blue", "cyan", "gray", "green", "magenta", "red",
"vellow"};
for (int x = 0; x < 2; x++) {
 for (int y = 0; y < 2; y++) {
   for (int z = 0; z < 2; z++) {
     int index = x+2*y+4*z;
     ResultFeature plot = pg.create("ann"+index, "AnnotationData");
     plot.set("pos", new double[]{x, y, z})
       .set("text", "$"+texts[index]+"$")
       .set("latexmarkup", true)
       .set("color", colors[index]);
   }
 }
}
pg.run();
selectNode(pg);
```

The Boolean property latexmarkup determines if the text should be interpreted using LaTeX syntax or not.

Reading and Writing Data to File

The Application Builder provides several built-in methods for reading and writing different types of files: text files, CSV-files, Excel[®] files (requires LiveLink[™] *for* Excel[®]), and binary files. These file methods are listed in the table "File Methods" on page 96.

Note that easy-to-use user-interface-based techniques for reading and writing to file are available in the Form editor of the Application Builder. It is recommended that you consider those techniques first before using the programming-based ways described in this section. For more information, see the book *Introduction to Application Builder* and "GUI Command Methods" on page 122. There, you can also find information on the various file schemes used in the Application Builder for reading and writing files when running applications in a web browser.

READING AND WRITING TEXT AND SPREADSHEET FILES OVERVIEW

The following built-in methods are available for reading and writing text files:

- readFile
- readMatrixFromFile
- readStringMatrixFromFile
- readCSVFile
- writeFile
- writeCSVFile

In addition, you can use the low-level methods available in the class CsReader to read text files line by line or character by character. See the next section, "Processing Text Files using the CsReader and CsWriter Classes" on page 177, for more information.

If you have a LiveLink[™] *for* Excel[®] license, then the following methods are available for reading and writing Microsoft Excel Workbook files:

- readExcelFile
- writeExcelFile

INTRODUCTION TO READING FILES WITH A CSV-FILE EXAMPLE

Assume that you want to automate a certain thermal analysis of a circuit board by creating an application that reads in data from a spreadsheet. Further assume that information about the circuit board components is given by a proprietary format in a spreadsheet with columns for component type, heat dissipation, locations, and sizes. Assume that such a file looks like:

```
B,0,0,0,-1.57,350,200,1.57

B,3,30,10,0,40,10,2

C,1,100,30,0,3,10,

C,1,110,30,0,3,10,

B,4,30,30,0,40,10,2

...

C,1,200,30,0,3,10,

B,10,100,150,0,10,20,30


B,10,130,150,0,10,20,30


B,10,160,150,0,10,20,30
```

Each row of the spreadsheet represents a different component. The first column can contain a letter, either B or C, denoting that the component can be modeled as either a **Block** or a **Cylinder** primitive. The next column is the total heat dissipation within the component (measured in watts). The next three columns represent the location of the component in the global Cartesian coordinate system (measured in millimeters). Lastly, if the row contains a block component, there are three more columns that denote the width, depth, and height of the block. If the row contains a cylinder component, then there are two more columns that contain the radius and height information, respectively.

For the example shown above, the first row of the spreadsheet represents the circuit board itself, which is 1.57 mm thick and 350 mm x 200 mm. It is offset from the origin by -1.57 mm in the z-direction and does not dissipate any heat.

You can write the data in the spreadsheet out to a comma-delimited text file, also known as a CSV-file. The user interface of the application used to read the data is shown in the figure below.





The **Settings** window for the **File Import** form object is shown in the figure below.

In the **Settings** window, **CSV File (*.csv)** is added to the **File types** list. When browsing for the file, this setting will filter out any file that is not a CSV-file.

There is also a **File Declaration** called **File I**, which is referenced by the file scheme syntax upload:///inputFile in the method populateBoard, which is used to read and process the data. The method is called as an event shown at the bottom of the **Settings** window of the **File Import** form object in the **Events** section.

Note that if you would like to open a file browser from a button or a menu item, instead of using a **File Import** object, you can create a method that calls the built-in method importFile; for example

```
importFile("file1");
```


assuming there is a file declaration file1.


The method populateBoard is listed below.

```
String[][] D = readCSVFile("upload:///inputFile");
model.geom("geom1").feature().clear();
```

```
for (int k = 0; k < D.length; k++) {
  if (D[k][0].equals("B")) { // Read in a block
    model.geom("geom1").create("P"+k, "Block").set("pos", new
String[]{D[k][2], D[k][3], D[k][4]});
    model.geom("geom1").feature("P"+k).set("size", new String[]{D[k][5],
D[k][6], D[k][7];
  else if (D[k][0].equals("C")) { // Read in a cylinder
    model.geom("geom1").create("P"+k, "Cylinder").set("pos", new
String[]{D[k][2], D[k][3], D[k][4]});
    model.geom("geom1").feature("P"+k).set("r", D[k][5]);
    model.geom("geom1").feature("P"+k).set("h", D[k][6]);
  }
  model.geom("geom1").feature("P"+k).set("selresult", "on");
  model.variable().remove("var"+k);
  model.variable().create("var"+k).model("comp1");
  model.variable("var"+k).selection().named("geom1 P"+k+" dom");
  model.variable("var"+k).set("Q", D[k][1]);
model.geom("geom1").run();
zoomExtents("/form1/graphics1");
```

In the first line, the data read from the CSV-file is stored in the 2D array D. The rest of the code parses this array and populates the various parts of a model object. The application allows you to save the result as an MPH-file with variables defined for the heat sources and geometry objects defined for the components, as shown in the figures below.






You can download the MPH-file for this app from:

https://www.comsol.com/model/using-text-files-to-automate-model-preprocessing-46721

READING EXCEL FILES

The application described above can easily be extended to also read Microsoft Excel[®] Workbook files. Note that this requires LiveLinkTM for Excel[®]. In the **Settings** window for the **File Import** form object, you can add **Microsoft Excel**


Workbook (*.xlsx) and Microsoft Excel Workbook (*.xls) to the File types section, as shown in the figure below.



The next step is to add a few lines of code in the beginning of the method populateBoard, as shown below.

```
String file_name = getFilePath("upload:///inputFile");
if (file_name.endsWith(".xls") || file_name.endsWith(".xlsx"))
  D = readExcelFile("upload:///inputFile");
else if (file_name.endsWith(".csv"))
  D = readCSVFile("upload:///inputFile");
else
  error("Unknown file type.");
```

Here the 2D array D is defined as a global array in the **Declarations** node in the application tree, as shown below.




Alternatively, it can be declared as an array that is local to the method by adding the line

```
String[][] D = null;
```

before the if statement. Which option to choose depends on how you would like to use the 2D array data after having read the file.

The method getFilePath returns the full path and name of the uploaded file. The if statements control which method is used to read the file based on its file extension. The file extension is retrieved with the Java[®] method endsWith(), which belongs to the String class. Note that you can see which methods are

available for a string by typing the name of the string followed by a period and Ctrl+Space, as shown in the figure below.



WRITING CSV-FILES

You can write to a CSV-file using four different call syntaxes for the method writeCSVFile, depending on if the contents are strings or doubles and whether you would like to overwrite an already existing file or appending to its contents.

In the case above, the contents are a mix of numbers and characters, so the 2D array storing the information needs to be a string array.

Assume that we would like to move one of the components, say, the second to last one, in the file listed above. We would like to change the corresponding line in the file from

```
B,10,130,150,0,10,20,30
to
B,10,130,140,0,10,20,30
```

This corresponds to a change in the y-coordinate of one of the blocks from 150 to 140.

The following code shows how to make this change and then write data on this format, assuming that the array D has been declared as a global variable in the **Declarations** node, as described above.

```
int[] sz = matrixSize(D);
D[sz[0]-2][3] = "140.0";
writeCSVFile("temp:///my_layout.csv", D);
fileSaveAs("temp:///my_layout.csv");
```

The first line stores the size of the 2D array (or matrix) D in a 1-by-2 array (or vector) sz. The second line sets the string value of the *y*-coordinate of the block of the second-to-last row in D.

The line

```
writeCSVFile("temp:///my layout.csv", D);
```

writes the data to a file my_layout.csv in a temporary folder whose location is determined by the **Preferences** of either COMSOL Multiphysics or COMSOL Server, depending on which software is used to run the application. For example, in a typical Windows[®] installation of COMSOL Multiphysics, the location will be similar to

```
C:\Users\paul\AppData\Local\Temp\
```

where the username is paul.

WRITING FILES IN GENERAL

Note that as a first step in the example above, the file is written to a temporary file using the writeCSVFile method. This step is done automatically by the application. In the second step, the method fileSaveAs opens a file browser and lets the user of the application choose the file location; for example, a folder on the computer's local file system or to a network folder. This extra step is needed in order for the application to function in a web browser. Due to the security settings of a typical web browser, the application is not permitted to automatically save a file to an arbitrary location. Instead, the application is allowed to save to a few specific locations, including the temp folder, whose location is specified in the **Preferences** settings. The other locations are the user and common folders, also specified in the **Preferences** settings. For more information, see the *Introduction to Application Builder*.

WRITING EXCEL FILES

If you have licensed LiveLink[™] *for* Excel[®], then you can write to a Microsoft Excel Workbook file in a way that is similar to that of a CSV-file, with the exception that the append option is not available. The following code, corresponding to the previous CSV-file example, shows how to write to an Excel file.

```
int[] sz = matrixSize(D);
D[sz[0]-2][3] = "140.0";
writeExcelFile("temp:///my_layout.xlsx", D);
fileSaveAs("temp:///my_layout.xlsx");
```

READING MATRIX FILES

Reading files with numerical data in matrix format is easiest when using the readMatrixFromFile method. This method assumes that the file has the spreadsheet format, as available in the model tree **Export** node. The example below shows a file on the spreadsheet format.

```
% Model:
                     my model.mph
% Version:
                     COMSOL 5.4.0.123
% Date:
                    May 1 2018, 8:00
% Dimension:
% Nodes:
                    5
% Expressions:
% Description:
                   Line graph
% X
1.2 -0.45
1.11 -0.3
1.0440468877558806 -0.38655264416650392
1.041666666666667 -0.4916666666666667
1.02 -0.15
```

The first few lines with comments start with the character % and are ignored by the readMatrixFromFile method. You can optionally omit such lines and just have the numerical part of a file read by readMatrixFromFile. Assume that this file is uploaded to an application using a **File Import** form object and a **File** declaration file1. The following code can then be used to read the data into a double array p.

```
double p[][] = readMatrixFromFile("upload:///file1");
```

The code below shows how to both import and visualize these points in an application that, in addition to a **File Import** form object and a **File** declaration file, has a form form1 and a graphics object graphics1.

```
double p[][] = readMatrixFromFile("upload:///file1");
double pt[][] = transpose(p);

String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 2);
ResultFeature plot = pg.create("pt1", "PointData");
plot.set("pointdata", pt);
plot.run();
useGraphics(model.result(pgTag), "form1/graphics1");
```

Reading files on the spreadsheet format as a string array can be done with the method readStringMatrixFromFile. Also, in this case, the comment lines will be ignored. The code below shows how you can replace the first few lines in the above example using readStringMatrixFromFile instead of readMatrixFromFile.

```
String p[][] = readStringMatrixFromFile("upload:///file1");
double pt[][] = transpose(toDouble(p));
```

The method readStringMatrixFromFile is most useful when parts of the read file contains text


WRITING MATRIX FILES

To write numerical matrix data to file, you can use the method writeFile. Assume that you want to write a matrix of random 2D coordinate values to a file on the spreadsheet format; for example:

The code below shows how to do this.

```
int N = 100;
double[][] p = new double[N][2];
for (int k = 0; k < N; k++) {
   p[k][0] = Math.random()-0.5;
   p[k][1] = Math.random()-0.5;
}
writeFile("temp:///my_data.txt", p);
fileSaveAs("temp:///my_data.txt");</pre>
```

The resulting file can now be read back in and plotted by using the code of the previous example. The result, in an application, may look like the figure below.




Note that you can append data to an already existing file by providing an additional Boolean input argument; for example:

```
writeFile("temp:///my_data.txt", p,true);
fileSaveAs("temp:///my_data.txt");
```


If you would like to export a matrix with a mix of numeric and text data, you can use the writeFile method with a string array instead of a double array. The syntax for this case is otherwise identical to that of the double array shown in the example above.

READING A TEXT FILE TO A STRING

For reading text files into a string, you can use the method readFile. A straightforward use of readFile is for previewing a text file; for example, before importing and parsing it, as illustrated by the example application in the figure below.



This application has two form objects: a **File Import** form object referencing a **File** declaration file1 and a **Text** form object referencing a string str declared in the **Declarations** node as a global variable.



The **File Import** form object has an **Event** that calls the method read_string upon data change.

This method has one line of code, as shown below.

```
str = readFile("upload:///file1");
```

Since the **Text** object is referencing the global string str, the contents of the file are displayed in the **Text** object immediately after import.

Parsing of smaller text files can be done with readFile in combination with the many text processing methods available in the String class. However, it is often more efficient to use methods in the CsReader class, as described in the section "Processing Text Files using the CsReader and CsWriter Classes" on page 177, especially for larger text files. The reason is that when using the readFile method, the entire file is read into a string with all its contents kept in memory; whereas when using the CsReader class methods, only small portions of the file are kept in memory at any given time.

If you would like to parse smaller text files using readFile, then the built-in "String Methods" on page 144 are useful. The example code below illustrates using the built-in methods findIn, substring, split, as well as the regular Java® methods System.getProperty and String.startsWith. The example parses the header of a text file containing polygon information to retrieve information about the number of points of each polygon in the main body of the file (not shown) as

well as the number of properties (for example, color or material property). The header portion of the file may look like the example below.

```
Demo file for string parsing
Created on May 1st 2018
begin_header
number_of_points 4
number_of_properties 4
end header
```

The code for parsing the header is listed below. It stores the number of points and properties in the variables n_of_points and n_of_properties, respectively. To keep things simple, no error handling is done. For example, the code assumes that there is exactly one instance of begin header and end header.

```
int n of points = 0;
int n of properties = 0;
String fileContents = readFile("upload:///file1");
String eol = System.getProperty("line.separator"); // find the system end of line
int headerBeginIndex = findIn(fileContents, "begin header");
int headerEndIndex = findIn(fileContents, "end header");
String headerContents = substring(fileContents, headerBeginIndex,
  headerEndIndex-headerBeginIndex); // Convert to string array by splitting at
String[] headerContentsArr = split(headerContents, eol);
int ix = 1;
String[] headerRowArr = new String[2];
  // Split each line at space.
  headerRowArr = split(headerContentsArr[ix], " ");
  if (headerRowArr.length == 2) {
    if (headerRowArr[0].trim().equalsIgnoreCase("number of points"))
          n of points = toInt(headerRowArr[1]);
    if (headerRowArr[0].trim().equalsIgnoreCase("number of properties"))
          n of properties = toInt(headerRowArr[1]);
  }
  ix++;
} while (ix < headerContentsArr.length);</pre>
```

The Java[®] String class has many methods for text processing. See the online Java[®] documentation for more information.

WRITING A STRING TO A TEXT FILE

The following example shows how to use the method writeFile to write a string to file.

```
String contents = "# Created by me\r\n"
    +"# Version 1.0 of this file format \r\n"
    +"# Body follows\r\n"
    +"0 1 \r\n"
```

```
+"2 3\r\n"
+"4 5\r\n";

writeFile("temp:///my_data.txt", contents);
fileSaveAs("temp:///my_data.txt");
```

The use of the file scheme syntax temp:/// is described above in the earlier examples of this section. The end-of-line characters of this example are for Windows[®]; see also "Special Characters" on page 11.

To append additional data to the same file, for example:

```
String contents_2 = "6 7\r\n"
+"8 9\r\n"
+"10 11\r\n";
```

use an additional Boolean input argument, which appends data when set to true:

```
writeFile("temp:///my_data.txt", contents_2, true);
fileSaveAs("temp:///my_data.txt");
```

PROCESSING TEXT FILES USING THE CSREADER AND CSWRITER CLASSES

The most efficient and flexible way to read and write to a text file is to use the methods in the CsReader and CsWriter classes, respectively. However, using the methods of these classes is more complicated than using any of the built-in methods described above.

The CsReader class inherits all public methods of the abstract Java® class Reader. In a similar way, the CsWriter class inherits all public methods of the abstract Java® class Writer. This means that when using these classes, you get access to a large number of methods for processing text files. These methods are not documented here, but you can find a lot of information with regards to using these methods online as well as in books on Java® programming. In addition, you can see which methods are available by using code-completion Ctrl+Space.

READING TEXT FILES USING THE CSREADER CLASS

The example code below shows how to parse the text file header of the earlier example for reading strings using the built-in method readFile. The header may look like:

```
Demo file for string parsing
Created on May 1st 2018
begin_header
number_of_points 4
number_of_properties 4
end header
```

and the corresponding code is listed below (compare with the example "Reading a Text File to a String" on page 174).

```
int n_of_points = 0;
int n of properties = 0;
```

```
int max header length = 100;
  CsReader reader = openFileStreamReader("upload:///file1");
  String line: // Each line in the file
  String[] lineArr; // The contents of each line in an array
  int li = 0; // Line counter
  boolean begin header found = false;
  boolean end header found = false;
  while (!begin header found && li < max header length && ((line =
  reader.readLine()) != null)) {
    if (line.trim().startsWith("begin header"))
      begin header found = true;
    li++;
  }
  while (begin header found && !end header found && li < max header length &&
  ((line = reader.readLine()) != null)) {
    lineArr = split(line, " ");
    if (lineArr[0].trim().equalsIgnoreCase("number of points"))
      n of points = toInt(lineArr[1]);
    if (lineArr[0].trim().equalsIgnoreCase("number of properties"))
      n of properties = toInt(lineArr[1]);
    if (line.trim().startsWith("end header"))
      end header found = true;
    li++;
  if (!begin header found || !end header found)
    error("File does not have the right format.");
Comments
The line
```

```
CsReader reader = openFileStreamReader("upload:///file1");
```

opens a Java® character stream and assigns it to the object reader belonging to the class CsReader.

The while loop condition contains the statement

```
(line = reader.readLine()) != null)
```


which is reading a line from the character stream and storing the result in the string line. A line is considered to be terminated by one of the characters carriage return \r, line feed \n, or the composite \r\n. If there are no more lines to read, then null is returned.

For more information on the string methods used in this and earlier examples, including findIn, substring, and split, see the section "Writing a String to a Text File" on page 176.

Note that you can see which additional methods are available for the reader object by using Ctrl+Space, as shown in the figure below.

```
CsReader reader = openFileStreamReader("upload:///file1");
 5
 6
 7
      reader.
 8
          markSupported()
9
      Stri@ read()
                                  n the file
      Strio read(CharBuffer)
10
                                  ntents of each line in an array
11
          read(char[])
          read(char[], int, int)
13
                                  = false:
      bool readLine()
14
                                  false;
          ready()
15
16 □ whii reset()
                                  && li < max header length && (()
        ii skip(long)
17
                                  eader") != -1)
18
          equals(Object)
                                ue;
        1i++,
```

By using Ctrl+Space following a string, you can see the many additional methods available for strings, including the trim method used in the example above:



WRITING TEXT FILES USING THE CSWRITER CLASS

The example of the section "Reading Matrix Files" on page 172 uses an example on the spreadsheet data format. This section contains an example that writes a file on the sectionwise format, the other primary format in COMSOL Multiphysics for saving postprocessing data. Data on the sectionwise format can, for example, be read into an **Interpolation Curve** geometry primitive. A file on the sectionwise format may look like this:

```
% Version: COMSOL 5.4.0.123
% Date: May 5 2018, 8:00
% Description: Interpolation curve
```

```
-1.1 -0.8
1.2 -0.9
0.9 1.3
-0.8 1.05
% Elements (segments)
1 2
2 3
3 4
```

The first few lines with comments start with the character % and are ignored when imported as an **Interpolation Curve**. The first section containing data starts on the line after % Coordinates. The second section containing data starts on the line after % Elements (segments). Note that the strings Coordinates and Elements (segments) are not necessary but each section containing data will be assumed to start after each block of comments, regardless of what comes after the character %. There may be additional blocks of data when, for example, exporting **Contour** plot data

The following example code uses a CsWriter stream to write interpolation curve data to a text file. A template point set p is copied in a circular pattern for a given radius R and number of copies n_of_copies.

```
CsWriter writer = openFileStreamWriter("temp:///my curve.txt");
int n of copies = 10;
double[][] p = \{\{-1.2, -0.9\}, \{0.9, -1.1\}, \{1.3, 0.8\}, \{-0.9, 1.0\}\}; // template
int template length = p.length;
double R = 10;
double px, pv;
double pi = Math.PI;
String line;
int i1, i2;
String header = "% Version:\tCOMSOL 5.4.0.123\r\n"
 +"% Date:\tMay 5 2018, 8 : 00\r\n"
  +"% Description:\tInterpolation curve\r\n"
  +"% Coordinates:\r\n";
writer.append(header);
for (int j = 0; j < n of copies; j++) {
  for (int i = 0; i < template length; i++) {
    px = p[i][0];
    py = p[i][1];
    px = px+R*Math.cos(2*pi*j/n of copies);
    py = py+R*Math.sin(2*pi*j/n_of_copies);
    line = toString(px)+"\t"+toString(py)+"\r\n";
   writer.append(line);
 }
}
writer.append("% Elements (segments):\r\n");
for (int j = 0; j < n of copies; j++) {
```

```
for (int i = 0; i < template length; i++) {</pre>
      i1 = i+1;
      i2 = (i+1)%template length+1;
      i1 = i1+j*template length;
      i2 = i2+j*template length;
      line = toString(i1)+"\t"+toString(i2)+"\r\n";
      writer.append(line);
    }
  }
  writer.flush();
  writer.close();
  fileSaveAs("temp:///my curve.txt");
Comments
The line
  CsWriter writer = openFileStreamWriter("temp:///my curve.txt");
opens a Java® character stream and assigns it to the object writer belonging to
the class CsWriter.
The line
  writer.append(header);
appends the contents of the string header to the (empty) file my curve.txt.
The line
  writer.flush():
writes the contents of the character stream buffer to file and empties the buffer but
does not close the stream permanently. At this point, you can still write more data
to the stream.
```


writer.close();

closes the stream permanently. If you wish to write additional data to the file, you have to open the stream again and append additional data.

Just as described above for the reader object, you can see which additional methods are available for the writer object by using Ctrl+Space, as shown in the figure below.

```
CsWriter writer = openFileStreamWriter("temp:///my curve.txt");
 2
      writer.
4
          append(CharSequence)
 5
      append(CharSequence, int, int)
                                           1.1}, {1.3, 0.8}, {-0.9, 1.0}}; // template
 6
      dout append(char)
          checkError()
 8
      dout
          close()
      dout
 9
      dout flush()
10
      Stri® format(Locale, String, Object...)
11
     int format(String, Object...)
12
          print(Object)
13
14
      Stri@ print(String)
                                            .4.0.123\r\n"
15
        +"% Description:\tInterpolation curve\r\n"
      +"% Coordinates:\r\n";
```

You can import the resulting interpolation data as an **Interpolation Curve** by selecting the **Sectionwise** option for **Data format**. This can be done for a 2D geometry object or for a **Work Plane** in 3D. The figure below shows the data imported to a 2D model.



WRITING BINARY FILES

The line

You write data to a binary file by using the methods of the class CsBinaryWriter in a way that is somewhat similar to that of writing text using CsWriter. However, instead of writing strings and characters, you are writing bytes. To see how many bytes each data type requires, see the table in the section "Primitive Data Types" on page 8.

The example code below writes random 3D point data to a binary file. Each point coordinate is stored as a double and takes 8 bytes to store. The first 4 bytes of the file stores the number of points in the file as an int.

To conveniently convert between the regular data types, such as double, int, and byte arrays, the Java® library method java.nio.ByteBuffer is needed. This method is not part of the standard methods available in the Method editor and you need to use the fully qualified Java® class name java.nio.ByteBuffer, as shown in the example code below.

```
byte[] bytes8 = new byte[8];
  byte[] bytes4 = new byte[4];
  CsBinaryWriter bwriter =
  openBinaryFileStreamWriter("temp:///my binary file.dat");
  int N = 1000:
  java.nio.ByteBuffer.wrap(bytes4).putInt(N);
  bwriter.write(bytes4);
  double p[][] = new double[N][3];
  for (int k = 0; k < N; k++) {
    p[k][0] = Math.random();
    iava.nio.ByteBuffer.wrap(bytes8).putDouble(p[k][0]):
    bwriter.write(bytes8);
    p[k][1] = Math.random();
    java.nio.ByteBuffer.wrap(bytes8).putDouble(p[k][1]);
    bwriter.write(bytes8);
    p[k][2] = Math.random();
    java.nio.ByteBuffer.wrap(bytes8).putDouble(p[k][2]);
    bwriter.write(bytes8);
    bwriter.flush();
  bwriter.close();
  fileSaveAs("temp:///my_binary_file.dat");
Comments
The first two lines declare byte arrays of size 8 and 4, respectively
The line
  CsBinaryWriter bwriter =
  openBinaryFileStreamWriter("temp:///my binary file.dat");
opens a Java<sup>®</sup> byte stream.
```

```
int N = 1000; // The number of points
```

denotes the number of points written to file.

The line

```
ByteBuffer.wrap(bytes4).putInt(N);
```

uses the imported ByteBuffer method to convert the integer N to a byte array bytes4 of length 4.

The line

```
bwriter.write(bytes4);
```

writes the value of N to file.

The for-loop creates N points and writes each x-, y-, and z-coordinate as doubles using a byte array bytes8 of length 8.

The line

```
bwriter.flush();
```

empties the byte buffer and the last two lines

```
bwriter.close();
fileSaveAs("temp:///my_binary_file.dat");
```

close the byte stream and display a file browser to the user to select a location to save the binary file.

READING BINARY FILES

Based on the data format of the previous example, the code below reads a corresponding binary file and plots the points as 3D point data.

```
byte[] bytes8 = new byte[8];
byte[] bytes4 = new byte[4];
CsBinaryReader breader = openBinaryFileStreamReader("upload:///file1");
breader.read(bytes4);
int N = java.nio.ByteBuffer.wrap(bytes4).getInt();
double p[][] = new double[N][3];
for (int k = 0; k < N; k++) {
    breader.read(bytes8);
    p[k][0] = java.nio.ByteBuffer.wrap(bytes8).getDouble();
    breader.read(bytes8);
    p[k][1] = java.nio.ByteBuffer.wrap(bytes8).getDouble();
    breader.read(bytes8);
    p[k][2] = java.nio.ByteBuffer.wrap(bytes8).getDouble();
}
breader.close();</pre>
```

```
double pt[][] = transpose(p);
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("pt1", "PointData");
plot.set("pointdata", pt);
plot.run();
useGraphics(model.result(pgTag), "form1/graphics1");
```

Comments

The line

```
CsBinaryReader breader = openBinaryFileStreamReader("upload:///file1");
```

opens a Java[®] byte stream based on a **File** declaration file1, typically referenced in a **File Browser** form object, as in the earlier examples on reading text files.

The two lines

```
breader.read(bytes4);
int N = ByteBuffer.wrap(bytes4).getInt();
```

read the first 4 bytes and convert them to an int N.

The following for-loop reads chunks of 8 bytes into the byte array bytes8, converts them and stores the results in a 2D double array p.

The line

```
breader.close():
```

closes the byte stream.

The last section of the example code plots the data and is similar to the example in "Reading Matrix Files" on page 172.

ADDITIONAL COMMENTS ON READING AND WRITING BINARY FORMATS

When processing binary files, there are two formats in which bytes can be stored: little endian and big endian, respectively. By default, Java® uses the big endian format. For example, the line


```
p[k][2] = ByteBuffer.wrap(bytes8).getDouble();
is the same as
p[k][2] = ByteBuffer.wrap(bytes8).order(ByteOrder.BIG ENDIAN).getDouble();
```

In case the format you are reading is on the little endian format, the corresponding line should be

```
p[k][2] = ByteBuffer.wrap(bytes8).order(ByteOrder.LITTLE ENDIAN).getDouble();
```

Converting Interpolation Curve Data

The following method converts a geometry **Interpolation Curve** to an **Interpolation** function (by creating an interpolation table). The method demonstrates extracting geometry information from the underlying parameterization of an edge. The edge doesn't have to be an **Interpolation Curve** but can be any single edge.



The curve is checked for being monotonous, which is required in order to be able to convert to an interpolation function. Note that since an interpolation curve is represented using splines, even though the interpolation points form a monotonous sequence, the resulting curve may not; hence, the second consistency check (the first check can potentially be skipped).

```
// Convert using N points
int N = 100;
double monoTol = 1e-6;
int edgeNum=1;

// Update and get geometry information
model.component("comp1").geom("geom1").run("fin");
GeomSequence geom1 = model.component("comp1").geom("geom1");
GeomFeature ic1 = geom1.feature("ic1");
double[][] curvePoints = ic1.getDoubleMatrix("table");
int len = curvePoints.length;
double minX = curvePoints[0][0];
double maxX = curvePoints[len-1][0];
double scale = maxX-minX;
double scaledTol = monoTol*scale;
```

```
for (int i = 1; i < len; i++) {
  if ((curvePoints[i][0]-curvePoints[i-1][0]) < scaledTol) {</pre>
    error("Curve needs to be a function curve with monotonously growing x
coordinates.");
  }
double minMaxS[] = geom1.edgeParamRange(edgeNum);
double minS = minMaxS[0];
double maxS = minMaxS[1];
double sList[] = new double[N];
for (int k = 0; k < N; k++) {
  sList[k] = (double) (N-1-k)/(double) (N-1)*minS+k/(double) (N-1)*maxS;
double[][] XY = geom1.edgeX(1, sList);
for (int j = 1; j < N; j++) {
  if ((XY[j][0]-XY[j-1][0]) < scaledTol) {</pre>
    error("Curve needs to be a function curve with monotonously growing x
coordinates.");
}
// Create interpolation table
model.func().create("int1", "Interpolation");
with(model.func("int1"));
  set("funcname", "int1");
set("interp", "cubicspline");
set("extrap", "linear");
endwith();
model.func("int1").set("table", toString(XY));
```

Comments


The method assumes that there is a geometry sequence geom1 with an interpolation curve ic1. It further assumes that there are no other geometry features and that the geometry object has a single edge. The integer N determines how granular the interpolation table should be. It is assumed that there is only one edge in the geometry sequence (edgeNum). Note that the curve parameter range may not be the unit interval (minS does not have to be 0.0 and maxS does not have to be 1.0). To run the method more than once, you can create a cleanup method that contains the lines:

```
model.func().remove("int1");
model.result().remove("pg1");
```

for removing previously created model tree nodes.

Plotting Points on a Parametric Surface

The following method retrieves coordinate values for a regularly sampled parametric surface and plots the corresponding points using a **Point Data** plot. The method demonstrates extracting geometry information from the underlying parameterization of a surface.



```
// Sample and plot N-by-N points on a parametric surface
int N = 20;
int faceNum = 1;
// Update and get geometry information
model.component("comp1").geom("geom1").run("fin");
GeomSequence geom1 = model.component("comp1").geom("geom1");
GeomFeature ps1 = geom1.feature("ps1");
double minMaxS[] = geom1.faceParamRange(faceNum);
double minS1 = minMaxS[0];
double maxS1 = minMaxS[1];
double minS2 = minMaxS[2];
double maxS2 = minMaxS[3];
double s1List[] = new double[N];
double s2List[] = new double[N];
for (int k = 0; k < N; k++) {
  s1List[k] = (double) (N-1-k)/(double) (N-1)*minS1+k/(double) (N-1)*maxS1;
  s2List[k] = (double) (N-1-k)/(double) (N-1)*minS2+k/(double) (N-1)*maxS2;
}
double s12List[][] = new double[N*N][2];
for (int i = 0; i < N; i++) {
```


```
for (int j = 0; j < N; j++) {
    s12List[i+N*j][0] = s1List[i];
    s12List[i+N*j][1] = s2List[j];
  }
}
double[][] XY = geom1.faceX(faceNum, s12List);
// Plot points
String pgTag = model.result().uniquetag("pg");
ResultFeature pg = model.result().create(pgTag, 3);
ResultFeature plot = pg.create("pt1", "PointData");
double[][] p = new double[3][N*N];
double[] color = new double[N*N];
for (int i = 0; i < N*N; i++) {
  p[0][i] = XY[i][0];
  p[1][i] = XY[i][1];
  p[2][i] = XY[i][2];
  color[i] = p[1][i];
plot.set("pointdata", p)
  .set("colordata", color)
  .set("coloring", "colortable")
  .set("sphereradiusscale", 1);
plot.run();
selectNode(pg);
```

Using Selections for Editing Geometry Objects

The following method generates a plate with an array of cylinders. The cylinders may be used, for example, in a difference operation to create an array of holes in the plate.


```
GeomSequence geom = model.component("comp1").geom("geom1");
geom.create("blk1", "Block");
geom.feature("blk1").set("size", new int[]{10, 10, 1});
geom.create("start_cyl1", "Cylinder");
geom.feature("start_cyl1").set("pos", new double[]{2.5, 2.5, 0});
geom.create("arr1", "Array");
geom.create("arr1").selection("input").set("start_cyl1");
geom.feature("arr1").set("fullsize", new int[]{2, 2, 1});
geom.feature("arr1").set("disp1", new int[]{5, 5, 0});
geom.run("arr1");
```

The resulting geometry is shown in the figure below.



Assume now that the resulting geometry, from the previous step, corresponds to an imported geometry object and that you would like to replace the cylinders with larger cylinders before subtracting and generating the holes. Furthermore, assume that the cylinder objects are generated by an external software in such a way that, although you know these objects are cylinders, they are represented as generic geometry objects with no information on radius, height, or position. The following method finds the array of cylinders, extracts coordinate information for each cylinder, deletes the cylinders, creates a new array of wider cylinders, and

finally subtracts the cylinders from the plate. The resulting geometry is shown in the figure below.



The method exemplifies retrieval of geometry object names, coordinate information, and the use of selections. To start from another geometry object (which is also necessarily a plate with cylinders), you can replace the string tag in the variable plateAndCylinders accordingly.

```
double selTol = 1e-2; // Selection tolerance
double newR = 1.25; // New cylinder radius
double newH = 1; // New cylinder height
double plateThickness = 1; // Plate thickness
String plateAndCylinders = "arr1";
// Update and split geometry
GeomSequence geom = model.component("comp1").geom("geom1");
geom.run(plateAndCylinders);
geom.create("spl1", "Split");
geom.feature("spl1").selection("input").set(plateAndCylinders);
geom.run("spl1");
// Find extents of geometry in x,y,z directions
double[] bBox = geom.getBoundingBox();
double MinX = bBox[0];
double MaxX = bBox[1];
double MinY = bBox[2];
double MaxY = bBox[3];
double MinZ = bBox[4];
double MaxZ = bBox[5];
// Define scaled coordinate tolerance
double scale = Math.max(Math.max(MaxX-MinX, MaxY-MinY), MaxZ-MinZ);
```

```
double scaleSelTol = scale*selTol;
// Create box selection based on geometry extents
geom.create("boxsel1", "BoxSelection");
with(geom.feature("boxsel1"));
  // Select boundaries inside box in X-Y direction using tolerance
  set("xmin", MinX+scaleSelTol);
  set("xmax", MaxX-scaleSelTol);
  set("ymin", MinY+scaleSelTol);
  set("ymax", MaxY-scaleSelTol);
 set("zmin", MinZ-scaleSelTol);
set("zmax", MaxZ+scaleSelTol);
  set("condition", "inside");
  set("entitydim", -1); // Select objects
endwith();
geom.run("boxsel1");
// Get object names
String[] so = geom.selection("boxsel1").objects();
int nso = so.length;
// Extract cylinder parameters
double[] MinXC = new double[nso];
double[] MaxXC = new double[nso];
double[] MinYC = new double[nso];
double[] MaxYC = new double[nso];
double[] MinZC = new double[nso];
double[] MaxZC = new double[nso];
double[] bBoxC = new double[6];
for (int i = 0; i < nso; i++) {
  bBoxC = geom.obj(so[i]).getBoundingBox();
  MinXC[i] = bBoxC[0];
  MaxXC[i] = bBoxC[1];
 MinYC[i] = bBoxC[2];
 MaxYC[i] = bBoxC[3];
  MinZC[i] = bBoxC[4];
 MaxZC[i] = bBoxC[5];
double[] radius = new double[nso];
double[] xc = new double[nso];
double[] yc = new double[nso];
double[] zc = new double[nso];
double[] hc = new double[nso];
double ry;
double tol = scale*1e-6; // Tolerance check for skew cylinders, optional
consistency check
for (int i = 0; i < nso; i++) {
  xc[i] = (MaxXC[i]+MinXC[i])/2;
  yc[i] = (MaxYC[i]+MinYC[i])/2;
  zc[i] = (MaxZC[i]+MinZC[i])/2;
  hc[i] = MaxZC[i]-MinZC[i];
  radius[i] = (MaxXC[i]-MinXC[i])/2;
  ry = (MaxYC[i]-MinYC[i])/2;
  if (Math.abs(radius[i]-ry) > tol)
```

```
error("Object is not a circular cylinder.");
}
// Delete all cylinder objects
geom.create("del1", "Delete");
geom.feature("del1").selection("input").init();
geom.feature("del1").selection("input").set(so);
geom.run("del1");
// Add new cylinders
String[] cylname = new String[nso];
for (int i = 0; i < nso; i++) {
  cylname[i] = "cyl"+toString(i+1);
  geom.create(cylname[i], "Cylinder");
  with(geom.feature(cvlname[i]));
    set("r", newR);
    set("h", newH+2*scaleSelTol);
    set("pos", new double[]{xc[i], yc[i], plateThickness-2*zc[i]-scaleSelTol});
  endwith();
}
// Combine all cylinders into one object
geom.create("uni1", "Union");
geom.feature("uni1").selection("input").set(cylname);
geom.run("uni1");
// Difference between all objects and cylinders
geom.create("dif1", "Difference");
String[] objs = geom.objectNames();
geom.feature("dif1").selection("input").set(objs);
geom.feature("dif1").selection("input2").set("uni1");
geom.run("dif1");
```

Comments

The method assumes that the input geometry objects have the same structure as the plate with cylinders example above. Note that to clear the geometry sequence, you can create a method with the line


```
model.component("comp1").geom("geom1").feature().clear();
```


This can be useful if you are running the main method from above repeatedly, since you need to clear the geometry sequence before each run.

The first of the lines

```
geom.feature("del1").selection("input").init();
geom.feature("del1").selection("input").set(so);
```

initializes the selection to be empty of type object. The second line then selects all objects with names in the array so. In general, a call to init() without input argument means that the selection is for objects and init(n), where n=0,1,2, or 3, means that the selection is for points, edges, faces, and domains, respectively. Note that in some cases n=-1 is used to denote the object level (instead of an empty input argument); see the *Programming Reference Manual*.





Recursion and Recursively Defined Geometry Objects

Methods can support recursion by having a function calling itself in a recursive loop. The following examples create recursive CAD geometry models of a Sierpinski carpet in 2D and a Menger sponge in 3D.

Sierpinski Carpet


The following method, create_carpet, initiates the recursion to a certain recursive level according to a user-defined **Parameter** mslevel, defined under **Global Definitions** in the **Model Builder.** It sets a limit at 5 levels in order to avoid creating an exceedingly large geometry. The method assumes that you have created a 2D Component and that you have declared an integer scalar variable counter.

```
int level = (int) model.param().evaluate("mslevel");
if (level < 1)
  error("Carpet level needs to be at least 1.");
if (level > 5)
  error("Carpet level needs to be at most 5.");
counter = 0;
model.component("comp1").geom("geom1").feature().clear();
model.component("comp1").geom("geom1").autoRebuild("off");
double cx0 = 0, cy0 = 0;
double si0 = 1;
```

```
carpet(level, cx0, cy0, si0);
model.component("comp1").geom("geom1").runPre("fin");
```

The method create_carpet in turn calls the main recursive function carpet, listed below, using four input arguments for the recursion level, the center x- and y-coordinates, and the current side length.


The input arguments are defined in the method's **Settings** window, as shown below.



The code for the method carpet is shown below.

```
int 1 = level;
double posx, posy, si1;
String strix;
int 11;
for (int i = 0; i < 3; i++) {
  for (int j = 0; j < 3; j++) {
    posx = cx+i*si-si;
    posy = cy+j*si-si;
    strix = toString(i)+toString(j);
    if ((Math.abs((i-1))+Math.abs((j-1))) > 0) {
      if (1 == 1) {
        counter = counter+1;
model.component("comp1").geom("geom1").create("sq"+strix+"C"+toString(counter)
, "Square");
with(model.component("comp1").geom("geom1").feature("sq"+strix+"C"+toString(co
unter)));
          set("base", "center");
          set("size", new double[]{si});
          set("pos", new double[]{posx, posy});
        endwith();
```

The figure below shows the resulting geometry for a level-3 carpet.



Note that the number of square geometry objects defined for the level 3 carpet is 512. The number of geometry objects for a level-N carpet is 8^N. This means that for the maximum level 5 set by the method create_carpet, the resulting geometry has 32,768 geometry objects.

Menger Sponge

The methods for the Sierpinski carpet readily generalize to 3D. However, in 3D, you need to be careful not to generate more objects than your computer can handle. The method assumes that you have created a 3D Component and that you have declared an integer scalar variable counter.

The following method, create_sponge, initiates the recursion.


```
int level = (int) model.param().evaluate("mslevel");
if (level < 1)
  error("Sponge level needs to be at least 1.");
if (level > 3)
  error("Sponge level needs to be at most 3.");
```

```
counter = 0;
model.component("comp1").geom("geom1").feature().clear();
model.component("comp1").geom("geom1").autoRebuild("off");
double cx0 = 0, cy0 = 0, cz0 = 0;
double si0 = 1;
sponge(level, cx0, cy0, cz0, si0);
model.component("comp1").geom("geom1").runPre("fin");
```

The method sponge, shown below, is called by the above method and recursively creates a Menger sponge.

```
int 1 = level;
double posx, posy, posz, si1;
String strix;
int 11;
for (int i = 0; i < 3; i++) {
  for (int j = 0; j < 3; j++) {
    for (int k = 0; k < 3; k++) {
      posx = cx+i*si-si;
      posy = cy+j*si-si;
      posz = cz+k*si-si;
      strix = toString(i)+toString(j)+toString(k);
      if ((Math.abs((i-1))+Math.abs((i-1))+Math.abs((k-1))) > 1)  {
        if (1 == 1) {
          counter = counter+1;
model.component("comp1").geom("geom1").create("blk"+strix+"C"+toString(counter
), "Block");
with(model.component("comp1").geom("geom1").feature("blk"+strix+"C"+toString(c
ounter)));
            set("base", "center");
           set("size", new String[]{toString(si), toString(si), toString(si)});
            set("pos", new double[]{posx, posy, posz});
          endwith();
model.component("comp1").geom("geom1").feature("blk"+strix+"C"+toString(counte
r)).label("Block"+strix+"C"+toString(counter));
        } else {
          11 = 1-1;
          si1 = si/3;
          sponge(l1, posx, posy, posz, si1);
       }
     }
   }
 }
}
```





In this case, the number of geometry objects grows with the level N as 20^N and the level-2 sponge shown above has 400 block geometry objects.

Note that if you have any of the add-on products for additional CAD functionality, you can export these geometry objects on standard CAD formats. Without add-on products, you can export the meshed geometry to any of the supported mesh formats.

Mesh Information and Statistics

You can retrieve a variety of mesh information and statistics quantities, such as element quality, the total number of elements, mesh volume, and so on. The figure below shows part of an application displaying such information.

Number of elements:	79492
Tet min quality:	0.1405
Tet mean quality:	0.6532
Tet min volume:	2.815E-13
Mesh volume:	6.354E-6

Assuming that you would like to link the various mesh quantities to variables declared under the **Declarations** node, the corresponding method code would include the following lines of code:

```
a = model.component("comp1").mesh("mesh1").getNumElem();
b = model.component("comp1").mesh("mesh1").getMinQuality("tet");
c = model.component("comp1").mesh("mesh1").getMeanQuality("tet");
d = model.component("comp1").mesh("mesh1").getMinVolume("tet");
e = model.component("comp1").mesh("mesh1").getVolume("tet");
```

For more information on available mesh quantities, see the Reference Manual.

Accessing Higher-Order Finite Element Nodes

The extended mesh data structure contains information related to the finite element method including, for example, the placement of higher-order element nodes. The extended mesh information is contained in the class XmeshInfo and provides information about the numbering of elements, nodes, and degrees of freedom (DOFs) in the extended mesh and in the matrices returned by the Assemble feature and the solvers. For detailed information on XmeshInfo, see the *Programming Reference Manual*.

The following example method illustrates how to use the extended mesh information to plot higher-order nodes in a few important special cases. The example covers cases with one model component, one geometry, and a subset of physics combinations. If you apply it to other cases, you will get an error message.

// Note that this method is only implemented for one component and one geometry and doesn't work for all physics combinations.

```
String stdTag = model.study().uniquetag("stdfe");
model.study().create(stdTag);
model.study(stdTag).label("FE Nodes Study "+stdTag.substring(5));
model.study(stdTag).showAutoSequences("sol");
String solTag = model.sol().uniquetag("sol");
model.sol().create(solTag);
model.sol(solTag).create("st1", "StudyStep");
model.sol(solTag).create("v1", "Variables");
SolverFeature step = model.sol(solTag).feature("v1");
XmeshInfo xmi = step.xmeshInfo();
try {
  XmeshInfoNodes testnodes = xmi.nodes();
} catch (Exception e) {
 error("Cannot access finite element data. Only implemented for one geometry and
stationary studies.");
XmeshInfoNodes mynodes = xmi.nodes();
double[][] coords = mynodes.gCoords();
int[] coordsize = matrixSize(coords);
int sdim = 0;
if (coordsize[0] == 3) {
```

```
sdim = 3;
} else if (coordsize[0] == 2) {
  sdim = 2:
} else
  error("The geometry of the first component is not 2D or 3D.");
String mesh = "mesh"+stdTag;
model.result().dataset().create(mesh, "Mesh");
String pgTag = model.result().uniquetag("pgfe");
ResultFeature pg = model.result().create(pgTag, sdim);
model.result(pgTag).label("FE Nodes Plot "+pgTag.substring(4));
String nodes = pgTag;
model.result(nodes).create("mesh", "Mesh");
if (sdim == 3) {
 with(model.result(nodes).feature("mesh"));
    set("data", mesh);
    set("meshdomain", "volume");
  endwith();
} else {
  with(model.result(nodes).feature("mesh"));
    set("data", mesh);
    set("meshdomain", "surface");
  endwith();
with(model.result(nodes).feature("mesh"));
  set("elemcolor", "none");
  set("wireframecolor", "gray");
  set("elemscale", 0.999);
endwith();
with(model.result(nodes));
  set("edges", true);
  set("data", mesh);
endwith();
ResultFeature plot = pg.create("pt1", "PointData");
plot.set("pointdata", coords)
  .set("coloring", "uniform")
  .set("color", "red");
plot.run();
selectNode(pg);
```

Comments

The first few lines of the method set up a solver step object step, which is used to extract the extended mesh information. The extended mesh information, which contains information on the higher-order nodes, is extracted in the line

```
XmeshInfo xmi = step.xmeshInfo();
The lines
  XmeshInfoNodes mynodes = xmi.nodes();
  double[][] coords = mynodes.gCoords();
```

```
int[] coordsize = matrixSize(coords);
```

access and store the finite element node coordinates in a 2-by-coordsize (2D) or 3-by-coordsize (3D) array.

The following code segments set up a mesh data set and an associated mesh plot.

The last section uses the low-level PointData plot type to visualize the finite element nodes. For more information on this plot type, see "Points in 3D" on page 153.

Accessing System Matrices and Vectors

You can gain low-level access to the finite element system matrices and vectors by adding nodes of the types Assemble and Input Matrix under a Study node.

The example below shows how to set up and solve a 2D electrostatics problem on the unit square [0,1]-by-[0,1]. After the original problem is solved, the load vector is modified at a user-defined coordinate. The code searches for the degree of freedom closest to the target user-defined coordinate and modifies the load vector to a user-defined value. The physical interpretation of the modified load is that of an added volume charge.

To run the example code below, first use the Model Wizard to create a blank model. Then, add a new method and paste the example code below. Finally, run the method. You can try changing the variable values in the Initializations section at the beginning of the code and run again.

```
// Initializations
double x load = 0.2; // Target x-coordinate for load
double y load = 0.2; // Target y-coordinate for load
double load = 1e-9; // Load, volume charge
double dist = 10.0; // Distance to (x load,y load) from degree of freedom
int index = 0; // Index of the degree of freedom closest to (x load,y load)
// Clear any previous model.
clearModel(model);
// Create a new model component.
model.modelNode().create("comp1");
// Create the 2D geometry.
model.geom().create("geom1", 2);
model.geom("geom1").feature().create("sq1", "Square");
model.geom("geom1").run();
// Create the mesh.
model.mesh().create("mesh1", "geom1");
model.mesh("mesh1").feature().create("fre1", "FreeTri");
model.mesh("mesh1").run();
```

```
// Setup the electrostatics physics problem.
model.physics().create("es", "Electrostatics", "geom1");
model.physics("es").feature().create("gnd1", "Ground", 1);
model.physics("es").feature("gnd1").selection().set(new int[]{1});
model.physics("es").feature().create("sfcd1", "SurfaceChargeDensity", 1);
model.physics("es").feature("sfcd1").selection().set(new int[]{4});
// Add a varying distributed charge density along the rightmost boundary.
model.physics("es").feature("sfcd1").set("rhoqs", "1e-9*y");
model.component("comp1").physics("es").feature("ccn1").set("epsilonr mat",
"userdef");
model.component("comp1").physics("es").feature("ccn1").set("epsilonr", "1");
// Change to 1st order shape functions, to keep things simple.
model.component("comp1").physics("es").prop("ShapeProperty").set("order electr
icpotential", 1);
// Create and run the study.
model.study().create("std1");
model.study("std1").feature().create("stat1", "Stationary");
model.study("std1").run();
// Create a 2D plot group with a surface plot for the original problem.
model.result().create("pg1", 2);
model.result("pg1").set("data", 'dset1");
model.result("pg1").feature().create("surf1", "Surface");
selectNode(model.result("pq1")); // Set focus on the plot node.
// Create a reusable solver feature variable.
SolverFeature solft:
model.study().create("std2"); // Create a Study 2 node.
model.sol().create("sol2"); // Create a data set Solution 2.
// Create a Solver configurations node under Study 2
model.sol("sol2").study("std2");
model.sol("sol2").create("st1", "StudyStep"); // Create a Compile Equations
solft = model.sol("sol2").feature("st1"); // Assign solver step to variable
solver.
solft.set("study", "std2");
model.sol("sol2").create("v1", "Variables"); // Create a Dependent Variables
node
solft = model.sol("sol2").feature("v1");
model.sol("sol2").attach("std2");
model.sol("sol2").create("a1", "Assemble"); // Add an Assemble node.
solft = model.sol("sol2").feature("a1");
// Now define which system matrices should be output (Non-Eliminated Output).
// L=Load vector, K=Stiffness matrix, M=Constraint vector, N=Constraint Jacobian
// For more information see the Programming Reference Manual.
solft.set("L", "on");
solft.set("K", "on");
solft.set("M", "on");
solft.set("N", "on");
```

```
//Create a Stationary Solver 2 node: Study 2>Solver Configurations>Solution 2.
model.sol("sol2").create("s2", "Stationary");
// Create an Input Matrix node under Stationary Solver 2.
solft = model.sol("sol2").feature("s2").create("im1", "InputMatrix");
// Define which system matrices should be input.
solft.set("L", "on");
solft.set("K", "on");
solft.set("M", "on");
solft.set("N", "on");
// Find the degree of freedom coordinate closest to the target coordinate.
solft = model.sol("sol2").feature("v1");
XmeshInfo xmi = solft.xmeshInfo();
XmeshInfoDofs mydofs = xmi.dofs();
double[][] coords = mydofs.gCoords();
int[] coordsize = matrixSize(coords);
double new dist = dist;
for (int k = 0; k < coordsize[1]; k++) {
  new dist =
Math.sqrt((coords[0][k]-x load)*(coords[0][k]-x load)+(coords[1][k]-y load)*(co
ords[1][k]-y_load));
  if (new_dist < dist) {</pre>
    index = k;
    dist = new dist;
  }
}
// Run the solver sequence up to and including the Assemble node.
model.sol("sol2").runFromTo("st1", "a1");
// Extract system matrices and vectors.
solft = model.sol("sol2").feature("a1");
// K
int KM = solft.getM("K");
int KN = solft.getN("K");
int KNnz = solft.getNnz("K");
int[] Ki = solft.getSparseMatrixRow("K");
int[] Kj = solft.getSparseMatrixCol("K");
double[] Kv = solft.getSparseMatrixVal("K");
// For more information, see the Programming Reference Manual.
// L
double[] Lv = solft.getVector("L");
// N
int NM = solft.getM("N");
int NN = solft.getN("N");
int NNnz = solft.getNnz("N");
int[] Ni = solft.getSparseMatrixRow("N");
int[] Nj = solft.getSparseMatrixCol("N");
double[] Nv = solft.getSparseMatrixVal("N");
// M
double[] Mv = solft.getVector("M");
```

```
// Modify the load
Lv[index] = load;
// Put the system matrices and vectors back in again.
solft = model.sol("sol2").feature("s2").feature("im1");
solft.createSparseMatrix("K", KM, KN, KNnz, true);
solft.addSparseMatrixVal("K", Ki, Kj, Kv);
// L
solft.createVector("L", Lv.length, true);
solft.setVector("L", Lv);
// N
solft.createSparseMatrix("N", NM, NN, NNnz, true);
solft.addSparseMatrixVal("N", Ni, Nj, Nv);
// M
solft.createVector("M", Mv.length, true);
solft.setVector("M", Mv);
// Solve Stationary Solver 2 with the modified system.
model.sol("sol2").runFromTo("s2", "s2");
// Plot the results.
model.result().create("pg2", "PlotGroup2D");
with(model.result("pg2"));
 set("data", "dset2");
endwith();
model.result("pg2").create("surf1", "Surface");
// Plot electric potential and original mesh overlayed with no smoothing.
with(model.result("pg2").feature("surf1"));
 set("resolution", "norefine");
 set("smooth", "none");
endwith();
model.result("pg2").create("surf2", "Surface");
with(model.result("pg2").feature("surf2"));
 set("resolution", "norefine");
 set("coloring", "uniform");
 set("color", "gray");
 set("wireframe", true);
endwith();
model.result("pg2").run();
selectNode(model.result("pg2")); // Set focus on the plot node.
```

Comments

In the previous example, "Accessing Higher-Order Finite Element Nodes" on page 199, the XmeshInfoNodes methods are used to access finite element nodes that have the same length as the number of finite element nodes. In this example, the XmeshInfoDofs methods are used to access the degrees of freedom vector, which has the same length as the load vector.

Note that only the load vector is modified. The other matrices and vectors are merely extracted and then put back into the system again.

Using Built-In Methods from an External Java Library

When developing an external Java[®] library to be used in the Application Builder, it is possible to call the built-in methods from the external library. In order to do so, the com.comsol.api JAR-file needs to be added to the project build path, and the classes that call the methods need to extend the ApplicationLanguageBase class. The following steps explain how to create a simple example JAR library when using the Eclipse[®] integrated development environment:

- Start Eclipse[®].
- 2 Create a new Java® project. Enter JavaLibDemo as the project name and click Next.
- 3 Go to the **Libraries** tab and click **Add External JARs**. Add the JAR-file com.comsol.api_1.0.0.jar from the plugins directory under the COMSOL Multiphysics installation directory; for example
 - C:\Program Files\COMSOL\COMSOL54\Multiphysics\plugins
- 4 Click Finish.
- 5 Right-click the src folder in your Eclipse project and select New... Package. Enter demo as the package name and click Finish.
- 6 Right-click the demo package in your **Eclipse** project and select **New... Class**. Enter Hello as the class name.
- 7 Click on Superclass > Browse... and select ApplicationLanguageBase. Click OK and Finish.
- 8 In the editor window for the Hello class, add the following method and save the file:

```
public static void hello() {
   alert("Hello!");
}
```

- 9 Right-click the JavaLibDemo project and select Export... > Java > JAR file. Select the export destination JAR-file and click Finish.
- **10** Start COMSOL Multiphysics and create a **Blank Model**.
- II In the Application Builder, under the application tree, right-click **Libraries** and select **External Java Library**. In the **Settings** window, click **Browse...** and select the JAR-file previously exported from Eclipse[®].
- 12 In the Application Builder, add a form, button, and method for the button.

- I3 In the Method editor for the method, add the following code: Hello.hello();
- 4 Click **Test Application** and click the button in the application to verify that the alert method is invoked.

Measuring the Java Heap Space Memory

Software components that are based on Java[®], such as certain parts of COMSOL Multiphysics, are predefined to use only a limited amount of memory. This limit, the Java[®] heap space, is specified during startup. Note that the Java[®] heap space only affects certain parts of the software and not, for example, meshing or solvers. By default, COMSOL Multiphysics allocates 2 GB of Java[®] heap space memory. See the *Reference Manual* for information about increasing the available heap space memory.

In a method, you can measure the amount of heap space memory currently in use. For example, while debugging, you can add the following code:

```
Runtime runtime = java.lang.Runtime.getRuntime();
runtime.gc();
debugLog("Used memory (MB):
"+(runtime.totalMemory()-runtime.freeMemory())/(1024*1024));
```

The first line adds a request to run the Java® garbage collector.

In order to monitor the memory usage in an application, you can replace debugLog with message.

Time-Limited and Hardware-Locked Applications

By writing a few lines of code, you can make your application expire after a set date and lock the application to specific hardware.




The example MPH-file used in this section is available in the Application Gallery at https://www.comsol.com/model/70151

PASSWORD PROTECTION

The settings of an application can in principle be read from the file system by a user, including method code. By making your application password protected for editing, the method code will no longer be readable. This setting is available from the root node in either the model tree or the application tree, as shown in the

figure below.



Before implementing a time limit or hardware lock, as described below, make sure your application is password protected. Password protection for running the application is not required for this purpose.

TIME-LIMITED APPLICATION


To have an application expire after a specific date, create a method as follows:

```
java.text.SimpleDateFormat f = new java.text.SimpleDateFormat("yyyy-MM-dd");
//java.text.SimpleDateFormat f = new java.text.SimpleDateFormat("MM/dd/yyyy");


ok = false;
try {
    java.util.Date d = f.parse(timeoutDate);
    long currentTime = timeStamp();
    long timeoutTime = d.getTime()+24*60*60*1000; // To allow running until the end of the day
    if (currentTime < timeoutTime) {
        ok = true;
    }
}
catch (java.text.ParseException e) {
    debugLog("Failed to parse timeout date "+timeoutDate);
    debugLog(e.getMessage());
}</pre>
```

In this method, you need to decide on a date format. Two format examples are shown and you can uncomment the line corresponding to the format you would like to use. For more details on available formats, see the Java[®] documentation for

SimpleDateFormat. This method has one string input argument, timoutDate, and one Boolean output argument, ok, as shown below.



The expiration date is defined as a string variable, trial_date, in **Declarations>String**, as shown below.



HARDWARE-LOCKED APPLICATION

To lock an application to the MAC address of a specific network card on a computer, create a method as follows:

```
ok = false;
try {
    java.util.List < java.net.NetworkInterface > nis =
    java.util.Collections.list(java.net.NetworkInterface.getNetworkInterfaces());
    for (java.net.NetworkInterface ni : nis) {
        StringBuilder macString = new StringBuilder();
        byte[] macBytes = ni.getHardwareAddress();
        if (macBytes!= null && macBytes.length > 0) {
            for (byte b : macBytes) {
                if (macString.length() > 0) {
                     macString.append(":");
                }
                macString.append(String.format("%02x", b));
        }
}
```

```
if (contains(allowedAddresses, macString.toString())) {
    ok = true;
    break;
    }
}
catch (java.net.SocketException e) {}
```

In order to check the MAC address when running an application, you need to enable **Allow access to network sockets** under **Security** in **Preferences**. However, for a compiled application, no security changes are needed.

This method has one array 1D string input argument, allowedAddresses, and one Boolean output argument, ok, as shown below.



The MAC address is defined as a string array mac_addresses in **Declarations>Array ID String**, as shown below.

Settings Array 1D String					
List of Variables					
→ Name	Initial values	New element value	Description		
mac_addresses	{'34:17:eb:d2:5e:14'}		MAC address (needs to be lowercase)		

Note that you can provide a list of MAC addresses to allow use on a computer with multiple network cards or multiple computers.

CHECKING FOR ALLOWED DATE AND HARDWARE

To check for both the MAC address and the date, create a method check_allowed_to_run as follows:

```
if (!check_mac_address(mac_addresses)) {
   alert("You are not allowed to run this application on this computer.",
"COMSOL");
```

```
exit();
}

if (!check_date(trial_date)) {
    alert("The trial for this application has expired "+trial_date, "COMSOL");
    exit();
}
```

The figure below shows this method in the Method editor.


You can call this type of method at startup of the application, for example, as an On load event for the main form of the application. In the Tuning Fork example application, available in the Application Library of COMSOL Multiphysics, there is a method p_init_application that is run as an On load event for the main form. In this case, the method p_init_application can be edited as follows:

```
check_allowed_to_run();
if (model.sol("sol1").isEmpty()) {
   solution_state = "nosolution";
}
else {
   solution_state = "solutionexists";
}
zoomExtents("graphics1");
```

Notice the call to the method check_allowed_to_run in the first line. The figure below shows this method in the Method editor.



The method p_init_application is then called as an **On load** event. This is specified in the **Settings** window of the main form, as shown in the figure below.



Index

	ID array 12, 31, 136	writing 183
	2D array 13, 31, 136	Blank Model 29
Α	accessing 201	boolean
	add-in 23. 148	data type 8, 29
	alert 112, 118	Boolean variable 8
	anisotropic diffusion coefficient 33	conversion 134
	Annotation Data plot type 161	boundary condition 41
	Application Builder 55	built-in method library 91
	Application Builder Reference Manual	button
	124	object 65
	application example	C libraries
	tubular reactor 110	external /23
	application object 7, 25, 55, 91	card stack object 66
	app variable 57	carriage return 12
	classes 57	catch 17
	application tree 55	C-code
	array 12	linking / 23
	methods 136	char
	array ID	data type 8
	object 84	character
	array 2D	data type 8
	object 84	character stream 178
	array input object 65	characters
	Arrow Data plot type 159, 160	special 177
	assignments 8	check box object 66
	auto complete 18	choice list 57, 86, 116
	automatic solver sequence 47	methods 86
	axisymmetric property 29	object 84
В	backslash 12	classes
	backspace 12	application object 57
	basic data type 29	code completion 18
	big endian 185	code generation 18
	binary file	collection methods 145
	processing 185	color 59
	reading 184	of user interface component 58
	=	

combo box object 67	Declarations 12, 14, 56
Compact History 52	deformation plot 34
Compile Equations node 45	degrees of freedom 199
computation time 133	Dependent Variables node 45
last /32	description 17
Compute 46	parameter 17, 34
COMSOL Desktop 51	variable 17
COMSOL Help Desk 53	Developer tab 150
COMSOL Multiphysics 7, 25	dialog box 111, 112
confirm 11, 112, 118	diffusion coefficient
contour plot 48	anisotropic 33
contour plot data 180	dimension
control flow statements 15	spatial 28
conversion	disable form object 59, 63, 64, 116
between data types 9	Display Name
methods 134	for choice list 116
coordinate information 190, 191	double 9
Copy as Code to Clipboard 29	data type 8, 29
creating	variable conversion 134
feature node 37, 41	double quotation mark //
model object 28, 51	E edge
CSV-file 162, 170	parameterization 186
curve	Editor Tools window 35
interpolation 179	Electric Currents 50
parameterization 186	element
cut point	order / 99
data set 33, 92	size 32, 39
data display object 68	elementary math functions 15
data set 48, 151	email
Data Source	class 107
class 57, 84	methods 107
data types	preferences 109
primitive 8	email attachment
date and time methods 131	export 107
debug	report 107
methods 123	table <i>10</i> 7
Debug Log window 123	embedded model 51
declaration	enable form object 57, 59, 63, 64, 116

D

equation	class <i>58</i> , <i>62</i>	
object 69	declarations 14	
error dialog box 17	list methods 89	
example code 91, 150	form collection 70	
Excel® file 49, 100, 162, 167, 171	form method 23	
exception	form object 69	
handling 17	class 58, 63	
exit 122	list methods 89	
application 122	types 64	
expiration date for application 206	formfeed 12	
export	Fully Coupled nod	e 46
email attachment 107	G general properties	59
external C libraries 123	generating code 18	
external Java® library 205	Geometry node 3	
face	geometry object 3	
parameterization 188	names 191	
feature node	get 29	
creating 37, 41	global method 23	
removing 38, 41	global parameter 3	34
file	graphics	
methods 96	object 70, 111	
name 100	view 117, 119	
open 103	grid data set 150	
reading 162	GUI command	
writing to 162	methods 122	
File Declaration 165	GUI related metho	ods III
file import 165	H hardware lock 206	
file import object 69	heap space 206	
file open	Heat Transfer in S	olids 40, 50
system method 103	higher-order eleme	ent nodes 199
file scheme	history	
syntax 96, 165	model 52	
finite element	HTML	
accessing 199	report 119	
system matrix 201	hyperlink object 7	1
vector 201	if-else statement /	5
floating point number 8	image object 72	,
for loop 16, 64, 90	import	
form	import	

F

file 165	K	keyboard shortcut
information card stack object 72		Ctrl+Space 18
information node 133	L	legend 33, 34
inherit		license
color 60		check out 123
input field object 73		method 93
integer		lighting 157
data type 8, 29		Line Data plot type 154
variable conversion 134		line object 75
interpolation curve 179, 186		list box object 75
interpolation function 186		literals 8
Introduction to Application Builder 7,		little endian 185
18, 22, 23, 55, 87, 96, 133, 162		load vector 204
Introduction to COMSOL Multiphysics		loading
22, 25		model 51, 92
isosurface 150		local method 23
item		locking application to hardware 206
class 58		log object 76
list methods 89		looplevel property 49
menu 83		
object 83	М	MAC address 206
ribbon 83		main application class 57, 60
toolbar 83		main user interface component classes
iterative solver 45		58
Iterator class and method 41		Main Window
jagged arrays 12		class 58, 61
Java		node 58
Documentation, model object class		material
structure 53		link 33
math library 15		tag 87
programming language 7, 8, 91		Materials node 42
syntax 9		math functions 15
unary and binary operators 9		maximum value 49
Java®		menu
character stream 178		item 83
classes for read/write 177		mesh
external library 205		information and statistics 198
heap space 206		mesh element size 32, 39
Troup space 200		Mesh node 39

J

message log object 76, 114	form object 55, 57
message method 118	in application object 57
method 7, 91	method 24
form 23	scoping 27
get 29	shortcut 14, 55
global 23	user interface component 55, 57
local 23	network card 206
name 24	newline 11, 12
Method class 89	node
Method editor 91	finite element 199
using 7, 18	nonlinear solver 46
method name 24	normal
Microsoft® Word® format 119	surface 157, 158
model 51	numerical
loading 51, 92	Derived Values 49
saving 51, 92	• operating system
Model Builder 25	methods 103
model component 28	operators 36
model data access 22	Java 9
model history 52, 153	model object 36
recording 52	OS commands 103
turning off 153	P parameter 17, 33, 34, 49
Model Java-file 52	method 16, 23
Model M-file 52	real and imaginary part 35
model object 7, 25, 42, 55, 91	parameterization
class structure 53	edge 186
tag 25	face 188
model tag 28	parameterized solution 49
model tree 25	parsing
node 41, 42	text file 177
model utility methods 52, 91	physics interface 40, 44
Model Wizard 29, 51	play sound 104
models, working with multiple 51	plot
MPH file 51, 91, 122	group <i>34, 118</i>
multiphysics 50	mesh element nodes 92
Multiphysics node 50	point trajectories 92
multiple models 51	surface 37, 48
name	table surface 49
form 55 57	table surface +/

useGraphics 111	Record Code 20, 46
Plot Group node 48	recursion 194
plot type	recursive loop 194
Annotation Data 161	Reference Manual 199
Arrow Data 159, 160	removing
Line Data 154	feature node 38, 41
Point Data 152, 153, 201	report 110
Surface Data 155, 156, 157	email attachment 107
Tube Data 159	HTML 119
Point Data plot type 152, 153, 201	Microsoft® Word® format 119
point trajectories plot 92	request 113, 118
precedence, of operators 9, 36	reset
primitive data types 8	model history 52
printing	Results node 48
graphics 122	results table object 77, 115
programming examples 91, 150	RGB color 60
Programming Reference Manual 25, 47,	ribbon item 83
91, 92, 193, 199	s save application 122
progress 125	save as 122
dialog box 126, 130	saving
methods 125	model 51, 92
progress bar object 76, 127, 129, 130	scalar
properties	object 84
general 59	scene light 122
property and property values 29	sectionwise
radio button object 77	format 179, 182
ragged arrays 12, 32	sectionwise format 179
reading	selection input
binary file 184	object 78
CSV-file 163	selections 191
Excel® file 167	set 29
file 162	setIndex 29
matrix file 172	shortcuts 14, 55
Microsoft Excel® Workbook file 167	Shortcuts node 14
spreadsheet 163	single quotation mark //
text file 177	sleep 133
text file to string 174	slider object 79
real and imaginary part	SMTP 109
of parameter 35	solution

R

data 150	system vector 201	
data structure 45	T tab 12	
parameterized 49	table 49	
Solution node 45	email attachment 107	
Solver Configurations node 44	object 80, 114	
solver sequence 44	Table node 49	
spacer object 79	table surface plot 49	
spatial dimension 28	tag 57	
special character / /	model 28	
Java 52	model object 25	
special characters 177	physics interface 40	
sphere 150	temporary folder	
spreadsheet 163	location 171	
format 96, 172, 173, 179	text file 162	
Stationary Solver node 45	reading 177	
Stationary study step 44	writing 177	
status bar 125	text label object 81	
stream	text object 80	
character 178	time /3/	
String	time-limited application 2	06
data type 10, 29	title 112	
methods 144	toggle button object 81	
string variable 49	toolbar	
conversion 135	item 83	
methods 144	object 82	
strings	transparency 120, 122	
comparing / /	transparent	
concatenating 10	color 60	
Study node 44	try and catch 17	
subform object 69	Tube Data plot type 159	
surface	type declaration 54	
parameterization 188		
Surface Data plot type 155, 156, 157	u unit 35	
surface normal 157, 158	object 82	
surface plot 37, 48	Unit List 57	
system matrix	unit set	
accessing 201	methods 86	
system methods 103	object 84	
OS commands 103	unit sphere 150	

```
Unit System 35
    username 103
  variable 23
      description 17
      name completion 19
    video object 82
    view
      graphics 117, 119
    visualization 150
w web page object 83
    while loop 16
    with statement 16
    writing
       CSF-file 170
       Excel file 171
      matrix file 173
       string to text file 176
      text file 177
      to binary file 183
      to file 162, 171
```

z zoom extents 118, 122